

### BOLTLOCKER PRIMER PART NO. 49674

#### PHYSICAL PROPERTIES

Solvent Based .....	Acetone
Appearance.....	Green Liquid
Boiling Point (DIN 51751).....	210°F
Flash Point (TCC) .....	-4°F
Density (g/cc) .....	0.786
Viscosity (cP @ 68°F) .....	2 cP
Odor.....	Pungent
NFPA Flammability Rating.....	4*

\*Highly Flammable



#### DESCRIPTION

**Dynatex® Boltlocker Primer** is a highly reactive surface activator designed to speed cure rates of **Dynatex® Anaerobic Adhesives**. **Dynatex® Boltlocker Primer** is designed for use in bonding applications where speed is essential. Parts should be as clean as possible before application to ensure optimal adhesive performance, but **Dynatex® Boltlocker Primer** can also act as a cleaner in situations where part preparation is impossible.

#### FEATURES

- Increases cure of **Dynatex®** threadlockers by 50%
- Increased strength
- Cleans and prepares surfaces for bonding
- Insures cold-weather curing

#### TYPICAL APPLICATIONS

- For inactive metal surfaces \*
- Large gaps
- Cold temperatures

#### \*Inactive Metals

Bright platings, anodized surfaces, titanium, zinc, pure aluminum, stainless steel and cadmium.

#### GENERAL INSTRUCTIONS

Surfaces to be bonded should be clean and dry. Spray or wipe **Dynatex® Boltlocker Primer** onto metal surface prior to applying **Dynatex®** anaerobic adhesive.

#### HEALTH PRECAUTIONS

**Dynatex® Boltlocker Primer** is highly reactive and should be stored away from heat, open flame, or ignition sources. Keep containers tightly closed. Use in a well ventilated area. Wash exposed areas with copious amounts of soap and water for at least 15-20 minutes. Contact a physician. Consult MSDS prior to use.

## STORAGE AND SHELF LIFE

**Dynatex® Boltlocker Primer** should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F to 82°F unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. Store in accordance with NFPA 30B for level 3 aerosol. **Dynatex® Boltlocker Primer** has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 120°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## TRANSPORTATION INFORMATION

### DOT Road Shipment Information

Proper Shipping Name .....Aerosols, flammable  
DOT Description ...Consumer Commodity ORM-D  
UN Number .....UN1950  
Hazard Class or Division ..... 2.1  
Packing Group ..... None  
DOT Reportable Quantity ..... Acetone  
(CAS #67-64-1) is reportable at 5000 lbs.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it the user's responsibility to determine suitable of use. Since the supplier cannot know all the uses, or the conditions of use to which there products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The users exclusive remedy and the suppliers sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** A division of Accumetric, LLC

**Dynatex**  
350 Ring Road  
Elizabethtown  
Kentucky 42701 USA  
(800) 999-2937  
TEL (270) 769-5557  
FAX (270) 769-6418  
*Outside U.S.*  
TEL +1(270) 769-5557  
FAX +1(270) 769-6418

**Accumetric Asia Pacific, LTD**  
18 Kitpanit Bldg. 5<sup>th</sup> Floor  
#502 Patpong Road  
Suriyawong, Bangrak  
Bangkok, 10500 Thailand  
TEL (662) 634-3060  
FAX (662) 634-3066

Email: [sales@dynatexinc.com](mailto:sales@dynatexinc.com)  
Website: [www.dynatexinc.com](http://www.dynatexinc.com)