

## **Product Information Sheet**



## **Cast Blast** #16-048 Cast Iron Gray

A professional grade coating that restores rebuilt cast iron engine parts to their original luster. Hi solid formulation allows for more coverage than standard spray. Resists light cleaning solvents such as mineral spirits.

Suggested Uses:

Used or rebuilt cylinder heads

Engine blocks Water pumps

Any other cast iron parts Assembly line piece work

Industrial

Benefits:

Fast dry

Restores cast iron parts to original OEM finish

Stops flash rusting Non-abrasive

Durable

Can be top coated with OEM colors

Packaging:

**UPC** Code

Cans per case

Shipping weight per case

Container Label weight

**Shipping Classification** 

**Hazard Class** 

043281000048

6

7 lbs.

16 fluid ounce can 12 ounces (340 grams)

Consumer Commodity ORM-D, UN 1950

2.1

Properties:

Flammability "Extremely Flammable"

Flash point Specific Gravity 0.79 Solids Content 21%

VOC content ~58%, cannot exceed 80% MIR value ~1.52, cannot exceed 1.90

HAPs content ~25% 40-100F Storage Temperature Application Temperature 50-90F Hard Cure 12 hours Durability Good **Abrasion Resistance** Good Gasoline Resistance No  $250^{0} \, F$ Heat Resistance

Resin System Acrylic lacquer

Guaranteed for 2 years Shelf life Food contact rating Category 21: Acceptable Dry Time\*:

To touch 7 minutes 20 minutes To recoat

\*At 72° F, 50% humidity, 1.5 mil thickness

\*\*Curing/Recoat time is extended with multiple coats and excessively thick coats \*\*

Gloss\*: Flat, <15

\*as measured on a 60° gloss meter

## **Available Colors:**

Phone: 815-895-9101 or 800-435-4482 815-895-8475 or 800-343-4258 www.seymourpaint.com