

## Safety Data Sheet

Printing date 02/08/2016

Revised On 01/29/2016

**1 Identification of the substance and manufacturer**

**Trade name:** HOT SPOT CAST BLAST  
**Product code:** 0000162668  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178  
 Phone: 815-895-9101 www.seymourpaint.com  
**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

**2 Hazard(s) identification****Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT SE 3 H336 May cause drowsiness or dizziness.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

**Signal word****Hazard statements**

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of damaging fertility or the unborn child.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
**Precautionary statements** Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 If skin irritation occurs: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of water.  
 If eye irritation persists: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Protect from sunlight. Store in a well-ventilated place.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

**3 Composition/information on ingredients****Chemical characterization: Mixtures****Chemical Description:**

This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

67-64-1	Acetone	23.21%
74-98-6	propane	18.91%
108-88-3	Toluene	18.33%
106-97-8	n-butane	11.11%
64742-89-8	VM&P Naphtha	6.34%
7727-43-7	barium sulfate, natural	6.12%
68186-94-7	Iron Manganese Oxide Black	2.77%
1330-20-7	xylene (mix)	1.11%
108-65-6	PM acetate	1.05%

**4 First-aid measures****After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**Rinse out mouth and then drink plenty of water.  
Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

## Safety Data Sheet

Printing date 02/08/2016

Revised On 01/29/2016

Trade name: HOT SPOT CAST BLAST

(Contd. of page 1)

**Most important symptoms and effects:**

Dizziness

**Indication of any immediate medical attention needed:**

No further relevant information available.

**5 Fire-fighting measures****Extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppmTLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppmLong-term value: 594 mg/m<sup>3</sup>, 250 ppm

BEI

**74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F in TLVs and BEIs book

**108-88-3 Toluene**

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppmLong-term value: 375 mg/m<sup>3</sup>, 100 ppmTLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm

BEI

**106-97-8 n-butane**REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppmTLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm**7727-43-7 barium sulfate, natural**PEL (USA) Long-term value: 15\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

TLV (USA) Long-term value: 5\* mg/m<sup>3</sup>

\*inhalable fraction; E

**1330-20-7 xylene (mix)**PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV (USA) Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**108-65-6 PM acetate**

WEEL (USA) Long-term value: 50 ppm

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

## Safety Data Sheet

Printing date 02/08/2016

Revised On 01/29/2016

Trade name: HOT SPOT CAST BLAST

(Contd. of page 2)

**108-88-3 Toluene**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

<b>Hygienic protection:</b>	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
<b>Breathing equipment:</b>	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
<b>Hand protection:</b>	Nitrile gloves.
<b>Eye protection:</b>	Protective gloves. The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

**9 Physical and chemical properties**

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	-110 °C (-166 °F)
<b>Flash point:</b>	-19 °C (-2 °F)
<b>Flammability (solid, gas):</b>	Extremely flammable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.5 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Vapor pressure:</b>	Not determined.
<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.
<b>Partition coefficient: n-octonal/water:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>VOC content:</b>	584.1 g/l / 4.87 lb/gl
<b>VOC content (less exempt solvents):</b>	58.3 %
<b>MIR Value:</b>	1.29
<b>Solids content:</b>	19.0 %

**10 Stability and reactivity**

<b>Reactivity:</b>	Stable at normal temperatures.
<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
<b>Chemical stability:</b>	Not fully evaluated.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

(Contd. on page 4)

## Safety Data Sheet

Printing date 02/08/2016

Revised On 01/29/2016

Trade name: HOT SPOT CAST BLAST

(Contd. of page 3)

**1330-20-7 xylene (mix)**

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

**108-65-6 PM acetate**

Oral	LD50	8500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

**Information on toxicological effects:** No data available.  
**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.

**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

108-88-3	Toluene	3
1330-20-7	xylene (mix)	3

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**UN-Number** UN1950  
**DOT** N/A  
**DOT** UN1950  
**ADR** Consumer Commodity ORM-D  
**Transport hazard class(es):** Aerosols, flammable  
**Class** 1950 Aerosols  
**Marine pollutant:** 2.1  
**Special precautions for user:** No  
**EMS Number:** Warning: Gases  
**Packaging Group:** F-D,S-U  
**UN "Model Regulation":** --  
 UN1950, Aerosols, 2.1

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-88-3	Toluene
7727-43-7	barium sulfate, natural
1330-20-7	xylene (mix)

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

100-41-4 ethyl benzene

**California Proposition 65 chemicals known to cause developmental toxicity:**108-88-3 Toluene  
67-56-1 Methanol**CANADIAN ENVIRONMENTAL PROTECTION ACT: WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.  
 A - Compressed gas  
 D2A - Very toxic material causing other toxic effects

**EPA:**

67-64-1	Acetone	I
108-88-3	Toluene	II
7727-43-7	barium sulfate, natural	D, CBD(inh), NL(oral)

(Contd. on page 5)

## Safety Data Sheet

Printing date 02/08/2016

Revised On 01/29/2016

**Trade name: HOT SPOT CAST BLAST**

(Contd. of page 4)

1330-20-7 xylene (mix)

I

**16 Other information**

**Contact:** Regulatory Affairs  
**Date of preparation / last revision** 02/08/2016 / -