

SEAL-IT Multi-Purpose Sealant



This is a multi-purpose sealant that seals small cracks and does not lose flexibility. Resists water, protects against UV sunlight, and will not crack in cold temperatures. The thermoplastic elastomer base makes it an ideal product for sealing leaks around roofs, windows and doors. It can also be topcoated with oil or latex paints.

Suggested Uses:

- Skylights
- Windows
- Flashings
- Air vents
- Driveway and sidewalk cracks
- Gutters
- Shingles

Packaging:

Cans per case	12
Shipping weight per case	19 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-40 F
Specific Gravity	0.80
Solids Content	~13%
VOC content	~46%, cannot exceed 60%
MIR value	~1.15, cannot exceed 1.20
HAPs content	~10%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Heat Resistance	2500 F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To topcoat	30 minutes

*At 720 F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick
coats**

Gloss*: Flat, <15

*as measured on a 600 gloss meter

Available Colors:

<u>Part #</u>	<u>Description</u>	<u>UPC Code</u>
#20-147	White	043281005029
#20-148	Black	043281005036
#20-149	Clear	043281005043
#20-150	Silver	043281005074

Additional Information:

This product leaves a slightly bubbly film. When covering a broad area it is recommended that two coats be applied to ensure a non-porous final coating. Allow first coat to dry to touch (about 8-10 minutes) before applying the second and final coat.