



STRIPE 3 SERIES MARKING PAINT

A fast drying marking paint designed to be sprayed in an inverted position. Uses a patented technology to cut the environmental impact in half (as compared to a standard solvent based marking paint). Produces vivid marks, does not clog, and is safe for grass. Meets APWA color standards and can be sprayed by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

- Utility marking;
- Golf courses
- Landscaping
- Construction sites
- Surveying
- Mining

Packaging:

Cans per case	12
Shipping Weight	20 ounce cans: 20 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (454 grams)
Hazard Class	2.1
Shipping Classification	Consumer Commodity ORM-D, UN 1950

Properties:

Flammability	"Flammable"
Flash point	-4F
Specific Gravity	0.73
Solids Content	~16%
MIR value	~0.48, cannot exceed 1.20
HAPs content	<1%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Freeze/Thaw	Up to 7 times without harm

****Do not warehouse in subfreezing temperatures****

Dry Time*:

To touch 15 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

****Curing/Recoat time is extended with multiple coats and excessively thick coats****

Gloss*: Flat, <15

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code	Part #	Description	UPC Code
20-352	White	043281008273	20-368	Fluorescent Green	043281008341
20-353	Precaution Blue	043281008280	20-369	Fluorescent Blue	043281008358
20-354	Fluorescent Red	043281008297	20-370	Alert Orange	043281008365
20-355	Safety Green	043281008303	20-371	Safety Red	043281008372
20-357	Fluorescent Orange	043281008310	20-376	Hi Visibility Yellow	043281008389
20-358	Fluorescent Red/Orange	043281008327	20-378	Caution Yellow	043281008396
20-363	Black	043281008334	20-379	Fluorescent Hot Pink	043281008402
			20-380	Purple	043281008563