Printing date 03/24/2016 Revised On 03/11/2016

#### 1 Identification of the substance and manufacturer

STRIPE GREEN FLUORESCENT Trade name:

0000200968 Product code:

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms** 

**Precautionary statements** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Calcium Carbonate	24.61%
64742-89-8	VM&P Naphtha	16.57%
74-98-6	propane	16.07%
	n-butane	9.44%
64742-47-8	Mineral Spirits	7.24%
142-82-5		5.86%
110-19-0	isobutyl acetate	4.91%

### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Indication of any immediate medical

attention needed: No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing agents:** 

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures. Protective equipment for

firefighters: A respiratory protective device may be necessary.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 2)

Printing date 03/24/2016 Revised On 03/11/2016

Trade name: STRIPE GREEN FLUORESCENT

Methods and material for containment and cleaning up: Ensure adequate ventilation. (Contd. of page 1)

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs and BEIs book

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

142-82-5 heptane

PEL (USA) Long-term value: 2000 mg/m<sup>3</sup>, 500 ppm REL (USA) Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800\* mg/m³, 440\* ppm \*15-min

Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm TLV (USA)

110-19-0 isobutyl acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm

TLV (USA) Short-term value: NIC-712 mg/m³, NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine. Nitrile gloves.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eve protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Not determined. Odor threshold: pH-value: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) Flash point:

-19 °C (-2 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined Viscosity: Not determined. **VOC** content: 527.1 g/l / 4.40 lb/gl

VOC content (less exempt solvents): 61.6 % MIR Value: 0.68 Solids content: 38.3 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

(Contd. on page 3)

(Contd. of page 2)

Printing date 03/24/2016 Revised On 03/11/2016

Trade name: STRIPE GREEN FLUORESCENT

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

No further relevant information available. Incompatible materials: Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 isobutyl acetate

4763 mg/kg (rbt) Oral LD50

Information on toxicological effects: No data available. No irritant effect. Skin effects: Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. **Ecotoxical effects:** 

Remark:

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must

be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Completely empty cans should be recycled.

14 Transport information

**UN-Number** UN1950 DOT N/A UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable

Transport hazard class(es):

Class 2.1 Marine pollutant:

Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Special precautions for user: Warning: Gases

**EMS Number:** F-D,S-Ŭ

Packaging Group: UN "Model Regulation": UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL PROTECTION ACT:

WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. A - Compressed gas



EPA:	
142-82-5 heptane	D
110-19-0 isobutyl acetate	D

Page 4/4

# Safety Data Sheet

Printing date 03/24/2016 Revised On 03/11/2016

Trade name: STRIPE GREEN FLUORESCENT

(Contd. of page 3)

16 Other information

Contact: Regulatory Affairs Date of preparation / last revision 03/24/2016 / -