Printing date 01/26/2016 Revised On 01/26/2016

1 Identification of the substance and manufacturer

Trade name: MRO CASCADE GREEN

0006201448 **Product code:**

Product category PC9a Paints and coatings. Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:**

Onionniour Booon	in product to a mixture of the dabotaneous noted below that normalizations to	additiono.
Dangerous com		
67-64-1 Aceto		17.37%
74-98-6 propa		15.75%
106-97-8 n-buta		9.25%
	m sulfate, natural	8.3%
2807-30-9 Glyco		6.64%
	yl isobutyl ketone	6.59%
108-65-6 PM ad		2.95%
	yl Propyl Ketone	2.8%
1330-20-7 xylene		2.45%
110-19-0 isobu	ityl acetate	1.69%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Dizziness

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/26/2016 Revised On 01/26/2016

Trade name: MRO CASCADE GREEN

Protective equipment for

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

firefighters:

Wear protective equipment. Keep unprotected persons away

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling Storage requirements:

8 Exposure controls/personal protection

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing

conditions. Store locked up.

Components	with limit values that require monitoring at the workplace:
67-64-1 Acet	one
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm

74-98-6 propane

TLV (USA)

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm Long-term value: 1800 mg/m³, 1000 ppm REL (USA) TLV (USA) refer to Appendix F inTLVs and BEIs book

Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

106-97-8 n-butane

Long-term value: 1900 mg/m³, 800 ppm REL (USA) TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

7727-43-7 barium sulfate, natural

BEI

Long-term value: 15* 5** mg/m³ *total dust **respirable fraction PEL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction REL (USA) TLV (USA) Long-term value: 5* mg/m³

*inhalable fraction; E

108-10-1 methyl isobutyl ketone PEL (USA)

Long-term value: 410 mg/m³, 100 ppm Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm REL (USA) Short-term value: 307 mg/m³, 75 ppm TLV (USA) Long-term value: 82 mg/m³, 20 ppm BEI

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm REL (USA) Long-term value: 530 mg/m³, 150 ppm TLV (USA) Short-term value: 529 mg/m3, 150 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm Short-term value: 655 mg/m³, 150 ppm REL (USA) Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA) BEI

110-19-0 isobutyl acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm

TLV (USA)

Short-term value: NIC-712 mg/m³, NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/26/2016 Revised On 01/26/2016

Trade name: MRO CASCADE GREEN

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. **Breathing equipment:**

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Undetermined.

Boiling point: -44 °C (-47 °F) Flash point: -19 °C (-2 °F) Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

503.8 g/l / 4.20 lb/gl VOC content: VOC content (less exempt solvents): 49.4 % MIR Value: 1.11

Solids content: 32.8 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat) 108-10-1 methyl isobutyl ketone

LD50 2100 mg/kg (rat) LD50 Dermal 16000 mg/kg (rab) Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

108-65-6 PM acetate

LD50 8500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

(Contd. on page 4)

(Contd. of page 3)

Printing date 01/26/2016 Revised On 01/26/2016

Trade name: MRO CASCADE GREEN

1330-20-7 xylene (mix) LD50 8700 mg/kg (rat) Oral LD50 2000 mg/kg (rbt) Dermal Inhalative LC50/4 h 6350 mg/l (rat)

110-19-0 isobutyl acetate

4763 mg/kg (rbt) Oral LD50

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eve effects: Irritating effect.

Sénsitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-10-1 methyl isobutyl ketone 2B 1330-20-7 xylene (mix) 3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A UN1950

Consumer Commodity ORM-D Aerosols, flammable DOT

ADR 1950 Aerosols

Transport hazard class(es):

2.1 Class Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate, natural

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. WHMIS Symbols for Canada:

A - Compressed gas

Toxic material causing other toxic effects



EPA:	EPA:		
67-64-1		I	
		D, CBD(inh), NL(oral)	
	methyl isobutyl ketone	I	
1330-20-7	xylene (mix)	I	
110-19-0	isobutyl acetate	D	
		(Contd. on page 5)	

Safety Data Sheet

Printing date 01/26/2016 Revised On 01/26/2016

Trade name: MRO CASCADE GREEN

USDA (United States Department of

Agriculture):

(Contd. of page 4)

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

16 Other information

Contact: Rec Date of preparation / last revision 01/2

Regulatory Affairs 01/26/2016 / -