

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

1 Identification of the substance and manufacturer

Trade name: TOOL CRIB CONTRACTOR'S ADHESIV
Product code: 0006201538
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Wear protective gloves.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a POISON CENTER/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Precautionary statements

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	41.02%
142-82-5	heptane	28.7%
74-98-6	propane	15.74%
106-97-8	n-butane	9.25%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Immediately wash with water and soap and rinse thoroughly.
 Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

Trade name: TOOL CRIB CONTRACTOR'S ADHESIV

(Contd. of page 1)

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
	BEI

142-82-5 heptane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm
	Ceiling limit value: 1800* mg/m ³ , 440* ppm
	*15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm
	Long-term value: 1640 mg/m ³ , 400 ppm

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs and BEIs book

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: -44 °C (-47 °F)
Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.1 Vol %
Upper Explosion Limit: 10.9 Vol %

(Contd. on page 3)

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

Trade name: TOOL CRIB CONTRACTOR'S ADHESIV

(Contd. of page 2)

Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	573.3 g/l / 4.78 lb/gl
VOC content (less exempt solvents):	53.7 %
MIR Value:	0.64
Solids content:	5.3 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available.**Skin effects:** Irritant to skin and mucous membranes.**Eye effects:** Irritating effect.**Sensitization:** No sensitizing effects known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Ecotoxicological effects:	
Remark:	Very toxic for fish
Other adverse effects:	No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.**14 Transport information**

UN-Number	UN1950
DOT	N/A
DOT	UN1950
ADR	Consumer Commodity ORM-D
Transport hazard class(es):	Aerosols, flammable
Class	1950 Aerosols, ENVIRONMENTALLY HAZARDOUS
Marine pollutant:	2.1
Special marking (ADR):	Yes
Special precautions for user:	Symbol (fish and tree)
EMS Number:	Symbol (fish and tree)
Packaging Group:	Warning: Gases
UN "Model Regulation":	F-D,S-U
	--
	UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

(Contd. on page 4)

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

Trade name: TOOL CRIB CONTRACTOR'S ADHESIV

(Contd. of page 3)

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL PROTECTION ACT:**WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
 A - Compressed gas
 D2B - Toxic material causing other toxic effects

**EPA:**

67-64-1 Acetone

I

142-82-5 heptane

D

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 02/08/2016 / -