

Product Information Sheet



TOOL CRIB CONTRACTOR'S GRADE ADHESIVE

#620-1538

An all-purpose industrial adhesive for bonding substrate with differing textures. This colorless adhesive has fast tack properties, resists water, and is ideal for tacking on fiberglass insulation. Cleans up easily with lacquer thinner. Not recommended on vinyl plastic or vinyl coated cloth.

Suggested Uses:

Paper, cloth, cardboard, felt Rubber, fiberglass, styrofoam Certain types of plastic Weather stripping and trim Fiberglass insulation to heating ducts

Packaging:

UPC Code 043281003414

Phone: 815-895-9101 or 800-435-4482

815-895-8475 or 800-343-4258

Cans per case 6 Shipping weight per case 9 lbs.

Container 20 fluid ounce can Label weight 14 ounces (397 grams)

Shipping Classification Consumer Commodity ORM-D, UN 1950

Hazard Class 2.1

Properties:

Flammability "Extremely Flammable"

Flash point -4F Specific Gravity 0.75 Solids Content 21%

VOC content ~54%, cannot exceed 65%

MIR Value 0.64 HAPs Content 0 Heat Resistence 200oF

Shelf life Guaranteed for 2 years

Food contact rating No

Dry Time*:

Not Applicable

*At 72₀ F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*:

Not Applicable

*as measured on a 600 gloss meter