

TOOL CRIB 5WAY CORROSION INHIBITOR & LUBE #620-1541



This is a multi-purpose lightweight lubricant that both penetrates and protects against rust and corrosion. Displaces moisture, prevents flash rusting, and provides long term protection for metal. Does not contain silicone and meets following government specifications: MIL-C-16173D and MIL-C-23411 (metal corrosion test) and MIL-C-22235A (stain test).

Suggested Uses:

Lubricate hinges, threads, and pulleys
Loosen frozen nuts and bolts
Substitute for WD-40
Coat metal parts that will sit outside

Packaging:

UPC Code	043281007078
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity ORM-D
	UN 1950
Hazard Class	2.1

Properties:

Storage Temperature	40o -100o F
Application Temperature	50o -90o F
Flammability	"Extremely Flammable"
Flash point	-4F
Specific Gravity	0.75
Solids Content	~28%
VOC content	~49%, can't exceed 50%
MIR Value	0.58
HAPs Content	18%
Lubricity Rating	Excellent
Appearance	Clear
Weather Resistance	Excellent
Operating Speed	2000+ RPM
High Temperature Resistance	150o F
Low Temperature Resistance -	20o F
Heavy Load Capability	No
Shelf life Guaranteed for	2 years
Food contact rating Category	H-1:Acceptable

Dry Time*:

Not applicable

*At 72o F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: not applicable

*as measured on a 60o gloss meter