## FLEXOVIT USA, INC

## Material Safety Data Sheet

Used to comply with OSHA's Hazard

Communication Standard, 29 CFR 1910.1200

## SECTION I - NAME AND PRODUCT

Company Name: Flexovit Abrasives

Address: 1305 Eden-Evans Road


Angola, NY 14006

Phone: 800-689-3539

Date Updated: 11/1/2011

Product: Sandpaper Sheets Floor Sanding Sheets,

Rolls, Belts, and Discs



## NFPA HAZARD RATING CODE

SECTION II - COMPOSITION								
Ingredient	% By Weight	OSHA Regulate	Cas #	OSHA PEL	ACGIH TLV	Other Limits	Carcin- ogen	
Heavy weight floor sanding								
paper or combination backing:								
Animal Hide Glue	N/A	N/A	9000-70-8	N/A	N/A	N/A	No	
Cured Phenol Formaldehyde	N/A	N/A	N/A	N/A	N/A	N/A	No	
Resin								
Limestone	N/A	N/A	001317-65-3	N/A	N/A	N/A	No	
Abrasives:								
Aluminum Oxide	N/A	N/A	1344-28-1	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	N/A	No	
Silicon Carbide	N/A	N/A	409-21-2	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	N/A	No	
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS								
Physical State N/A	Boiling Poi	nt	N/A	Specific Gravity (H2O=1)			N/A	
Vapor Pressure (mm HG) N/A	Freezing Point N/A			Odor Threshold			N/A	
Vapor Density (Air=1) N/A	Melting Point N/A			pH N/A			N/A	
Solubility in Water-Disintegrates in water	% Volatile			Evaporation Rate N/A			N/A	
Odor/Appearance-Paper/combination Coated with Abrasive Material Coefficien				oefficient of Water/Oil Distribution N/A			N/A	
	SECTIO	ON IV - FIRE	AND EXPLOSION DA	ТА				
Means Of Extinction Water spra	Lower And Upper E	Lower And Upper Explosion Limits						
Flammable Limits	mable Limits N/A S				Special Fire Fighting Procedures Use Respiratory Protection			
Flash Point N/A Unusual Fire or Explosion Hazards						N/A		

SECTION V - REACTIVITY DATA						
Stability: Stable	Conditions to Avoid: Open Flame					
ncompatability (Materials to Avoid): N/A						
Hazardous Decomposition or Byproducts: In use, abrasive dust may be generated						
Hazardous Polymerization: Will not occur						
SECTION VI - HEALTH HAZARD DATA						
Abrasives and other dusts cause irritation , coughing, shortness of breath. May affect breathing capacity, may cause						
abrasion. Elevated sound level, during use, may affect hearing.						
Route(s) of Entry	Signs and Symptoms of Exposure	Emergency & First-Aid Procedures				
Inhalation	Irritation, coughing, shortness of breath	Remove to fresh air				
		Apply artificial respiration if needed				
Skin	May cause abrasion	N/A				
Eyes	Irritation	Flush with large amount of water				
		Obtain first aid and medical assistance				
SECTION VII- STORAGE HANDLING AND USE PROCEDURES						
Normal clean-up procedures						
Waste disposal method	: Normal landfill-follow Federal, State, and Local laws					
Precautions to be taken in handling and storing: Handle with adequate ventilation-See OSHA 29CFR 1910-14 and						
CFR 1910.1000 for ventilation & specific air contaminant						
SECTION VIII- CONTROL MEASURES						
Protection	Requirements and Referrals					
Respiratory	Approved dust mask					
Ventilation	Local Exhaust: Recommended Mechanical (General): Recommended					
Protective Gloves	Recommended					
Eye Protection	Use Safety Glasses					
Hearing Protection	Recommended					
Hygienic Practices	N/A					
ther N/A						
COMPANY USE						
The information and recommendations set forth herein are taken from sources and references believed to be						
accurate and complete as of the date hereof. However, Flexovit® U.S.A., Inc. makes no expressed or implied						
warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.						
וומטוווגץ נט מוזץ עצפו נוופופטו.						