## Type 1

Use on Straight & Die

## Small Diameter Abrasive Wheels



BEST

Flexovit fully reinforced Small Diameter Wheels are designed for use on die grinders and straight grinders. Wheels from .035" through 1/8" thick are designed for cutting applications. Wheels from 3/16" through 1/2" thickness are designed for grinding using the periphery of the wheel as the grinding face.



Maximum Productivity 
Premium Abrasive Grain 
Longest Life

FLEXON Type 1 Small Diameter Wheels incorporate premium zirconia grain with advanced bond systems to deliver the highest job productivity and the lowest total cost.

Notching, & Light Grinding

Cutoff,

METAL, STAINLESS, ALLOYS

Fast Cut - ZA60T, ZA46T

Developed with premium zirconia grain, Flexon small diameter wheels deliver fast cutting and exceptional life.





High Productivity • Versatility • Durability

GOOD

Flexovit HIGH PERFORMANCE Small Diameter Wheels are the hardest working aluminum oxide wheels available. Choose from 3 specifications depending on the wheel thickness your job requires.

## METAL, STAINLESS, ALLOYS

Fast Cut - A60T, A46T, A36R Designed for cutting and notching, these wheels work especially well on thin walled tube and pipe.

Fast Cut, Grind - A36R Fast Grind - A36Q

Designed for cutting, notching and peripheral grinding.

Designed for peripheral jobs, including weld grinding, burr removal and smoothing of steel and other alloys.



MANDREL ADAPTERS

Quick mounting mandrel adaptors for small diameter wheels.





MANDREL ADAPTERS					
FITS WHEEL SIZE OF:				PART NUMBER	вох
Diameter	Thickness	Arbor	Shank Size		QTY.
2 - 4	.035 - 1/2	3/8	1/4	Z0201	1
2 - 4	.035 - 3/16	3/8 or 1/4	1/4	Z0202	1
2 - 4	.035 - 1/2	1/4	1/4	Z0251	1

