

# INSTALLATION DATA SHEET

## NYLON TUBE (485 - 486 - 487)

485 - TYPE 11 (FLEXIBLE)    486 - TYPE 6 (SEMI-RIGID)    487 - TYPE 11 (HEAVY WALL)

**Applications:** Polyethylene tube is manufactured from F.D.A. approved resins. It has very low moisture absorption. It is fungus resistant, non-corrosive, and highly resistant to stress cracking. It is suitable for air and water applications and is used for beverage and soda transfer. It is available in two types, low and high density. Low density provides flexibility and high density, while not as flexible, has a higher temperature and pressure rating.

**Color:** 360 series only: BLK (Black), BLU (Blue), GRN (Green), ORA (ORANGE), Red (Red), YEL (Yellow)  
**NOT ALL SIZES ARE AVAILABLE IN ALL COLORS. MINIMUM RUNS MAY APPLY.**

**Temperature:** -20°F TO +230°F, -28°C TO +110°C

**Packaging:** 100 FT. COILS

**Fittings:** 200 SERIES, 1500 SERIES AND PC SERIES

**Working Pressure:**

Check all tube prior to installation for defects, kinking and discoloration which could be an indication of old age. The few moments it takes is well worth it.

Make nice clean 90 degree cuts for ease of installation and to improve seal. Use brass inserts in tube when using compression style fittings to stop tube collapse.

Always check for leaks on completion.