

# TECHNICAL DATA SHEET

## PRESSURE WASH HOSE ASSEMBLY (PW2 ASSY)

**Applications:** Two Star (PW2) is a one wire construction, black covered hose. (also available in blue) Its' tube is specially formulated to handle high pressure water. Suitable for pressures up to 4000 P.S.I., at +70°F,(+21°C), or temperatures up to +250°F,(+121°C) at lower pressures. Swivels on both ends available upon request. Suffix PART No. with SW. Example: PW2A-6-50SW



PART No.	Length (FT.)	Actual I.D (IN.)
PW2A-4-30	30	1/4
PW2A-4-50	50	1/4
PW2A-4-75	75	1/4
PW2A-4-100	100	1/4
PW2A-6-30	30	3/8
PW2A-6-50	50	3/8
PW2A-6-75	75	3/8
PW2A-6-100	100	3/8
PW2A-6-50SW	50	3/8
PW2A-6-100SW	100	3/8
PW2A-6BLU-30	30	3/8
PW2A-6BLU-50	50	3/8
PW2A-6BLU-75	75	3/8
PW2A-6BLU-100	100	3/8



- CAN BE MADE TO ORDER • ALL ASSEMBLIES COME WITH THERMOPLASTIC BEND PROTECTORS • SYNTHETIC RUBBER BEND PROTECTORS ALSO AVAILABLE
- STANDARD HOSE ASSEMBLIES CONSIST OF SWIVEL MALE PIPE X SOLID MALE PIPE