

TECHNICAL DATA SHEET

S.A.E. 30R7 FUEL LINE HOSE (FLH)

Applications: Designed to convey most fuels in cars, trucks, buses etc. Durable cover resists deterioration from oil, grease, heat and ozone and gives long service life.

NOTE: FLH IS NOT DESIGNED FOR MARINE USE WITH ALCOHOL BLENDED FUELS.

- **MEETS:** S.A.E. 30R7
- **COLOR:** Black
- **TEMPERATURE:** -40°F to +257°F, -40°C to +125°C
- **PACKAGING:** 250 FT Reels, 50 and 100 FT Coils
- **FITTINGS:** Hose Barbs
- **CLAMPS:** HC5 & HC6

Dash Size	Actual I.D. (IN.)	Hose O.D. (IN.)	Length (FT.)	Working Pressure (P.S.I.)	Min. Burst Pressure (P.S.I.)
-3-25	3/16	.406	25	50	250
-3-50	3/16	.406	50	50	250
-3-100	3/16	.406	100	50	250
-3-250	3/16	.406	250	50	250
-4-25	1/4	.500	25	50	250
-4-50	1/4	.500	50	50	250
-4-100	1/4	.500	100	50	250
-4-250	1/4	.500	250	50	250
-5-25	5/16	.563	25	50	250
-5-50	5/16	.563	50	50	250
-5-100	5/16	.563	100	50	250
-5-250	5/16	.563	250	50	250
-6-25	3/8	.625	25	50	250
-6-50	3/8	.625	50	50	250
-6-100	3/8	.625	100	50	250
-6-250	3/8	.625	250	50	250

* NOTE: WORKING PRESSURE RATED AT +75°F, +24°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE WORKING PRESSURE.