Printing date 02/08/2016 Revised On 02/08/2016

1 Identification of the substance and manufacturer

STRIPE EXTRA HANDICAP DARK BLUE Trade name:

0000200789 Product code:

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Precautionary statements

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

	ngerous components:			
	VM&P Naphtha	24.18%		
1317-65-3	Calcium Carbonate	21.0%		
	propane	12.6%		
67-63-0	isopropyl alcohol	9.48%		
	n-butane	7.4%		
	Acetone	2.64%		
	titanium dioxide	2.41%		
108-65-6	PM acetate	1.14%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

Dizziness

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: STRIPE EXTRA HANDICAP DARK BLUE

A respiratory protective device may be necessary.

6 Accidental release measures

Protective equipment for

firefighters:

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing

conditions. Store locked up.

8 Exposure controls/personal protection

l	74-96-6 propane				
I	PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
I	REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
l	TLV (USA)	refer to Appendix F inTLVs and BEIs book			

Components with limit values that require monitoring at the workplace:

67-63-0 isopropyl alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm REL (USA) Short-term value: 1225 mg/m3, 500 ppm Long-term value: 980 mg/m³, 400 ppm TLV (USA) Short-term value: 984 mg/m³, 400 ppm ong-term value: 492 mg/m³, 200 ppm BFI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

67-64-1 Acetone

Long-term value: 2400 mg/m³, 1000 ppm PEL (USA) REL (USA) Long-term value: 590 mg/m³, 250 ppm Short-term value: 1187 mg/m³, 500 ppm TLV (USA) Long-term value: 594 mg/m³, 250 ppm BEI

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:

67-63-0 isopropyl alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

67-64-1 Acetone

BEI (USA) 50 mg/L

Flash point:

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

-19 °C (-2 °F)

Nitrile gloves. Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F)

(Contd. on page 3)

(Contd. of page 2)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: STRIPE EXTRA HANDICAP DARK BLUE

Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density
Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Not determined.
Not determined.
Not determined.
VOC content:
526.4 g/l / 4.39 lb/gl

VOC content (less exempt solvents): 58.5 % MIR Value: 0.76 Solids content: 38.7 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

LD/LC50 values that are relevant for classification:

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:

Hazardous decomposition:

No further relevant information available.

No dangerous decomposition products known.

11 Toxicological information

67-63-0 is	67-63-0 isopropyl alcohol				
Oral	LD50	4570 mg/kg (rat)			
Dermal	LD50	13400 mg/kg (rab)			
Inhalative	LC50/4 h	30 mg/l (rat)			
106-97-8 r	106-97-8 n-butane				
Inhalative	LC50/4 h	658 mg/l (rat)			
13463-67-	13463-67-7 titanium dioxide				
Oral	LD50	>20000 mg/kg (rat)			
Dermal	LD50	>10000 mg/kg (rbt)			
Inhalative	LC50/4 h	>6.82 mg/l (rat)			
108-65-6 PM acetate					
Oral	LD50	8500 mg/kg (rat)			
Inhalative	LC50/4 h	35.7 mg/l (rat)			

Information on toxicological effects: No data available. Skin effects: No irritant effect. No irritating effect. No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

 67-63-0 isopropyl alcohol
 3

 13463-67-7 titanium dioxide
 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 (Contd. on page 4)

(Contd. of page 3)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: STRIPE EXTRA HANDICAP DARK BLUE

DOT UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: No

Special precautions for user: EMS Number: Warning: Gases F-D,S-U

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. WHMIS Symbols for Canada:

Compressed gas

EPA:

ADR

67-64-1 Acetone

Ι

16 Other information

Contact: Regulatory Affairs Date of preparation / last revision 02/08/2016 / -