Printing date 01/25/2016 Revised On 01/25/2016

1 Identification of the substance and manufacturer

SPRUCE PINK Trade name: 0000980039 Product code:

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements

GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.

Do not breathe dustrume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

| | The production a mixture of the outstands include select mixture and additional | |
|------------------|---|--|
| | | |
| | | 23.9% |
| | | 18.85% |
| | | 11.07% |
| | | 11.06% |
| | | 9.99% |
| | | 4.68% |
| titanium dioxide | | 4.41% |
| | | 2.5% |
| xylene (mix) | | 1.73% |
| | components: Acetone propane n-butane Toluene VM&P Naphtha Mineral Spirits titanium dioxide isopropyl alcohol xylene (mix) | Acetone propane n-butane Toluene VM&P Naphtha Mineral Spirits titanium dioxide isopropyl alcohol |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor.

After swallowing: Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: SPRUCE PINK

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing Storage requirements:

conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F inTLVs and BEIs book

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm REL (USA)

Long-term value: 75 mg/m³, 20 ppm TLV (USA)

BEI

67-63-0 isopropyl alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

REL (USA) Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm TLV (USA)

BEI

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA)

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: SPRUCE PINK

108-88-3 Toluene

BEI (USA) 0.02 mg/L Medium: blood

Time: prior to last shift of workweek Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-63-0 isopropyl alcohol BEI (USA) 40 mg/L Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be **Breathing equipment:**

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance. Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Boiling point: Undetermined. -110 °C (-166 °F)

Flash point: -19 °C (-2 °F) Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

Between 0.77 and 0.85 (Water equals 1.00) **Relative Density:**

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. VOC content: 527.1 g/l / 4.40 lb/gl

VOC content (less exempt solvents): 60.4 % MIR Value: 1.07 Solids content: 15.6 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known. Printing date 01/25/2016 Revised On 01/25/2016

Trade name: SPRUCE PINK

(Contd. of page 3)

11 Toxicological information

| LD/LC50 v | LD/LC50 values that are relevant for classification: | | | | |
|---------------------------|--|--------------------|--|--|--|
| 106-97-8 r | 106-97-8 n-butane | | | | |
| Inhalative | LC50/4 h | 658 mg/l (rat) | | | |
| 13463-67- | 13463-67-7 titanium dioxide | | | | |
| Oral | LD50 | >20000 mg/kg (rat) | | | |
| Dermal | LD50 | >10000 mg/kg (rbt) | | | |
| Inhalative | LC50/4 h | >6.82 mg/l (rat) | | | |
| 67-63-0 isopropyl alcohol | | | | | |
| Oral | | 4570 mg/kg (rat) | | | |
| Dermal | LD50 | 13400 mg/kg (rab) | | | |
| Inhalative | LC50/4 h | 30 mg/l (rat) | | | |
| 1330-20-7 xylene (mix) | | | | | |
| Oral | | 8700 mg/kg (rat) | | | |
| | | 2000 mg/kg (rbt) | | | |
| Inhalative | LC50/4 h | 6350 mg/l (rat) | | | |

Information on toxicological effects: No data available. No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

| IARC (Inter | IARC (International Agency for Research on Cancer) | | | | |
|-------------|--|----|--|--|--|
| 108-88-3 | Toluene | 3 | | | |
| 13463-67-7 | titanium dioxide | 2B | | | |
| 67-63-0 | isopropyl alcohol | 3 | | | |
| 1330-20-7 | xylene (mix) | 3 | | | |

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes.

Persistence and degradability: Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A UN1950

Consumer Commodity ORM-D Aerosols, flammable DOT

1950 Aerosols

ADR Transport hazard class(es):

Class Marine pollutant: No

Special precautions for user:

Warning: Gases

EMS Number: F-D,S-U

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 isopropyl alcohol

1330-20-7 xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet

Revised On 01/25/2016 Printing date 01/25/2016

Trade name: SPRUCE PINK

California Proposition 65 chemicals known to cause developmental

toxicity:
CANADIAN ENVIRONMENTAL
PROTECTION ACT:
WHMIS Symbols for Canada:

108-88-3 Toluene

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

A - Compressed gas
D2A - Very toxic material causing other toxic effects



| EPA: | | |
|-----------|--------------|----|
| 67-64-1 | Acetone | 1 |
| 108-88-3 | Toluene | II |
| 1330-20-7 | xylene (mix) | 1 |

16 Other information

Contact: Date of preparation / last revision Regulatory Affairs 01/25/2016 / -