



CUTTING & GRINDING

371



POWERPLUS®



BETTER**

500425

POWER XTREME™



BEST**

501653

POWERPLUS® DUO

Depressed Centre Wheels - High Performance Combo (for Angle Grinders)

- These dual purpose wheels are ideal when performing multiple cutting and light grinding tasks without changing wheels. Saving time and money while improving productivity and safety
- Complies with EN 12413 OSA standards – allows side load capacity of +/- 290.n



TYPE 27



PROD. NO.	Size (inches)	Thickness (mm)	Thickness (inches)	Grade	Max. RPM	Pkg. Qty.
500405	4 x 1/8 x 5/8	3.2	.125	A30DUO	15,300	25
500415	4-1/2 x 1/8 x 7/8	3.2	.125	A30DUO	13,300	25
500425	5 x 1/8 x 7/8	3.2	.125	A30DUO	12,200	25
500431	6 x 1/8 x 7/8	3.2	.125	A30DUO	10,200	25
500435	7 x 1/8 x 7/8	3.2	.125	A30DUO	8,600	25
500445	9 x 1/8 x 7/8	3.2	.125	A30DUO	6,600	25

POWER-XTREME® DUO

(PREVIOUSLY POWERPLUS TZ+ DUO)

Depressed Centre Wheels - Super High Performance Combo (for Angle Grinders)

- Specially designed dual purpose wheels for high performance cutting and light grinding of both steel and stainless steel materials
- Ideal for notching, chamfering, deburring and much more
- Fe+S+Cl free for contamination free cutting and light grinding of stainless steel
- Special reinforcements and pressing technologies allow thin cutting wheels to safely perform light grinding operations without changing wheels, saving time and money
- Complies with EN 12413 OSA standards – allows side load capacity of +/- 290.n
- Designed to cut at 90° and grind at 30°



TYPE 27



PROD. NO.	Size (inches)	Thickness (mm)	Thickness (inches)	Grade	Max. RPM	Pkg. Qty.
501653	4-1/2 x 5/64 x 7/8	1.9	.075	A46PX-DUO	13,300	25
501656	5 x 5/64 x 7/8	1.9	.075	A46PX-DUO	12,200	25



CUT & GRIND

POWER-XTREME® DUO SSt (PREVIOUSLY POWERPLUS DUO)

Depressed Centre Wheels - Super High Performance Combo
(for Angle Grinders)

- Dual purpose wheels are ideal when performing multiple cutting and light grinding tasks without changing wheels. Saving time and money while improving productivity and safety
- Fe+S+Cl free for contamination free cutting and light grinding of stainless steel
- Complies with EN 12413 OSA standards – allows side load capacity of +/- 290.n

SSt Fe+S+Cl Free  **TYPE 27**

PROD. NO.	Size (inches)	Thickness (mm)	Thickness (inches)	Grade	Max. RPM	Pkg. Qty.
500465	4-1/2 x 1/8 x 7/8	3.2	.125	A30DUO	13,300	25
500475	5 x 1/8 x 7/8	3.2	.125	A30DUO	12,200	25
500481	6 x 1/8 x 7/8	3.2	.125	A30DUO	10,200	25
500485	7 x 1/8 x 7/8	3.2	.125	A30DUO	8,600	25

POWER-XTREME™



500475

BEST**