



# Founded in 1972

The fastest-growing vehicle lighting manufacturer in the U.S., Optronics International attributes its success to delivering better value, better options and better lighting to its customers. Optronics International is a premier worldwide manufacturer of industrial and commercial vehicle safety lighting products. Optronics specializes in interior and exterior LED and incandescent lighting for the HD, trailer, RV, marine, and transit vehicle markets.

# **ISO Certified**

Optronics is headquartered in Tulsa, Oklahoma, with an ISO/TS 16949:2009 certified manufacturing facility in Annan District, Tainan, Taiwan, and additional manufacturing capabilities in its ISO 9001:2008 certified facility in Muskogee, Oklahoma. The company has an ISO 9001:2008 certified distribution facility in Goshen, Indiana, as well as distribution through its location in Ontario, Canada.

# Lifetime LED Warranty

**ALL Optronics LED lighting** is now covered by a one-diode lifetime warranty that replaces the lamp if even one diode fails.





Goshen, IN



Tainan City, Taiwan



# CONTENTS

All Optronics products conform to DOT/SAE/FMVSS/CMVSS 108 standards where applicable when applied according to federal lighting requirements

LED TRUCK & TRAILER LIGHTING	2 - 168
Headlamps FUSION™ Stop/Turn/Tail/Back-Up Lamps	
Sealed Stop/Turn/Tail Lights & Parking/Turn Signals	
Combination Tail Lights & Kits	
Towing Lights	
DOT Compliant Back-Up Lights	
Warning Lights	70
Millennium <sup>®</sup> Series	
Sealed Marker/Clearance Lights	
Surface Mount Marker/Clearance Lights	
Identification Light Bars License Plate Lights	
Utility Lights	
Interior & Utility Lights	
Work & Utility Lights	
INCANDESCENT TRUCK & TRAILER LIGHTING Sealed Stop/Turn/Tail Lights & Parking/Turn Signals	<b>169 - 233</b>
Combination Tail Lights & Kits	
DOT Compliant Back-Up Lights	
Millennium Series® Marker/Clearance Lights	
Sealed Marker/Clearance Lights	
Surface Mount Marker/Clearance Lights	
Identification Light Bars	
License & Utility Lights	
Utility & Interior Lights	
Work & Ag Lights	
Halogen Lights	
RV LIGHTS & ACCESSORIES	234 - 262
ACCESSORIES - CONSPICUITY, MOUNTING, WIRING	263 - 288
FMVSS LIGHTING REQUIREMENTS	289 - 295
INDEX	296 - 305
<b>Optronics International</b> <b>OKLAHOMA:</b> 401 South 41st Street East, Muskogee OK 74403 toll free: 800-364-5483 • phone: 918-683-9514 • fax: 918-683-9517	
INDIANA: 3535 Corrie Dr, Goshen, IN 46526 toll free: 800-826-5483 • phone: 574-389-0040 • fax: 574-389-0041	
website: www.optronicsinc.com • email: sales@optronicsinc.com	
©2016 Optronics International ZH2016M	







HLL88LB





HLL89HB

#### HLL88/89 SERIES DOT Compliant High and Low Beam Sealed LED Headlamps


- Replace standard 4" x 6" sealed beam halogen and HID headlamps
- · Light output whiter than incandescent for greater visibility
- Long lasting, energy efficient diodes last up to 50 times longer than incandescent, draw less than 1 amp
- Dual power: use with 12VDC or 24VDC systems
- Hard wired with standard H4 3-blade connector;
   16 gauge, 7-inch leads
- Die cast aluminum construction with powder coat finish resists corrosion
- Tough polycarbonate lens with protective coating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LOW BEAM H	EADLAMP - 8 DIODES	
HLL88LB	HLL88LBP	12-24VDC Low beam	1
	HIGH BEAM H	IEADLAMP - 8 DIODES	
HLL89HB	HLL89HBP	12-24VDC High beam	1

HLL88LB: 12.8VDC - 23.7W / 28VDC - 23.7W HLL89HB: 12.8VDC - 23.7W / 28VDC - 23.7W

**IP67 rating:** protected from dust and capable of withstanding water immersion, offering increased reliability and service life

FMVSS	HL
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 0.85A
WT/DIMS	1.14 lbs. / 6.563" x 4.188" x 3.313"
WARRANTY	Lifetime LED Warranty





#### HLL90 SERIES DOT Compliant High/Low Beam Sealed LED Headlamp

- Replace standard 7" sealed beam halogen and HID headlamps
- Light output whiter than incandescent for greater visibility
- Long lasting, energy efficient diodes last up to 50 times longer than incandescent, draw less than 1 amp
- Dual power: use with 12VDC or 24VDC systems
- Hard wired with standard H4 3-blade connector; 16 gauge, 7-inch leads
- Die cast aluminum construction with powder coat finish resists corrosfion
- Tough polycarbonate lens with protective coating





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
Н	IGH/LOW BEAN	M HEADLAMP - 16 DIODES	
HLL90HLB	HLL90HLBP	12-24VDC High/low beam	1

HLL90HLB



High Beam: 12.8VDC - 23.68W / 28VDC - 22.4W Low Beam: 12.8VDC - 23.04W / 28VDC - 22.4W

**IP67 rating:** protected from dust and capable of withstanding water immersion, offering increased reliability and service life

FMVSS	HL
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - High Beam 1.85A / Low Beam 1.80A
WT/DIMS	2.05 lbs. / 7" x 7" x 2.8"
WARRANTY	Lifetime LED Warranty






**otronic**s








**STL201 GLOLIGHT® SERIES** 


#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Multi-function: Stop, turn, tail and back-up, all in one light
- Flange mount for security, theft reduction
- · Weathertight connection standard

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED S	RED STOP/TURN/TAIL/BACK-UP LIGHT - 24 DIODES		
STL201RFMB	STL201RFMBP	Weathertight connection	10
ACCESSORIES			
A45PMB	A45PMBP	Weathertight pigtail, 3-wire	50
A42PMB	A42PMBP	Weathertight pigtail, 2-wire	100











Weathertight connection

#### STL201 SERIES FUSION™ 4" Round Sealed Stop/Turn/Tail/Back-Up Light

- Sonically sealed, waterproof
- Multi-function: Stop, turn, tail and back-up, all in one light
- Accepts standard PL-3 plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED S	TOP/TURN/T	AIL/BACK-UP LIGHT - 16 DIODI	≣S
STL201RB	STL201RBP	PL-3 connections	10
	A	ACCESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10








S2 T2 I6 (2)R
Polycarbonate lens and housing
12.8VDC375A Stop/Turn, .145A Tail, .3A Back-Up
.35 lbs. / 4.313" x 4.313" x 2"
Lifetime LED Warranty



Standard PL3 connections



HOLE CUT-OUT: 4.5"





- Sonically sealed, waterproof •
- Multi-function: Stop, turn, tail and back-up, all in one light
- Accepts standard PL-3 plugs





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ST	OP/TURN/TAIL	BACK-UP LIGHT - 16 DIODES	\$
STL211RB	STL211RBP	Red lens, PL-3 connection	10
STL211RCB	STL211RCBP	Clear lens, PL-3 connection	10
	ACC	CESSORIES	
A70GB	A70GBP	Grommet, flush mount	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A77SB	A77SBP	Grey steel bracket	20
BK70BB	BK70BBP	Black steel bracket	10


	8-8	-17-10
( 6	0 0	20

68	00	30
STL211F	RCB	

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC375A Stop/Turn, .020A Tail, .242A Back-Up
WT/DIMS	.35 lbs. / 6.438" x 2.313" x 1.50"
WARRANTY	Lifetime LED Warranty









Standard PL3 connections

# STL68 SERIES

FUSION<sup>™</sup> Surface Mount LED Combination Stop/Turn/Tail/Back-Up Light

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Low profile design-only 1/2" thick
- Surface mount on 9-11/16" centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
STOP/T	URN/TAIL/BAC	K-UP LIGHT - 14 DIODE	S	
STL68RB	STL68RBP	Red, hard wired	10	
STL68RPB	STI68RPBP	Red, .180 male bullets	10	
ACCESSORIES				
A68SSB	A68SSBP	Stainless steel snap-on ring	20	


FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC35A Stop/Turn, .05A Tail, .3A Back-up
WT/DIMS	.275 lbs. / 10.125" x 3.063" x 0.5"
WARRANTY	Lifetime LED Warranty








A68SSB







			ET MOUNT SERI	ES
STOP/TURN			ECHNOLOGY	
		· · · · · · · · · · · · · · · · · · ·	sealed, waterproof any 360 degree position	
COLO ASSA			in tinted and clear lens model	s
	TAIL LIGHT	Available	with standard PL-3 or optiona oht connection	-
	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STLIOIRB	RE	D STOP/TURN	/TAIL LIGHT - 21 DIODES	
	STL101RB	STL101RBP	PL-3 connection	10
	STL101RMB	STL101RMBP	Weathertight connection	10
	STL101RCB	STL101RCBP	Clear lens, red diodes, PL-3	10
	STL101RCMB	STL101RCMBP	Clear lens, red diodes, weathertight	10
	STL101RKB	STL101RKBP	Kit: Red stop/turn/tail light, PL-3 connection, A45GB grommet, A47PB pigtail	10
	YELL		TURN SIGNAL - 21 DIODES	
	STL101AB	STL101ABP	PL-3 connection	10
STL101RCB	STL101ACB	STL101ACBP	Clear lens, yellow diodes, PL-3	10
		ACO	CESSORIES	
	A45GB	A45GBP	Grommet	50
	A45PB	A45PBP	Pigtail, 3-wire	100
	A47PB	A47PBP	Right angle pigtail, 3-wire	100
	A45PMB	A45PMBP	Weathertight pigtail	100
	AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
	BK45BB	BK45BBP	Black steel bracket	10
CARL CONT	A45BB	A45BBP	Black plastic flange	100
	A45SB	A45SBP	Stainless steel mounting flange	20
STL101AB	A45CGB	A45CGBP	Chrome grommet cover	20
	FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	Red: 12 Yellow: 12	e lens and housing .8VDC375A Stop/Turn, .145A Tail .8VDC315A Turn, .143A Parking 3" dia x 1.375" D	
STL101ACB			4 5/16" HOLE CUT-OUT: 4.5"	

8

**Gptronics** 

LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS

800-364-5483 / 918-683-9514

#### STL101 FLANGE MOUNT SERIES GloLight® 4" Sealed LED Lights with Mounting Flange

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RE	D STOP/TURN/	TAIL LIGHT - 21 DIODES	
STL101RFB	STL101RFBP	PL-3 connection	10
STL101RFMB	STL101RFMBP	Weathertight connection	10
STL101RCFB	STL101RCFBP	Clear lens, red diodes, PL-3	10
STL101RCFMB	STL101RCFMBP	Clear lens, red diodes, weathertight	10
	ACC	ESSORIES	
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A101TRSSB	A101TRSSBP	Stainless steel trim ring	50
A42GB	A42GBP	Mounting gasket, black	100

FMVSS	Red S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC375 Stop/Turn, .145A Tail
WT/DIMS	.38 lbs. / 5.48" x 5.48" x 1.53"
WARRANTY	Lifetime LED Warranty

#### Industry-standard connections


Easy retrofit of lights to existing harness



Standard PL3 connection



Weathertight connection



# STOP/TURN

TAIL LIGHT

**GloLight** 

STL101RFB



**ptronics** 



9



HOLE CUT-OUT: 4.5"




#### STL113 SERIES GloLight<sup>®</sup> 4" Round Sealed LED Lights

#### PATENTED TECHNOLOGY

- Unique mirrored reflector
- Sonically sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
l i i i i i i i i i i i i i i i i i i i	RED STOP/TU	RN/TAIL LIGHT - 18 DIODES	
STL113RB	STL113RBP	PL-3 connection	10



ERIES

**Glo**Light

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC375A Stop/Turn, .145A Tail
WT/DIMS	.35 lbs. / 4.313" x 4.313" x 2"
WARRANTY	Lifetime LED Warranty

#### **STL513 Series** HD500<sup>™</sup> 4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Available in tinted and clear lens models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
R	ED STOP/TU	RN/TAIL LIGHT - 18 DIODES	
STL513RB	STL513RBP	PL-3 connection	10
STL513RCB	STL513RCBP	Clear lens, red diodes, PL-3	10
FMVSS	S2 T2 I6		
MATERIALS	Polycarbona	ate lens and housing	
VOLT/AMP	12.8VDC	435A Stop/Turn, .042A Tail	
WT/DIMS	.287 lbs. / 4.	.313" x 4.313" x 1.938"	
WARRANTY	Lifetime LE	D Warranty	

STL113 & STL513 ACCESSORIES				
A45GB	A45GBP	PVC grommet, flush mount	50	
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100	
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100	
BK45BB	BK45BBP	Black steel bracket	10	
A45BB	A45BBP	Black mounting flange	100	
A45SB	A45SBP	Stainless steel mounting flange	20	
A45CGB	A45CGBP	Chrome trim ring	20	



STL513RCB


#### STL43 SERIES 4" Round Sealed LED Lights


- Sonically sealed, waterproof
- Kits include grommet and plug
- Mount in any 360 degree position
- Available in 12V and 24V models
- Available with standard PL-3 or optional weathertight connection


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		
RED STOP/TURN/TAIL LIGHT - 10 DIODES					
STL43RB	STL43RBP	PL-3 connection, 12V	10		
STL43RKB	STL43RKBP	Kit with A45GB & A47PB, PL-3, 12V	10		
STL43R24B	STL43R24BP	PL-3 connection, 24V	10		
STL43RMB	STL43RMBP	Weathertight connection, 12V	10		
STL53RCB	STL53RCBP	Clear lens, red diode, PL-3	10		
YEL		TURN SIGNAL - 10 DIODES			
STL43AB	STL43ABP	PL-3 connection, 12V	10		
STL43A24B	STL43A24BP	PL-3 connection, 24V	10		
STL43AKB	STL43AKBP	Kit with A45GB & A47PB, PL-3, 12V	10		
	ACO	CESSORIES			
A45GB	A45GBP	Grommet	50		
A45PB	A45PBP	Pigtail, 3-wire PL-3	100		
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100		
A45PMB	A45PMBP	Weathertight pigtail	100		
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50		
BK45BB	BK45BBP	Black steel bracket	10		
A45BB	A45BBP	Black plastic flange	100		
A45SB	A45SBP	Stainless steel mounting flange	20		
A45CGB	A45CGBP	Chrome grommet cover	20		
		RETAIL			
STL43RK	Retail Ready	12V kit with A45GB & A47PB, clam	6		

FMVSS	Red S T I P2; Yellow I6 P		
MATERIALS	Polycarbonate lens and housing		
VOLT/AMP	Red: 12.8VDC360A Stop/Turn, .030A Ta	il	
	Yellow: 12.8VDC310A Turn, .046A Parking		
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.938"		
WARRANTY	Lifetime LED Warranty		









HOLE CUT-OUT: 4.5"

ONIC



LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS




STL42RB



STL42AB



A42GB



STL42 SERIES	
4" Round Sealed LED Lights	j
with Mounting Flange	

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Red available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
R	ED STOP/TU	RN/TAIL LIGHT - 10 DIODES	
STL42RB	STL42RBP	Black flange, PL-3	10
STL42RMB	STL42RMBP	Black flange, weathertight	10
STL42RMBK	STL42RMBKP	Kit: Red stop/turn/tail light with weathertight connection, AL45PWTB pigtail	10
YEL	LOW PARKIN	NG/TURN SIGNAL - 10 DIODES	
STL42AB	STL42ABP	Black flange, PL-3	10
STL42AMB	STL42AMBP	Black flange, weathertight	10
	ļ	ACCESSORIES	
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A42FCB	A42FCBP	Chrome flange cover	100
A5TRSSB	A5TRSSBP	Stainless steel trim ring	100
A42GB	A42GBP	Mounting gasket, black	100
		RETAIL	
STL42RS	Retail Ready	Light only, clam	6

FMVSS	Red S T I P2; Yellow I6 P			
MATERIALS	Polycarbonate lens and housing			
VOLT/AMP	Red: 12.8VDC413 Stop/Turn, .026A Tail			
	Yellow:	12.8VDC310 Turn, .046A Parking		
WT/DIMS	.617 lbs. / 5.5" x 5.5" x 1.938"			
WARRANTY	Lifetime LED Warranty			



#### **STL43 REFLEX FLANGE SERIES** 4" Round Sealed LED Lights with Reflex Mounting Flange

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Accepts standard PL-3 connector
- Reflex flange meets SAE A for reflector


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
R	RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL43RBX	STL43RBXP	Red reflex flange, gasket, PL-3	10	
STL43RBHX	STL43RBHXP	Red reflex flange, hard wire, gasket	10	
YEL	LOW PARKIN	NG/TURN SIGNAL - 10 DIODES		
STL43ABX	STL43ABXP	Yellow reflex flange, gasket	10	
	A	ACCESSORIES		
A45PB	A45PBP	Pigtail, 3-wire PL-3	100	
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100	
RETAIL				
STL43ABXS	Retail Ready	Yellow light only, clam	6	
STL43RBXS		Red light only, clam	6	







FMVSS	Red S T I; Yellow I6 P; Reflex A			
MATERIALS	Polycarbon	Polycarbonate lens and housing		
VOLT/AMP	Red:	Red: 12.8VDC413 Stop/Turn, .026A Tail		
	Yellow: 12.8VDC310 Turn, .046A Parking			
WT/DIMS	.397 lbs. / 5.75" x 5.75" x 1.625"			
WARRANTY	Lifetime LED Warranty			



HOLE CUT-OUT: 4.5"





#### STL13 SERIES FLEET Count<sup>™</sup> 4" Round Sealed LED

- FLEET Count<sup>™</sup> 4" Round Sealed LED Stop/Turn/Tail Lights
- Sonically sealed, waterproof
- Available in grommet and flange mount models
- Available with standard PL-3, male pin, weathertight or hard wired connections
- Retail kit includes grommet and plug


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP/T	URN/TAIL - 7 DIODES	
STL13RB	STL13RBP	PL-3 connection	10
STL13RMB	STL13RMBP	Weathertight connection	10
STL13RGB	STL13RGBP	Male pin connection	10
STL13RH1B	STL13RH1BP	Hard wired, PL-3 female plug	10
STL13RH3B	STL13RH3BP	Hard wired, .180 male bullets	10
STL13RFB	STL13RFBP	Flange, PL-3	10
STL13RFMB	STL13RFMBP	Flange, weathertight	10
STL13RKB	STL13RKBP	Kit: with A45GB grommet and A45PB plug, PL-3 connection	
	AC	CESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A42FCB	A42FCBP	Chrome flange cover	100
A5TRSSB	A5TRSSBP	Stainless steel trim ring	100
A45CGB	A45CGBP	Chrome grommet cover	20
		RETAIL	
STL13RK	Retail Ready	Kit with A45GB & A47PB, clam	6
STL13RS	Refail Ready	Light only, clam	6
STL13RFS		Flange mount light only, clam	6
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC234		

LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS



STL13RFB







STL13RGB male pin connection


14

800-364-5483 / 918-683-9514

#### STL413 Series FLEET Count<sup>™</sup> 4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360° position
- Available in standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
F	RED STOP/TU	IRN/TAIL LIGHT - 4 DIODES	
STL413RB	STL413RBP	PL-3 connection	10
STL413RMB	STL413RMBP	Weathertight connecton	10
	A	ACCESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail, 3-wire	50
AL45PWTB	AL45PWTBP	Weathertight pigtail to PL-3	50
A45BB	A45BBP	Black mounting flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
BK45BB	BK45BBP	Black steel bracket	10



STL413RB



FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC160A Stop/Turn, .008A Tail
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.625"
WARRANTY	Lifetime LED Warranty


**Industry-standard connections** Easy retrofit of lights to existing harness



Standard PL3 connection



Weathertight connection



HOLE CUT-OUT: 4.5"

optronics)



#### STL003 Series ONE<sup>™</sup> LED 4" Round Sealed Lights

- · Sonically sealed, waterproof
- Mount in any 360° position
- Available in grommet and flange mount models with PL-3 and weathertight connections


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
I	RED STOP/TU	RN/TAIL LIGHT - 1 DIODE	
STL003RB	STL003RBP	PL-3 connection	10
STL003RFB	STL003RFBP	Flange mount, PL-3 connection	10
STL003RFLB	STL003RFLBP	Flange mount, locking PL-3 connection	10
STL003SRFLB	STL003SRFLBP	LampLock™ snap-in flange mount, locking PL-3 connection, adhesive gasket	10
STL003RFMB	STL003RFMBP	Flange mount, weathertight connection	10
STL003RMB	STL003RMBP	Weathertight connection	50
YELLOW PARKING/TURN SIGNAL - 1 DIODE			
STL003AB	STL003ABP	PL-3 connection	50

ACCESSORIES			
A45GB	A45GBP	PVC grommet, flush mount	50
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
AL45PWTB	AL45PWTBP	Weathertight pigtail, plug to female PL-3	50
A45PMB	A45PMBP	Weathertight 3-wire pigtail, plug to bare wire	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

	RETAIL	
Retail Ready	Kit with grommet and pigtail, clam	6
	Light only, clam	6

FMVSS	Red: S T I, Yellow: I P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC25A Stop/Turn, .007A Tail
WT/DIMS	Grommet mount: .35 lbs. / 4.313" x 4.313" (depth varies)
	Flange mount: .275 lbs. / 5.5" x 5.5" (depth varies)
WARRANTY	Lifetime LED Warranty



STL003RK

STL003RS

Grommet mount, PL-3



LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS

16

STLOO3AB

ED LAMPS

0

STL003RB

# 



STLOO3SRFLB PATENT PENDING




#### STL23 SERIES Miro-Flex<sup>™</sup> 4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Accepts standard PL-3 plugs
- Available in 12V and 24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP/1	FURN/TAIL - 12 DIODES	
STL23RB	STL23RBP	PL-3 connection, 12V	10
STL23CCRB	STL23CCRBP	Clear lens, red reflector, PL-3, 12V	10
STL23R24B	STL23R24BP	PL-3 connection, 24V	10
YEL		G/TURN SIGNAL - 16 DIODES	
STL23AB	STL23ABP	PL-3 connection, 12V	10
STL23A24B	STL23A24BP	PL-3 connection, 24V	10
	A	CCESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20





STL23AB	000	/




FMVSS	Red S T I; Yellow I P	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	Red: Yellow:	12.8VDC208 Stop/Turn, .013A Tail 24.0VDC171 Stop/Turn, .061A Tail 12.8VDC310 Turn, .046A Parking 24.0VDC171 Stop/Turn, .061A Tail
WT/DIMS WARRANTY	.265 lbs. / 4.313" x 4.313" x 1.938" Lifetime LED Warranty	



#### STL543 SERIES HyperX® 4" Round Sealed LED Stop/Turn/Tail Light

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Accepts standard PL-3 plugs
- 12 diodes and contemporary, automotive style optics

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP/	TURN/TAIL - 12 DIODES	
STL543RB	STL543RBP	PL-3 connection	10
	Α	CCESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20



HYPERX

STL543RB

U

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC208 Stop/Turn, .013A Tail
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.938"
WARRANTY	Lifetime LED Warranty



18 **Gptronics** 

#### STL55 SERIES High LED Count 4" R

#### High LED Count 4" Round Sealed Lights for Recess Mount

- Sonically sealed, waterproof
- 21 LEDs for high diode count appearance
- Mount in any 360 degree position
- Accepts standard PL-3 plugs; red available with optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP/	TURN/TAIL - 21 DIODES	
STL55RB	STL55RBP	Grommet mount, PL-3 connection	10
STL55RFMB	STL55RFMBP	Flange mount, weathertight connection	10
YEL	LOW PARKIN	G/TURN SIGNAL - 21 DIODES	
STL55AB	STL55ABP	Grommet mount, PL-3 connection	10
	A	CCESSORIES	
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20
FMVSS MATERIALS VOLT/AMP		Yellow I6 P nate lens and housing 12.8VDC208 Stop/Turn, .013A Tail 12.8VDC310 Turn, .046A Parking	
WT/DIMS WARRANTY	Flange mo	nount: .265 lbs. / 4.313" x 4.313" x 1.5" unt: .265 lbs. / 5.5" x 5.5" x 1.5" ED Warranty	




STL55RB






**otronics**)

19



HOLE CUT-OUT: 4.5"



HOLE CUT-OUT: 4.5"



#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	R	ED STOP/TUR	N/TAIL LIGHT - 22 DIODES	
	STL111RB	STL111RBP	PL-3	10
	STL111RMB	STL111RMBP	Weathertight	10
	STL111RHB	STL111RHBP	Hard wired	10
	STL111RCB	STL111RCBP	Clear lens, red diodes, PL-3	10
	STL111RCMB	STL111RCMBP	Clear lens, red diodes, weathertight	10
	YEL	LOW PARKING	/TURN SIGNAL - 22 DIODES	
	STL111AB	STL111ABP	PL-3	10
	STL111ACB	STL111ACBP	Clear lens, yellow diodes, PL-3	10
		AC	CESSORIES	
	A70GB	A70GBP	Grommet	50
	A45PB	A45PBP	Pigtail, 3-wire	100
	A47PB	A47PBP	Right angle pigtail, 3-wire	100
	A45PMB	A45PMBP	Weathertight pigtail	100
	AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
	BK70BB	BK70BBP	Black steel bracket	10
9	A77SB	A77SBP	Gray steel bracket	20
_			RETAIL	
	TLL112RK	Retail Ready	<b>Try Me</b> kit with (2) ea. STL111RB, A70GB and A47PB, clam	2
	FMVSS	Red S2 T2 I6; \		
	MATERIALS	•	lens and housing	
	VOLT/AMP		BVDC59A Stop/Turn, .295A Tail	
	WT/DIMS	Yellow: 12.8 .35 lbs. / 6.5" x	8VDC515A Turn, .27A Parking 2 25" x 1 75"	
	WARRANTY	Lifetime LED W		
	•6	7/16*		
			Incort	

HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

25/16\*



# STLITIRCB

STL111RB

GloLight

STOP/TURN

•

TAIL LIGHT

STL111ACB



TLL112RK

20 **Optronics** 

800-364-5483 / 918-683-9514

15/16\*

#### STL111 FLANGE MOUNT SERIES GloLight<sup>®</sup> 6" Sealed LED Lights with Mounting Flange

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Recess flange mount for security, theft reduction
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED	STOP/TURN/TA	AIL LIGHT - 22 DIODES	
STL111RFB	STL111RFBP	PL-3 connection	10
STL111RFMB	STL111RFMBP	Weathertight connection	10
STL111RCFB	STL111RCFBP	Clear lens, red diodes, PL-3	10
STL111RCFMB	STL111RCFMBP	Clear lens, red diodes, weathertight	10
	ACCE	SSORIES	
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
A111TRSSB	A111TRSSBP	Stainless steel trim ring	50



**otronics** 


STL111RFB

**GloLight** 

TAIL LIGHT

STOP/ TURN

FMVSS	Red S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC59 Stop/Turn, .295A Tail
WT/DIMS	.38 lbs. / 7.5" x 3.3" x 1.938"
WARRANTY	Lifetime LED Warranty



LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS

#### STL178 SERIES GloLight® 6" Sealed LED Stop/Turn/Tail Lights for Surface Mount

#### TAIL LIGHT PATEN • Son • Mo • Fla • Hai • Ava

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Flange surface mount-no panel cut-out required
- Hard wired, with optional molded connectors
- Available in tinted and clear lens models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
REI	D STOP/TURN/1	AIL LIGHT - 22 DIODES	
STL178RB	STL178RBP	Hard wired	10
STL178RFPB	STL178RFPBP	Hard wired, female PL-3 plug	10
STL178RCFPB	STL178RCFPBP	Clear lens & glow ring, red diodes, hard wired with female PL-3 connector	10
STL178RCCFPB	STL178RCCFPBP	Clear lens, red diodes, hard wired with female PL-3 connector	10
	ACCI	ESSORIES	
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
A178TRSSB	A178TRSSBP	Stainless steel trim ring	50



STL178RB


**GloLight** 

STL178RCFPB



FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC59 Stop/Turn, .295A Tail
WT/DIMS	.38 lbs. / 7.5" x 3.3" x 1.1"
WARRANTY	Lifetime LED Warranty






PATENTED **TECHNOLOGY** 

## **STL112 SERIES** GloLight<sup>®</sup> 6" Sealed LED Lights


- Unique mirrored reflector
- Sonically sealed, waterproof •
- Mount in any 360° position
- Accepts standard PL-3 connector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED	STOP/TURN/T	AIL LIGHT - 22 DIODES	
STL112RB	STL112RBP	PL-3 connection	10
	ACCE	SSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	S T I Polycarbonate len 12.8VDC59A S .38 lbs. / 6.438" x Lifetime LED Ward	top/Turn, .295A Tail 2.313" x 1.938"	



**GloLight** 

(B) (B) (B) (B)



# **STL512 SERIES** HD500<sup>™</sup> 6" Sealed LED Lights

- Sonically sealed, waterproof
- Available in tinted and clear lens models


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RI	ED STOP/TURN	/TAIL LIGHT - 18 DIODES	
STL512RB	STL512RBP	PL-3 connection	10
STL512RCB	STL512RCBP	Weathertight connection	10
	AC	CESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
FMVSS MATERIALS	•	lens and housing	
VOLT/AMP WT/DIMS	12.8VDC294A Stop/Turn, .024A Tail .262 lbs. / 6.50" x 2.313" x 1.84"		
WARRANTY	Lifetime LED Warranty		

500 BERIES



STL512RB











STL72RB

STL82RCB



· Sonically sealed, waterproof


.

- Kits include grommet and plug
- Mount in any 360 degree position
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RE	D STOP/TURN	TAIL LIGHT - 10 DIODES	
STL72RB	STL72RBP	PL-3 connection	10
STL72RKB	STL72RKBP	Kit with A70GB, PL-3	10
STL74RBK	STL74RBKP	Kit with A70GB & A47PB, PL-3	50
STL74RKB	STL74RKBP	Kit with A70GB & A45PB, PL-3	10
STL72RMB	STL72RMBP	Weathertight connection	10
STL82RCB	STL82RCBP	Clear lens, red diodes, PL-3	10
YELL	OW PARKING/	TURN SIGNAL - 10 DIODES	
STL72AB	STL72ABP	PL-3	10
STL72AMB	STL72AMBP	Weathertight connection	10
STL72CAB	STL72CABP	Clear lens, amber diodes, PL-3	10
	ACC	ESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
		RETAIL	
STL72RK	Retail Ready	12V kit with A70GB & A47PB, clam	6
STL72RS		12V, clam	6

Although the second sec	
VIEN BURNER VIEN	A7
2 * * * * 2	A4
A MARKED A	A4
STL72AB	A4
	AL
60000	Bk
	A7
N G G A	ST
110042	ST

STL72CAB



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

FMVSS	Red I6 P3 S2 T2; Yellow I6 P	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	Red: 12.8VDC243A Stop/Turn, .046A Tail	
	Yellow: 12.8VDC275A Turn, .042A Parking	
WT/DIMS	.309 lbs. / 6.438" x 2.313" x 1.75"	
WARRANTY	Lifetime LED Warranty	

24

800-364-5483 / 918-683-9514

#### **STL78/88 SERIES** 6" Oval Sealed LED Lights for Surface Mount

- · Sonically sealed, waterproof
- Mount in any 360 degree position
- Flange surface mount-no panel cut-out required
- Hard wired, with optional molded connectors

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RE	ED STOP/TURN	I/TAIL LIGHT - 10 DIODES	
STL78RB	STL78RBP	Hard wired	10
STL78RPG	STL78RPGP	.180 male bullets	10
STL78REZB	STL78REZBP	3-way female PL-3 plug	10
STL78RLPB	STL78RLPBP	Low profile 9/16" thick, female PL-3 plug, gasket included	10
STL88RCB	STL88RCBP	Clear lens, red diodes, hard wired	10
STL88RCPG	STL88RCPGP	Clear lens, red diodes, 3-way female PL-3 plug	10
YELL	OW PARKING	TURN SIGNAL - 10 DIODES	
STL78AB	STL78ABP	Hard wired	10
	AC	CESSORIES	
A78CB1	A78CB1P	Chrome flange cover	25
A78RXB	A78RXBP	Red reflex flange cover & gasket	25
		RETAIL	
STL78RK	RetailReady	Single light, clam	6






STL78RB



STL88RCB



FMVSS	Red I6 P3 S2 T2; Yellow I6 P	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	Red: 12.8VDC243A Stop/Turn, .046A Tail	
	Yellow: 12.8VDC275A Turn, .042A Parking	
WT/DIMS	STL78/88:.265 lbs. / 7.563" x 3.313" x 0.750"	
	STL78RLPB: .260 lbs. / 7.563" x 3.313" x .563"	
WARRANTY	Lifetime LED Warranty	




**ptronics** 

G



STL12RB





HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)



TLL12RK

#### **STL12 SERIES** FLEET Count<sup>™</sup> 6" Oval Sealed LED Stop/Turn/Tail Lights

Sonically sealed, waterproof

•

- Available with standard PL-3 or optional weathertight connection
- Retail kit includes light, grommet and plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
RED STOP/TURN/TAIL - 6 DIODES				
STL12RB	STL12RBP	PL-3 connection	10	
STL12RMB	STL12RMBP	Weathertight connection	10	
STL12RK2B	-	Kit: STL12RB, A45PB, & A60GB	10	
STL12RKB	-	Kit: STL12RB, A45PB, & A70GB	10	
	A	CCESSORIES		
A70GB	A70GBP	Grommet	50	
A45PB	A45PBP	Pigtail, 3-wire PL-3	100	
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100	
A45PMB	A45PMBP	Weathertight pigtail	100	
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50	
BK70BB	BK70BBP	Black steel bracket for STL12RB	10	
A77SB	A77SBP	Gray steel bracket for STL12RB	20	
		RETAIL		
STL12RK		Kit with A70GB & A47PB, clam	6	
STL12RS	RetailReady	Light only, clam	6	
TLL12RK		Kit with (2) each STL12RB, A70GB & A47PB, clam	2	

FMVSS	STI
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC161A Stop/Turn, .007A Tail
WT/DIMS	.375 lbs. / 6.5" x 2.25" x 1.75"
WARRANTY	Lifetime LED Warranty

#### STL73 SERIES FLEET Count<sup>™</sup> 6" Oval Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Flange surface mount is hard wired requiring no panel cut-out; includes ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
RED STOP/TURN/TAIL - 6 DIODES				
STL73RB	STL73RBP	Flange surface mount, hard wired	10	
STL73RKB	STL73RKBP	Kit with STL78RB and A73GB gasket	10	
	Α	CCESSORIES		
A78CB1	A78CB1P	Chrome flange cover	25	
		RETAIL		
STL73RK		Kit with STL73RB and A78CB1, clam	6	
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC1	e lens and housing 61A Stop/Turn, .007A Tail 563" x 3.313" x 0.75" Warranty		

### STL412 SERIES FLEET Count™ 6" Sealed LED Lights


- Sonically sealed, waterproof
- Mount in any 360° position
- Accepts standard PL-3 connector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RE	D STOP/TURN/	TAIL LIGHT - 4 DIODES	
STL412RB	STL412RBP	PL-3 connection	10
	ACCE	ESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
FMVSS	STI		
MATERIALS	Polycarbonate len	s and housing	
VOLT/AMP	12.8VDC161A	Stop/Turn, .007A Tail	
WT/DIMS	.375 lbs. / 6.438" x	x 2.313" x 1.75"	
WARRANTY	Lifetime LED War	ranty	





















#### **STLOO2 SERIES** ONE<sup>™</sup> 6" Sealed LED Lights

- Sonically sealed, waterproof •
- Mount in any 360 degree position •
- Available in grommet and flange mount models •

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
R	ED STOP/TUR	N/TAIL LIGHT - 1 DIODE	
STL002RB	STL002RBP	PL-3 connection	50
STL002RMB	STL002RMBP	Weathertight connection	50
STL002RFB	STL002RFBP	Flange mount, PL-3 connection	10
STL002RK2B	STL002RK2BP	Kit with A60GB and A47PB, PL-3	10
YEL	LOW PARKING	G/TURN SIGNAL - 1 DIODE	
STL002AB	STL002ABP	PL-3 connection	50
	ACO	CESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
		RETAIL	
STL002RK	RetailReady	Kit with grommet and plug, clam	6
STL002RS		Grommet mount light only, clam	6
TLL002RK	Set with (2) each	STL002RB, A70GB and A47PB, clam	2



AMPS

0


STL002RB

STL002AB 0

STL002RFB

HOLE CUT-OUT:	6.85" x 2.5"	(1.25'' R)

FMVSS	Red: S2 T2 I6, Yellow: I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC25A Stop/Turn, .007A Tail
WT/DIMS	Grommet mount: .262 lbs. / 6.50" x 2.313" x 1.875"
	Flange mount: .262 lbs. / 7.563" x 3.313" x 1.125"
WARRANTY	Lifetime LED Warranty




NO PANEL CUT-OUT REQUIRED


**tronics** 28


#### **STL22 SERIES** Miro-Flex<sup>™</sup> 6" Oval Sealed LED Lights

- Sonically sealed, waterproof •
- Mount in any 360 degree position •
- Accepts standard PL-3 plugs •
- Available with tinted or clear lens and chrome or tinted reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	RED STOP/TURN/TAIL - 12 DIODES			
STL22RB	STL22RBP	PL-3 connection	10	
STL22RBH	STL22RBHP	Hard wired	10	
STL22CCRB	STL22CCRBP	Clear lens, red reflector, PL-3	10	
STL22RCB	STL22RCBP	Clear lens, PL-3	10	
YEL	YELLOW PARKING/TURN SIGNAL - 16 DIODES			
STL22AB	STL22ABP	PL-3 connection	10	
STL22CCAB	STL22CCABP	Clear lens, yellow reflector, PL-3	10	
ACCESSORIES				
A70GB	A70GBP	Grommet	50	
A45PB	A45PBP	Pigtail, 3-wire PL-3	100	
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100	
BK70BB	BK70BBP	Black steel bracket	10	
A77SB	A77SBP	Gray steel bracket	20	
RETAIL				
TLL22RK	Retail Ready	Set with (2) each STL22RCB, A70GB & A47PB, clam	2	













STL22CCRB



STL22RCB




STL22AB



TLL22RK

www.optronicsinc.com





STL70AB

A47PB


BK70BB


A77SB

A47PBP

BK70BBP

A77SBP





DOLIVIT			QL I
	RED STOP	TURN/TAIL - 48 DIODES	
STL70RB	STL70RBP	PL-3 connection	10
YEL	LOW PARKIN	IG/TURN SIGNAL - 56 DIODES	
STL70AB	STL70ABP	PL-3 connection	10
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	Polycarbo Red: Yellow: .353 lbs. /	P2; Yellow I P2 P nate lens and housing 12.8VDC362 Stop/Turn, .013A Tail 12.8VDC400 Turn, .046A Parking 6.5" x 2.25" x 1.125" ED Warranty	
	STL572 8	STL70 ACCESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100

800-364-5483 / 918-683-9514

Right angle pigtail, 3-wire PL-3

Black steel bracket

Gray steel bracket

100

10

20


#### STL175 SERIES GloLight® 6" Oval Sealed LED E Rated Mid-Ship Turn Signal and Intermediate Marker Light

#### PATENTED TECHNOLOGY


- Sonically sealed, waterproof
- SAE "E" compliant–meets California requirements for mid-ship turn signal on vehicles 30 feet or longer
- · Weathertight connection standard

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	E RATE	D - 10 DIODES	
STL175AMFB	STL175AMFBP	Weathertight connection	10
	AC	CESSORIES	
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
A7TRSSB	A7TRSSBP	Stainless steel flange cover	20





FMVSS	E P2	
MATERIALS	Polycarbonate lens	and housing
VOLT/AMP	12.8VDC201A T	urn, .054 Marker
WT/DIMS	Grommet Mount:	.309 lbs. / 6.5" x 2.375" x 2.5"
	Flange Mount:	.309 lbs. / 7.875" x 3.313" x 2.5"
WARRANTY	Lifetime LED Warra	anty









STL71AMB

2.3/8

2.1/2

61/2

STL71/75 SERIES 6" Oval Sealed LED E Rated Mid-Ship Turn Signal and Intermediate Marker Light


- · Sonically sealed, waterproof
- SAE "E" compliant–meets California requirements for mid-ship turn signal on vehicles 30 feet or longer
- Weathertight connection standard


	1		
BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	E RATI	ED - 10 DIODES	
STL71AMB	STL71AMBP	Weathertight connection	10
STL75AMFB	STL75AMFBP	Flange, weathertight connection	10
	AC	CESSORIES	
A70GB	A70GBP	Grommet	50
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20
A7TRSSB	A7TRSSBP	Stainless steel flange cover	20



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

stl75amfb





HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

FMVSS	E P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC201A Turn, .054 Marker
WT/DIMS	Grommet Mount: .309 lbs. / 6.5" x 2.375" x 2.5"
	Flange Mount: .309 lbs. / 7.875" x 3.313" x 2.5"
WARRANTY	Lifetime LED Warranty

LED SEALED STOP/TURN/TAIL & PARKING/TURN SIGNALS

32 **Gptronic** 


800-364-5483 / 918-683-9514

#### STL75 SERIES 6" Oval Sealed LED E2 Rated Mid-Ship Turn Signal and Intermediate Marker Light

- Sonically sealed, waterproof
- "E2" rated for vehicles less than 30 feet in length
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	E2 RA	TED - 9 DIODES	
STL75AB	STL75ABP	PL-3 connection	10
STL75AMB	STL75AMBP	Weathertight connection	10
	AC	CESSORIES	
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77SB	A77SBP	Gray steel bracket	20

FMVSS	A E2 P2	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	12.8VDC141A Turn, .060 Marker	
WT/DIMS	PL-3 Connection: .309 lbs. / 6.5" x 2.313"	x 2.75"
	Weathertight: .309 lbs. / 6.5" x 2.313"	x 2.58"
WARRANTY	Lifetime LED Warranty	



ptronics



**STOP/TURN** 

#### STL133 SERIES GloLight® Sealed Rectangular LED Stop/Turn/Tail Lights

#### PATENTED TECHNOLOGY


- Sonically sealed, waterproof
- Accepts standard PL-3 plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP	P/TURN/TAIL - 14 DIODES	
STL133RB	STL133RBP	Grommet mount, PL-3 connection	10
	1	ACCESSORIES	
A33GB	A33GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC278A Stop/Turn, .135A Tail
WT/DIMS	.309 lbs. / 5.313" x 3.438" x 1.813"
WARRANTY	Lifetime LED Warranty

TAIL LIGHT

**GloLight** 



STL133RB



#### **STL33 SERIES** Sealed Rectangular LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Accepts standard PL-3 plugs
- Available in grommet mount and flange mount models
- Flange mount model is hard wired, with female PL-3 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY			
RED STOP/TURN/TAIL - 12 DIODES						
STL33RB	STL33RBP	Grommet mount, PL-3 connection	10			
STL34RB	STL34RBP	Kit: STL33RB, A33GB & A45PB	10			
STL33RFB	STL33RFBP	Flange mount, hard wired, PL-3 plug	10			
	A	ACCESSORIES				
A33GB	A33GBP	Grommet	50			
A45PB	A45PBP	Pigtail, 3-wire PL-3	100			
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100			







**STL33RB** 



FMVSS	S2 T2 I6				
MATERIALS	Polycarbonate lens and housing				
VOLT/AMP	12.8VDC405 Stop/Turn, .038A Tail				
WT/DIMS	STL33RB: .309 lbs. / 5.313" x 3.438" x 1.938"				
	STL33RFB: .287 lbs. / 6.125" x 4.25" x .875"				
WARRANTY	Lifetime LED Warranty				



STL33RFB



HOLE CUT-OUT: 5.453" X 3.578" (1" R)

35

www.optronicsinc.com





STL35RB


**STL35 SERIES** Sealed Rectangular LED Lights


- Sonically sealed, waterproof •
- Accepts standard PL-3 plugs .
- Available in red and amber
- Miro-Flex<sup>™</sup> combines smooth lens and faceted reflector design for a contemporary automotive appearance

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY				
RED STOP/TURN/TAIL - 16 DIODES							
STL35RB	STL35RBP	PL-3 connection	10				
YELLOW PARKING/TURN SIGNAL - 16 DIODES							
STL35AB	STL35ABP	PL-3 connection	10				
	ACCESSORIES						
A33GB	A33GBP	Grommet	50				
A45PB	A45PBP	Pigtail, 3-wire PL-3	100				
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100				



FMVSS	STL35RB:	S2 T2 I6				
	STL35AB:	16 P				
MATERIALS	Polycarbonat	e lens and housing				
VOLT/AMP	STL35RB:	12.8VDC301 Stop/Turn, .020A Tail				
	STL35AB:	12.8VDC301 Turn, .020A Parking				
WT/DIMS	.309 lbs. / 5.313" x 3.438" x 2.313"					
WARRANTY	Lifetime LED	Warranty				





HOLE CUT-OUT: 5.453" X 3.578" (1" R)

#### STL63 SERIES Thinline LED Stop/Turn/Tail Lights



STL63CRB

1 5/8"

3/4"

- Sonically sealed, waterproof
- Low profile design—only 5/8" thick
- Surface mount on 14-1/8" centers
- Hard wired with separate ground wire
- Available with tinted or clear lens

•	0	(C)	$(\Phi)$		0		ren	(G)	٢	D
•	-		-	-		-	ST	L63RB		D
G	(4)	105	(6)	101	0	(0)			101	0

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED S	STOP/TURN/TA	IL LIGHTS - 9 DIODES	6
STL63RB	STL63RBP	Red	10
STL63CRB	STL63CRBP	Clear lens, red diodes	10
FMVSS	STI		
MATERIALS	Polycarbonate	lens and housing	
VOLT/AMP	12.8VDC350	) Stop/Turn, .022A Tail	
WT/DIMS	.275 lbs. / 15" >	( 1.625" x .75"	
WARRANTY	Lifetime LED V	/arranty	



	• • • • • • • • • •
•	an e transie a sublima da esto
	STL69RB
50	0.0 0.0 0 0.0.0 0 0
5	147 + 147 + 1 - 2 M Fax + 15 + 17
	STL69RCB
•	

#### STL69 SERIES Thinline Sealed LED Stop/Turn/Tail Lights

- · Sonically sealed, waterproof
- Low profile design–only 5/8" thick
- Surface mount on 14-1/8" centers; optional gasket
- STL69RRXB meets SAE S2T2I6 for over 80" wide vehicles and has built-in reflex meeting SAE A
- Hard wired with separate ground wire; available with optional molded plugs

	STL69RRXB		BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
-	14 1/8*		RED	STOP/TURN/TA	IL LIGHTS - 11 DIODES	
0		● 1 3/8*	STL69RB	STL69RBP	Red	10
-	15"	► 5/8"	STL69RCB	STL69RCBP	Clear lens, red diodes	10
	STL69RB/RCB		STL69CRPG	STL69CRPGP	Clear lens, red diodes, .180 male bullets	10
1	14 1/8"	•	STL69RCBMCV2B	STL69RCBMCV2BP	Clear lens, red diodes, 3-way female plug, A69CB base	10
CT.		15/8"	STL69RRXB	STL69RRXBP	Built-in reflex	10
4	<b>15</b> *	▶ 5/8"		ACCE	SSORIES	
	JILOJKKAD		A69GB	A69GBP	Gasket	10
			A69CB	A69CBP	Chrome base for STL69	10
-	14 1/8"	1 5/8"	A69RXCB	A69RXCBP	Chrome base for STL69RRXB	10
<u>e</u>		1		RE	TAIL	
-	15"	-	STL69RS		Light only, clam	6
4	16 5/16"	•	STL69RK	RetailReady	STL69RB with A69CB, clam	6
	A69CB		STL69RRXCS		STL69RRXB with A69RXCB, clam	6
	14 1/8"					
e	15*	9↓ 15/8" ►5/8"	FMVSS	STL69: STL69RRXB: S	6 T I 62 T2 I6 A	
	A69RXCB	- 5/8	MATERIALS	Polycarbonate le	ens and housing	
			VOLT/AMP		350A Stop, .022 Tail 161A Stop, .013A Tail	
			WT/DIMS	STL69:	441 lbs. / 15" x 1.375" x .625"	

WARRANTY

STL69RRXB: .445 lbs. / 15" x 1.625" x .625"

Lifetime LED Warranty

#### STL179 SERIES GloLight<sup>®</sup> Streamline LED Light

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Low profile design—only 1-3/8" high x 1" thick
- Surface mount on 16-1/8" centers
- Hard wired with separate ground wire




TAIL LIGHT	
STOP/TURN	000000

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY			
	RED STOP	TURN/TAIL - 28 DIODES				
STL179RB	STL179RBP	Stop/turn/tail light	10			
ACCESSORIES						
A79CB	A79CBP	Chrome mounting base	10			



STL179RB

FMVSS	STI
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC634 Stop/Turn, .445A Tail
WT/DIMS	.353 lbs. / 17" x 1.375" x 1"
WARRANTY	Lifetime LED Warranty







#### STL79 SERIES Streamline Sealed LED Lights

- Sonically sealed, waterproof
- Low profile design—only 1-3/8" high x 1" thick
- Surface mount on 16-1/8" centers
- Available as stop/turn/tail lights and third brake lights
- Hard wired with separate ground wire




STL79RB/80RB



STL89RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY			
	RED STOP/TURN/TAIL - 11 DIODES					
STL79RB	STL79RBP	Stop/turn/tail light	10			
STL80RB	STL80RBP	Third brake light	10			
STL89RCB	STL89RCBP	Clear lens stop/turn/tail light	10			
	Α	CCESSORIES				
A79CB	A79CBP	Chrome mounting base	10			
	0	RETAIL				
STL79RS	RetailReady	Stop/turn/tail light, clam	6			
FMVSS MATERIALS VOLT/AMP	STL79/89: STL80: Polycarbon STL79/89:	U ate lens and housing				
WT/DIMS Warranty		12.8VDC216 Stop 17" x 1.375" x 1" D Warranty				





#### STL76 SERIES Thinline Sealed LED Stop/Turn/Tail Light for Over 80" Wide Applications

#### PATENTED TECHNOLOGY

- Replaceable, snap-on red lens
- Clear lens sonically sealed to housing making light completely waterproof
- Surface mount on 12-7/8" centers
- Meets SAE S2T2I6 for over 80" wide vehicles
- Hard wired with separate ground wire






STL76RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED STOP/TURN	I/TAIL LIGHT - 11 DIODES	
STL76RB	STL76RBP	Stop/turn/tail light	10

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8V / .275A Stop, .022A Tail
WT/DIMS	.529 lbs. / 13.26" x 2.13" x 1.42"
WARRANTY	Lifetime LED Warranty





41

www.optronicsinc.com

#### STL153 SERIES GloLight® LED Dual Face Pedestal Mount Lights

#### PATENTED TECHNOLOGY

- 25 LEDs per side
- Ring illuminates for tail light function; inner LEDs light and ring brightens for brake/turn
- Includes built-in 3-LED yellow side marker with reflex
- Hard wired, includes separate ground wire




**Glo**Light

BULK P/N POLYPACK P/N		DESCRIPTION	QTY
D	UAL FACE RED	YELLOW - 25 DIODES	
STL153ARDBB	STL153ARDBBP	Driver side	10
STL153ARPBB	STL153ARPBBP	Passenger side	10

6 3/8"

S2 T2 I6, I6 P, A P2
Chrome plastic housing, acrylic lens
12.8V / .360A Stop,030A Tail
1.477 lbs. / 4.688" x 4.875" x 2.438"
Lifetime LED Warranty







#### STL52/53 SERIES LED Pedestal Mount Lights

- Lead wires exit through mounting post; separate ground wire
- 21 LEDs per side
- STL53 available in driver and passenger side models with built-in yellow side marker with reflex


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DUAL FACE	RED YELLOW - 42 DIODES	
STL52ARB	STL52ARBP	Round	10
STL53ARPB	STL53ARPBP	Square, passenger side	10
STL53ARDB	STL53ARDBP	Square, driver side	10

FMVSS	STL52ARB:	STIP
	STL53:	Tail S T I P, Side Marker A P2
MATERIALS	STL52:	Die cast housing, polycarbonate lens
	STL53:	Polycarbonate lens and housing
VOLT/AMP	STL52ARB:	12.8VDC360 Stop/Turn, .030A Tail
	STL53:	12.8VDC750 Stop/Turn, .114A Tail
WT/DIMS	STL52:	1.477 lbs. / 4.25" x 4.25" x 1.938"
	STL53:	.882 lb. / 4.5" x 4.75" x 2.25"
WARRANTY	Lifetime LED	Warranty





STL52ARB




STL53ARDB/ARPB











LED COMBINATION TAIL LIGHTS & KITS


44 **Cptronics** 

#### **STL90 SERIES** 7" Round LED Transit Lights

- Sonically sealed, waterproof
- Surface mount light with mounting gasket
- Hard wired with separate ground wire
- Available in 12V and 12-24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
R	ED STOP/TURN	/TAIL LIGHT - 31 DIODES	
STL90RB	STL90RBP	Stop/turn/tail light, 12V	5
STL90R24B	STL90R24BP	Stop/turn/tail light, 12-24V	5
	YELLOW TUR	N SIGNAL - 31 DIODES	
STL90AB	STL90ABP	Parking/turn signal, 12V	5
STL90A24B	STL90A24BP	Parking/turn signal, 12-24V	5

FMVSS	Red S2 I6	T2 P2 A; Yellow I6 P2 A	
MATERIALS	Polycarbonate lens and housing		
VOLT/AMP	Red: 12.8VDC243A Stop/Turn, .046A Tail		
	Yellow:	12.8VDC275A Turn, .042A Parking	
WT/DIMS	.970 lb. / 7	7" x 7" x 1.438"	
WARRANTY	Lifetime L	ED Warranty	











45

www.optronicsinc.com

# GloLight<sup>.</sup>



#### STL161 SERIES GloLight® LED Combination Tail Lights

#### PATENTED TECHNOLOGY

- Stud mount stop/turn/tail light with built-in back-up light and reflex
- 30-LED tail light; 6-LED back-up light
- Driver side light also includes 3-LED license light
- Hard wired; wire exits through back of housing
- Includes ground wire

TA	11 1	<b>IGI</b>	17
IA	1L L		


STOP/TURN/BACK-UP


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GLO	LIGHT <sup>®</sup> COM	BINATION TAIL LIGHTS - 36 DIODES	
STL161RB	STL161RBP	Passenger side, 30-LED tail, 6-LED back-up	5
STL161RLB	STL161RLBP	Driver side with 3-LED license light	5

FMVSS	STL161RB: A I6 (2)R S2 (3)T STL161RLB: A I6 (2)R S2 (3)T L
MATERIALS	Acrylic lens, plastic housing
VOLT/AMP	12.8VDC - Tail .19A, Stop/Turn .30A, Back-up .21A
WT/DIMS	.882 lb. / 5.813" x 6.75" x 2.688"
WARRANTY	Lifetime LED Warranty



STL161RB





#### STL60/61 SERIES LED Combination Tail Lights

- Stud mount stop/turn/tail lights with built-in back-up light and reflex
- Choose from Optronics<sup>®</sup> LED 52-diode and FLEET Count<sup>™</sup> 15-diode tail lights
- Hard wired; wire exits through back of housing
- Includes ground wire

Includes ground wire					
	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	OPTI	RONICS® COM	<b>IBINATION TAIL LIGHTS - 52 DIODES</b>		
	STL60RB	STL60RBP	Passenger side, 16-LED tail, 36-LED back-up	5	
	STL60RLB	STL60RLBP	Driver side with 5-LED license light	5	
	FLEET	COUNT™ CO	MBINATION TAIL LIGHTS - 15 DIODE	S	
	STL61RB	STL61RBP	Passenger side, 9-LED tail, 6-LED back-up	5	
	STL61RLB	STL61RLBP	Driver side with 3-LED license light	5	




STL60RB





FMVSS	STL61RB:	A I6 (2)R S2 (3)T
	STL61RLB:	A I6 (2)R S2 (3)T L
MATERIALS	Acrylic lens, p	lastic housing
VOLT/AMP	12.8VDC - Tai	I .015A, Stop/Turn .308A, Back-up .328A
WT/DIMS	.882 lb. / 5.813	3" x 6.75" x 2.688"
WARRANTY	Lifetime LED \	Narranty




STL61RB











47

#### STL108/109 SERIES GloLight® LED Combination Tail Lights

#### PATENTED TECHNOLOGY

- Traditional style fits many applications
- Stud mount lights mount on 2" centers
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	A CALL	QTY	
COMBINATION TAIL LIGHTS - 25 DIODES					
STL108RB	STL108RBP	Passenger side		10	
STL109RB	STL109RBP	Driver side, 3-LED lice	ense light	10	
RETAIL					
TLL190RK		STL109RB, mounting <b>Ie</b> package, clam	RetailReady	2	

TAIL LIGHT





STL108/109RB



TLL190RK

FMVSS	Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - Stop/Turn .310A, Marker .230A
WT/DIMS	.970 lb. / 5.031" x 4.563" x 2.625"
WARRANTY	Lifetime LED Warranty







800-364-5483 / 918-683-9514

#### **STL8/9 SERIES** LED Combination Tail Lights

- Traditional style fits many applications
- Stud mount lights mount on 2" centers
- · Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 11 DIODES			
STL8RB	STL8RBP	Passenger side	10
STL8R3B	STL8R3BP	Passenger side, female PL-3 plug	10
STL9RB	STL9RBP	Driver side, 3-LED license light	10
STL9R3B	STL9R3BP	Driver side, 3-LED license light, female PL-3 plug	10
		RETAIL	
STL6RS	Passenger side	Retail Ready	6
STL7RS	Driver side with 3	-LED license light	6
TLL9RK Kit: STL8RB, STL9RB, 25-ft harness, license plate bracket, mounting hardware; clam			2
TLL90RK	Set: STL8RB, ST	L9RB, mounting hardware; clam	2

Œ	10	NIC	Ð
Ц	Į	D	D



49




STL8/9RB STL6/7RS



FMVSS	Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .259A, Marker .062A
WT/DIMS	.970 lb. / 5.25" x 4.75" x 2.688"
WARRANTY	Lifetime LED Warranty

F N N
















- Designed for over 80" wide applications
- Stud mount lights mount on 2" centers
- Hard wired, with separate ground wire


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
OVE	R 80 COMBINAT	ION TAIL LIGHTS - 18 DIODES	
STL2RB	STL2RBP	Passenger side	10
STL3RB	STL3RBP	Driver side, license light	10

ing -	0	
	52	1
		E)

STL2/3RB

FMVSS	Stop/Tail A(3) I(3) S(3) T, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .268A, Marker .059A
WT/DIMS	.970 lb. / 6.25" x 4.75" x 2.688"
WARRANTY	Lifetime LED Warranty
	-







#### STL008/009 SERIES ONE<sup>™</sup> LED Combination Tail Lights

- Sealed, waterproof design
- Traditional style fits many applications
- Stud mount lights mount on 2" centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
(	COMBINATION	TAIL LIGHTS - 1 DIODE	
STL008RB	STL008RBP	Passenger side	10
STL009RB	STL009RBP	Driver side	10
STL008RPG	STL008RPGP	Passenger side, .180 bullets	10
STL009RPG	STL009RPGP	Driver side, .180 bullets	10
		RETAIL	
STL008RS	Passenger side	Retail Ready	6
STL009RS	Driver side with 3	B-LED license light	6
TLL008RK	Set: STL008RB,	STL009RB, mounting hardware, clam	2






STL008RB



FMVSS	S T A. P2 A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .25A, Marker .062A
WT/DIMS	.970 lb. / 5.063" x 4.563" x 2.875"
WARRANTY	Lifetime LED Warranty



TLL008RK





STL28/29 SERIES

marker and side reflex

**Combination Tail Lights** 

Universal design fits many applications Stud mount lights mount on 2" centers Hard wired with separate ground wire

Miro-Flex<sup>™</sup> LED

.





STL29RB



STL28RB




STL28 is 6-function: stop, turn, tail, rear reflex, side

STL29 is 7-function: above plus license illuminator

IEB>	WATERPROOF LED
1	

TLL29RK

FMVSS	STL28:	Stop/Tail A I S T, Side Marker A P2
	STL29:	Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic le	ens and plastic housing
VOLT/AMP	STL28:	12.8VDC174A Stop/Turn, .054A Marker
	STL29:	12.8VDC174A Stop/Turn, .054A Marker
WT/DIMS	.750 lb./	5.25" x 5" x 2.625"
WARRANTY	Lifetime	LED Warranty



52 **Cotronics** 

PATENTED

**TECHNOLOGY** 

#### **STL116/117 SERIES GloLight® LED Low Profile Combination Tail Lights**

- Designed for marine trailer application •
- Sealed, waterproof construction •
- Universal mount .
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBINATION	N TAIL LIGHTS - 28 DIODES	
STL116RB	STL116RBP	Passenger side	10
STL117RB	STL117RBP	Driver side, with 6-LED license light	10
		RETAIL	
TLL170RK	Set: STL116RB, <b>Try Me</b> package	STL117RB, mounting hardware, e	2
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	Acrylic lens and 12.8VDC - Stop .816 lb. / 8" x 2.	•	



# LED COMBINATION TAIL LIGHTS & KITS

2.6"

TLL170RK

2.9"

#### STL14/15 SERIES FLEET Count<sup>™</sup> LED Low Profile **Combination Tail Lights**

- Designed for marine trailer application .
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

Lifetime LED Warranty


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBINATION	N TAIL LIGHTS - 12 DIODES	
STL14RB	STL14RBP	Passenger side	10
STL15RB	STL15RBP	Driver side, with 6-LED license light	10
FMVSS	STL14: A I S T,	P2 A; STL15: A I S T, P2 A, L	
MATERIAL	S Acrylic lens and	l plastic housing	
VOLT/AMP	12.8VDC - Stop	o/Turn .252A. Marker .135A	
WT/DIMS	.816 lb. / 8" x 2	.875" x 2.813"	








STL14/15RB





WARRANTY








STL17RB





STL16NTRB










**Optronics** 

STL16/17 SERIES	
<b>LED Combination Tail</b>	Lights

- Designed for marine trailer application
- Sealed, waterproof construction •
- Universal mount
- Hard wired, with separate ground wire
- STL16/17NTRB feature light tube technology . and SMD LED

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBINATION	I TAIL LIGHTS - 18 DIODES	
STL16RB	STL16RBP	Passenger side	10
STL17RB	STL17RBP	Driver side, with 4-LED license light	10
STL16NTRB	STL16NTRB	Passenger side, SMD LED	10
STL17NTRB	STL17NTRB	Driver side, SMD LED with 4-LED license light	10
	A	CCESSORIES	
AL16RB	AL16RBP	Tail light lens	50
AL17RB	AL17RBP	Side marker lens	50
RETAIL			
STL16RS	Passenger side, s	stainless hardware	6
STL17RS	Driver side with 4	-LED license light, stainless hardware	6
TLL160RK	Set: STL16RB, S	TL17RB, mounting hardware; clam	2
TLL16RK	,	IL17RB, 25-ft harness, license plate s steel mounting hardware; clam	2

FMVSS	STL16:	Stop/Tail A I S T P2 PC, Side Marker A P2
	STL17:	Stop/Tail A I S T P2 PC, Side Marker A P2, License L
MATERIALS	Acrylic le	ens and plastic housing
VOLT/AMP	STL16:	12.8VDC259A Stop/Turn, .062A Marker
	STL17:	12.8VDC268A Stop/Turn, .059A Marker
WT/DIMS	.816 lb. /	8.063" x 2.875" x 2.813"
WARRANTY	Lifetime	LED Warranty



#### STL0016/0017 SERIES ONE<sup>™</sup> LED Combination Tail Lights

- Designed for marine trailer application •
- Sealed, waterproof construction •
- Universal mount .
- Hard wired, with separate ground wire .

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBIN	ATION TAIL LIGHTS	
STL0016RB	STL0016RBP	Passenger side	10
STL0017RB	STL0017RBP	Driver side, with license light	10
		RETAIL	
STL0016RS	Passenger side,	clam	6
STL0017RS	Driver side with 4	-LED license light, clam	6
TLL0016RK	Set: STL0016RB	, STL0017RB, mounting hardware, clam	2
FMVSS	·	I A I S T P2, Side Marker A P2	
	STL0017:Stop/Tai	IAISTP2, Side Marker AP2, License L	
MATERIALS	Acrylic lens and pl	astic housing	
VOLT/AMP	STL0016:12.8VD0	C31A Stop/Turn, .12A Marker	
	STL0017:12.8VD0	C32A Stop/Turn, .26A Marker	
WT/DIMS	.816 lb. / 8.0" x 2.9	)" x 2.6"	
WARRANTY	Lifetime LED Warr	anty	

8







13/16 27/8"



TLL0016RK



www.optronicsinc.com



LED COMBINATION TAIL LIGHTS & KITS

#### STL26/27 SERIES Miro-Flex<sup>™</sup> LED Combination Tail Lights

Concession of	125022302230023002	
		-

Designed	for	marina	trailor	application
Designed	101	manne	trailer	application

- Sealed, waterproof construction
- Universal mount

•

Hard wired, with separate ground wire

STL26RB




STL27RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
(	COMBINATION 1	TAIL LIGHTS - 14 DIODES	
STL26RB	STL26RBP	Passenger side	10
STL27RB	STL27RBP	Driver side with 4-LED license light	10
		RETAIL	
TLL26RK	Set: STL26RB, S	TL27RB, mounting hardware; clam	2
Retail	leady		

FMVSS	STL26: A I6 S2 (3)T PC		
	STL27: A I6 S2 (3)T PC L		
MATERIALS	Acrylic lens and plastic housing		
VOLT/AMP	STL26: 12.8VDC167A Stop/Turn, .054A Marker		
	STL27: 12.8VDC167A Stop/Turn, .107A Marker/License		
WT/DIMS	.882 lb. / 8.063" x 2.938" x 2.688"		
WARRANTY	Lifetime LED Warranty		



TLL26RK



56 **Gptronics** 

#### STL36/37 SERIES LED Combination Tail Lights

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBINATION	TAIL LIGHTS - 17 DIODES	
STL36RB	STL36RBP	Passenger side	20
STL36RPG	STL36RPGP	Passenger side, dual plug and ground eyelet	20
STL37RB	STL37RBP	Driver side, 6-LED license light	20
STL37RPG	STL37RPGP	Driver side, 6-LED license light, dual plug and ground eyelet	20
		RETAIL	
STL36RS	Passenger side	RetailReady	6
STL37RS	Driver side with 4-	LED license light	6
TLL36RK	marker lights with	L37RB, (2) MCL91AK sealed yellow chrome bases, 25-ft harness, license nless steel mounting hardware; clam	2






STL36/37RB



TLL36RK



FMVSS	STL36:	Stop/Tail A S T I P2, Side Marker A PC	
	STL37:	Stop/Tail A S T I P2, Side Marker A PC, License L	
MATERIALS	Acrylic lens and plastic housing		
VOLT/AMP	12.8VDC181A Stop/Turn, .047A Marker		
WT/DIMS	.992 lb. / 7.875" x 3.25" x 2.875"		
WARRANTY	Lifetime LED Warranty		







www.optronicsinc.com



#### STL56/57 SERIES LED Combination Tail Lights

- Designed for marine trailer application •
- Sealed, waterproof construction .
- Universal mount •
- Hard wired, with separate ground wire
- Stainless steel hardware .



00

TL56/57RB
-----------


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	COMBINATION	TAIL LIGHTS - 18 DIODES	
STL56RB	STL56RBP	Passenger side	10
STL57RB	STL57RBP	Driver side, 5-LED license light	10
		RETAIL	
TLL56RK		L57RB, 25-ft harness, license plate steel mounting hardware; clam	2



FMVSS	STL56:	Stop/Tail A S T I P2, Side Marker A P2
	STL57:	Stop/Tail A S T I P2, Side Marker A P2, License L
MATERIALS	Acrylic le	ns and plastic housing
VOLT/AMP	STL56:	12.8VDC259A Stop/Turn, .062A Marker
	STL57:	12.8VDC268A Stop/Turn, .059A Marker
WT/DIMS	.816 lb. / 6.063" x 3.625" x 2.25"	
WARRANTY	Lifetime LED Warranty	

TLL56RK





RBL10AS	e/Beac	on Light		en L			
<ul><li>Magnetic m</li><li>12-ft. coil co</li></ul>	ount ord with pow	er plug					
BULK P/N POLY	PACK P/N E	ESCRIPTION	QT	Y			
		RETAIL					
RBL10AS Amb	er rotary beacon	12/24V, clam	2 2				
	-30VDC Ib. / 5.125" x 5.1	125" x 3.5"			RBLIOAS		
WARRANTY Life	etime LED Warra	inty					
RBL10C	4	1000		ଙ୍କ		_	

# LED Multi-Function Strobe/Beacon Light

- Sonically sealed
- Five flash patterns
- Surface mount
- Operating range 9-36VDC
- SAE J845/EMC R10 approved •

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
RBL10CA	-	Clear lens, amber rotary beacon	1
FMVSS	W3-1		
MATERIALS	Polycarbonate		
VOLT/AMP	12.8VDC - 1.04/	12.8VDC - 1.04A, 36.0VDC - 0.36A	
WT/DIMS	1.53 lb. / 6.377" x 6.377" x 4.173"		
WARRANTY	Lifetime LED Wa	arranty	





**RBL10CA** 

# **TLL21/31 SERIES LED Magnet Mount Towing Light Kits**



Sonically sealed, waterpoof



FMVSS	STI
MATERIALS	Polycarbonate
VOLT/AMP	12.8VDC360A Stop/Turn, .030A Tail
WT/DIMS	2 lbs. / 3.875" x 2.188" x 6"
WARRANTY	Lifetime LED Warranty



**optronics** 

59



LED DOT COMPLIANT BACK-UP LIGHTS





BUL101CB


#### BUL101 SERIES GloLight® 4" Round Sealed DOT LED Back-Up Lights

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK-	UP LIGHTS - 21 DIODES	
BUL101CB	BUL101CBP	Standard 2-pin connection	10
BUL101CKB	BUL101CKBP	Kit with A45GB and A49PB	10
	AC	CESSORIES	
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20

HOLE CUT-OUT: 4.5"



#### BULO6 SERIES FLEET Count<sup>™</sup> 4" Round Sealed DOT LED Back-Up Lights

- · Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

	A CONTRACTOR		
BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		C-UP LIGHTS - 6 DIODES	
BUL06CB	BUL06CBP	Grommet mount, 2-pin connection	10
BUL06CKB	BUL06CKBP	Kit with A45GB and A49PB, 2-pin	10
BUL06CMB	BUL06CMBP	Grommet mount, weathertight connection	10
BUL06CFB	BUL06CFBP	Flange mount, 2-pin connection	10
BUL06CFMB	BUL06CFMBP	Flange mount, weathertight connection	10
	AC	CESSORIES	
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20
FMVSS MATERIALS VOLT/AMP WT/DIMS	12.8VDC - 0.18 Grommet mou	lens and housing 80A nt: .309 lbs. / 4.25" x 4.25" x 1.625" .350 lbs. / 5.5" x 5.5" x 1.875"	

Lifetime LED Warranty






BUL06CFB



HOLE CUT-OUT: 4.528"



HOLE CUT-OUT: 4.579"

**tro**nics

61

www.optronicsinc.com

WARRANTY



#### **BULOO3 SERIES** ONE<sup>™</sup> 4" Round Sealed DOT **LED Back-Up Lights**

- Sonically sealed, waterproof .
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK	-UP LIGHTS - 1 DIODE	
BUL003CB	BUL003CBP	Grommet mount, 2-pin connection	10
BUL003CKB	BUL003CKBP	Kit with A45GB grommet and A45CB pigtail	10
	AC	CESSORIES	
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100


BUL003CB

**Optronics** 

62

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC030A
WT/DIMS	.22 lbs. / 4.313" x 4.313" x 2"
WARRANTY	Lifetime LED Warranty





800-364-5483 / 918-683-9514


#### **BUL11 SERIES** 4" Round Sealed Clear DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- Available in grommet and flange mount models
- Grommet mount version available with standard 2-pin, or optional weathertight connection
- Grommet mount version available in 12V and 24V

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
(		UP LIGHTS - 10 DIODES		
BUL11CB	BUL11CBP	12V, two-pin connection	10	
BUL11CKB	BUL11CKBP	12V kit: BUL11CB, A45GB & A49PB	10	
BUL11CMB	BUL11CMBP	12V, weathertight connection	10	
BUL11CM24B	BUL11CM24BP	24V, weathertight connection	10	
CLEAR	CLEAR BACK-UP LIGHT WITH REFLEX - 10 DIODES			
BUL11CBX	BUL11CBXP	12V, two-pin connection	10	
ACCESSORIES				
A45GB	A45GBP	Grommet	50	
A45CB	A45CBP	Pigtail, 2-wire	100	
A49PB	A49PBP	Right angle pigtail, 2-wire	100	

FMVSS	(2) R		
MATERIALS	Polycarbonate lens and housing		
VOLT/AMP	12.8VDC - 0.26A		
WT/DIMS	BUL11CB/CKB:	.309 lbs. / 4.313" x 4.313" x 1.625"	
	BUL11CMB/CM24B:	.309 lbs. / 4.313" x 4.313" x 1.625"	
	BUL11CBX:	.353 lbs. / 5.75" x 5.75" x 1.625"	
WARRANTY	Lifetime LED Warrantv	/	






BUL11CB

HOLE CUT-OUT: 4.5"



**tro**nics.



HOLE CUT-OUT: 4.5"







#### BUL23/53 SERIES 4" Round Sealed Clear DOT LED Back-Up Lights



- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- High diode count; choose from 27- or 36-LED models
- 27-LED version available in 12V and 24V

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK	-UP LIGHTS - 27 DIODES	
BUL23CB	BUL23CBP	12V, two-pin connection	10
BUL23C24B	BUL23C24BP	24V, two-pin connection	10
		K-UP LIGHT - 36 DIODES	
BUL53CB	BUL53CBP	12V, two-pin connection	10
BUL53CKB	BUL53CKBP	12V Kit: BUL53CB, A45GB & A49PB	10
	A	CCESSORIES	
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100



FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	BUL23: 12.8VDC - 0.145A
	BUL53: 12.8VDC - 0.275A
WT/DIMS	.309 lbs. / 4.313" x 4.313" x 2"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 4.5"

#### BUL111 SERIES GloLight® 6" Oval Sealed DOT LED Back-Up Lights

#### PATENTED TECHNOLOGY


- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK	-UP LIGHTS - 22 DIODES	
BUL111CB	BUL111CBP	Standard two-pin connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

**GloLig**ht



FMVSS(2) RMATERIALSPolycarbonate lens and housingVOLT/AMP12.8VDC - 0.386AWT/DIMS.265 lbs. / 6.5" x 2.375" x 1.75"WARRANTYLifetime LED Warranty



HOLE CUT-OUT: 6.85" x 2.52" (1.26" R)



www.optronicsinc.com

optronics.







LED DOT COMPLIANT BACK-UP LIGHTS





BUL12CFB

#### **BUL12 SERIES** FLEET Count<sup>™</sup> 6" Oval Sealed **DOT LED Back-Up Lights**


- Sonically sealed, waterproof •
- Available with standard or weathertight connection
- Flange mount models available for recess or surface mount installation
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK	-UP LIGHTS - 6 DIODES	
BUL12CB	BUL12CBP	Recess mount, 2-pin	10
BUL12CFB	BUL12CFBP	Recess flange mount, 2-pin	10
BUL12CKB	BUL12CKBP	Kit with A70GB and A45CB, 2-pin	10
BUL12CSB	BUL12CSBP	Surface flange mount, hard wired	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A78CB1	A78CB1P	Chrome trim ring, snap-on	25






**FMVSS** (2) R MATERIALS Polycarbonate lens and housing VOLT/AMP 12.8VDC - 0.260A WT/DIMS .265 lbs. / 6.5" x 2.25" x 1.75" WARRANTY Lifetime LED Warranty



BUL12CSB



BUL12CB



#### BULOO2 SERIES ONE<sup>™</sup> 6" Oval Sealed DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	CLEAR BACK	-UP LIGHTS - 1 DIODE	
BUL002CB	BUL002CBP	Standard two-pin connection	10
BUL002CM3B	BUL002CM3BP	Weathertight connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PMB	A45PMBP	Pigtail, weathertight	50





BUL002CB

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.30A
WT/DIMS	.265 lbs. / 6.5" x 2.375" x 1.75"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" x 2.52" (1.26" R)




67

www.optronicsinc.com



BUL10CB




HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)



BUL22CB



BUL52CB



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)

#### **BUL10/22/52 SERIES** 6" Oval Sealed Clear DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- Low to high diode count; choose from 10-, 27- or 36-LED models
- Accept standard two-pin plugs; BUL10 available with standard or weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CI	LEAR BACK-U	P LIGHTS - 10 DIODES	
BUL10CB	BUL10CBP	Standard two-pin connection	10
BUL10CMB	BUL10CMBP	Weathertight connection	10
C	LEAR BACK-L	JP LIGHT - 27 DIODES	
BUL22CB	BUL22CBP	Standard two-pin connection	10
C	LEAR BACK-L	JP LIGHT - 36 DIODES	
BUL52CB	BUL52CBP	Standard two-pin connection	10
	ACC	ESSORIES	
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PMB	A45PMBP	Pigtail, weathertight	50
510/00			
FMVSS	(2) R		
MATERIALS	•	e lens and housing	
VOLT/AMP	BUL10:	12.8VDC - 0.260A	
	BUL22:	12.8VDC - 0.125A	
	BUL52:	12.8VDC - 0.275A	
WT/DIMS	BUL10:	.265 lbs. / 6.438" x 2.25" x 1.75"	
	BUL22/52:	.397 lbs. / 6.5" x 2.313" x 1.813"	
WARRANTY	Lifetime LED	Warranty	

#### BUL35/90 SERIES Sealed Clear DOT LED Back-Up Lights


- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- BUL35 is 5.5" x 3.5" recess mount model that accepts standard two-pin plugs
- BUL90 is 7" surface mount model, hard wired, with separate ground wire; designed for transit vehicles

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLE	AR 5.5" x 3.5"	BACK-UP LIGHT - 16 DIODES	
BUL35CB	BUL35CBP	Standard two-pin connection, 12V	10
C	CLEAR 7" BAC	K-UP LIGHT - 42 DIODES	
BUL90CB	BUL90CBP	12V, hard wired	5
BUL90C24B	BUL90C24BP	24V, hard wired	5
ACCESSORIES			
A33GB	A33GBP	Grommet for BUL35CB	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100


FMVSS	(2) R	
MATERIALS	Polycarbona	ate lens and housing
VOLT/AMP	BUL35:	12.8VDC - 0.295A
	BUL90:	12.8VDC - 0.301A
	BUL90: 2	24.0VDC - 0.089A
WT/DIMS	BUL35: .	397 lbs. / 5.313" x 3.438" x 2.313"
	BUL90: .	970 lbs. / 7" x 7" x 1.438"
WARRANTY	Lifetime LE	D Warranty








HOLE CUT-OUT: 5.462" x 3.562" (1" R)





**otronics** 

69

www.optronicsinc.com








SLL43AB1 SLL43AB2

#### SLL43 SERIES 4" Round Sealed LED Warning Lamps

- Sonically sealed, waterproof
- Flashing lights with triple-flash function, meeting SAE J595 and J845 standards for Class 2 and Class 3 directional warning lamps
- Use two Function 1 or Function 2 lights for synchronous flashing or pair a Function 1 with a Function 2 light for alternating flash pattern
- Accepts standard PL-3 plugs
- Operating voltage 9-30VDC, suitable for 12V or 24V systems

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
4" ROUND WARNING LAMPS - 22 DIODES			
SLL43AB1	SLL43AB1P	12V-24V Function 1	10
SLL43AB2	SLL43AB2P	12V-24V Function 2	10
SLL43AKB1	SLL43AKB1P	12V-24V Function 1, kit with A45GB & A45PB	10
SLL43AKB2	SLL43AKB2P	12V-24V Function 2, kit with A45GB & A45PB	10
ACCESSORIES			
A45GB	A45GBP	Grommet, 4" round	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100



HOLE CUT-OUT: 4.5"

FMVSS	W-2	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	12.8VDC - 0.56A	
WT/DIMS	.60 lbs. / 4.25" x 4.25" x 1.75"	
WARRANTY	Lifetime LED Warranty	

#### SLL72 SERIES 6" Oval Sealed LED Warning Lamps

- Sonically sealed, waterproof
- Flashing lights with triple-flash function, meeting SAE J595 and J845 standards for Class 2 and Class 3 directional warning lamps
- Use two Function 1 or Function 2 lights for synchronous flashing or pair a Function 1 with a Function 2 light for alternating flash pattern
- Accepts standard PL-3 plugs
- Operating voltage 9-30VDC, suitable for 12V or 24V systems








SLL72AB1 SLL72AB2

**otronics**)

71


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
6	" OVAL WARN	ING LAMPS - 22 DIODES	
SLL72AB1	SLL72AB1P	12V-24V Function 1	10
SLL72AB2	SLL72AB2P	12V-24V Function 2	10
SLL72AKB1	SLL72AKB1P	12V-24V Function 1, kit with A70GB & A45PB	10
SLL72AKB2	SLL72AKB2P	12V-24V Function 2, kit with A70GB & A45PB	10
ACCESSORIES			
A70GB	A70GBP	Grommet, 6" oval	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

FMVSS	W-2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.54A
WT/DIMS	.62 lbs. / 6.5" x 2.375" x 1.75"
WARRANTY	Lifetime LED Warranty





HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)



**SLL93 SERIES** 

•

FMVSS MATERIALS

VOLT/AMP WT/DIMS

WARRANTY

7" Round LED Warning Lights for Surface Mount

Acrylic lens, die cast aluminum base plate

8-LED school bus warning lights

W2 SAE J887

12.8VDC - 2.0A

Sealed, waterproof design






BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	RED WARNIN	G LIGHTS - 8 DIODES		
SLL93RB	SLL93RBP	Warning light, 12V	5	
	YELLOW WARN	IING LIGHTS - 8 DIODES		
SLL93AB	SLL93ABP	Warning light, 12V	5	
ACCESSORIES				
A94VB	A94VBP	Black Steel Visor	25	

Acrylic len, die cast aluminum base

1.3875lb. / 7.25" x 7.25" x 1.9"

Lifetime LED Warranty







SLL93AB with A94VB

72 **Cotronics** 

## GloLight® M1 SERIES 6.5" LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sealed, waterproof design
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 13 DIODES	
11212307B	11212355P	.180 male bullets	50
11212376B	11212356P	Clear lens, .180 male bullets	50
-	11212335P	Kit: .180 male bullets, chrome bezel	10
-	11212336P	Clear lens kit: .180 male bullets, chrome bezel	10
	R	ED - 13 DIODES	
11212309B	11212357P	.180 male bullets	50
11212378B	11212358P	Clear lens, .180 male bullets	50
-	11212337P	Kit: .180 male bullets, chrome bezel	10
-	11212338P	Cleanr lens kit: .180 male bullets, chrome bezel	10
	ł	ACCESSORIES	
00212317B	00212327P	Bezel	200/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.12A
WT/DIMS	.132 lbs. / 6.625" x 2.188" x 1"
WARRANTY	Three Year Warranty






M1 LED WITH BEZEL



M1 CLEAR LENS LED WITH BEZEL



HOLE CUT-OUT: 1.5"

ptronics

G

73



MILLENNIUM SERIES



M3 LED WITH BEZEL



M3 CLEAR LENS LED WITH BEZEL


## GloLight® M3 SERIES 3" LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

•

- Sealed, waterproof design
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YE	LLOW - 5 DIODES	
11212207B	11212255P	.180 male bullets	50
11212276B	11212256P	Clear lens, .180 male bullets	50
-	11212235P	Kit: .180 male bullets with chrome bezel	10
-	11212236P	Clear lens kit: .180 male bullets with chrome bezel	10
		RED - 5 DIODES	
11212209B	11212257P	.180 male bullets	50
11212278B	11212258P	Clear lens, .180 male bullets	50
-	11212237P	Kit: .180 male bullets with chrome bezel	10
-	11212238P	Clear lens kit: .180 male bullets with chrome bezel	10
		ACCESSORIES	
00212217B	00212227P	Bezel	500/20



FMVSSP2MATERIALSPolycarbonate lens, housing and bezelVOLT/AMP12.8VDC - 0.12AWT/DIMS.132 lbs. / 3" x 2" x 1"WARRANTYThree Year Warranty

HOLE CUT-OUT: 1.375"



## GloLight® M5 SERIES 4" LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sealed, waterproof design
- · Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW - 6 DIODES		
11212700B	11212708P	.180 male bullets	10
11212702B	11212710P	Clear lens, .180 male bullets	10
	11212704P	Kit: .180 male bullets with chrome bezel	10
-	11212706P	Clear lens kit: .180 male bullets with chrome bezel	10
		RED - 6 DIODES	
11212701B	11212709P	.180 male bullets	10
11212703B	11212711P	Clear lens, .180 male bullets	10
-	11212705P	Kit: .180 male bullets with chrome bezel	10
-	11212707P	Clear lens kit: .180 male bullets with chrome bezel	10
		ACCESSORIES	
00212717B	00212727P	Bezel	500/20






M5 LED WITH BEZEL



M5 CLEAR LENS LED WITH BEZEL

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.033A
WT/DIMS	.066 lb. / 4.156" x 1.5" x .75"
WARRANTY	Three Year Warranty





OTY



#### M1 SERIES Millennium Series® 6.5" Sealed LED Marker/Clearance Lights

• Sealed, waterproof design

BIIIK P/N

Hard wired, includes separate ground wire

POLYPACK P/N DESCRIPTION

- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel



M1 CLEAR LENS LED WITH BEZEL






M1 CLEAR LENS LED WITH BEZEL

BULK P/N	PULTPACK P/N	DESCRIPTION	QIT
	Y	ELLOW - 4 DIODES	
00212307B	00212355P	.180 male bullets	50/10
00212376B	00212356P	Clear lens, .180 male bullets	50/10
-	00212335P	Kit: .180 male bullets, bezel	10
-	00212336P	Kit: Clear lens, .180 male bullets, bezel	10
-	00212365P	Metripack connector	10
-	00212345P	Kit: Metripack connector, bezel	10
-	00212346P	Kit: Clear lens, metripack connector, bezel	10
		RED - 4 DIODES	
00212309B	00212357P	.180 male bullets	50/10
00212378B	00212358P	Clear lens, .180 male bullets	50/10
-	00212337P	Kit: .180 male bullets, bezel	10
-	00212338P	Kit: Clear lens, .180 male bullets, bezel	10
00212316B	00212367P	Metripack connector	100/10
00212386B	00212368P	Clear lens, metripack connector	100/10
-	00212347P	Kit: Metripack connector, bezel	10
		ACCESSORIES	
00212317B	00212327P	Bezel	200/20





FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.12A
WT/DIMS	.132 lbs. / 6.625" x 2.188" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1.5"



76

#### M3 SERIES Millennium Series® 3" Sealed LED Marker/Clearance Lights

• Sealed, waterproof design

P2

12.8VDC - 0.36A

.132 lbs. / 3" x 2" x 1"

Three Year Warranty

FMVSS MATERIALS

VOLT/AMP

WT/DIMS WARRANTY

- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 2 DIODES			
00212207B	00212255P	.180 male bullets	50/10
00212276B	00212256P	Clear lens, .180 male bullets	50/10
-	00212235P	Kit: .180 male bullets, bezel	10
-	00212236P	Kit: Clear lens, .180 male bullets, bezel	10
00212213B	00212263P	Clear lens, metripack connector	50/10
		RED - 2 DIODES	
00212209B	00212257P	.180 male bullets	50/10
00212278B	00212258P	Clear lens, .180 male bullets	50/10
-	00212237P	Kit: .180 male bullets, bezel	10
-	00212238P	Kit: Clear lens, .180 male bullets, bezel	10
-	00212254P	Clear lens, metripack connector	100
		ACCESSORIES	
00212217B	00212227P	Bezel	500/20





M3 LED WITH BEZEL



M3 CLEAR LENS LED WITH BEZEL



M3 LED WITH BEZEL




M3 CLEAR LENS LED WITH BEZEL

144



**otronics** 

77



Polycarbonate lens, housing and bezel

HOLE CUT-OUT: 1.375"

www.optronicsinc.com








M4 LED MARKER/CLEARANCE LIGHTS WITH BEZEL

#### M4 SERIES Millennium Series® 9" Sealed LED Lights

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Chrome trim ring included in kits or available separately

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELL	OW MARKER	CLEARANCE - 6 DIODE	S
00212104B	00212155P	.180 male bullets	10
-	00212135P	Kit: .180 male bullets, bezel	10
RED MARKER/CLEARANCE - 6 DIODES			
-	00212157P	.180 male bullets	10
-	00212137P	Kit: .180 male bullets, bezel	10
ACCESSORIES			
00212117B	00212127P	Bezel	70/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.090A
WT/DIMS	.132 lbs. / 9" x 3.25" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 2.5"

#### M5 SERIES Millennium Series® 4" Sealed LED Marker/Clearance Lights

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	Y	ELLOW - 3 DIODES	
00212700B	00212708P	.180 male bullets	10
00212702B	00212710P	Clear lens, .180 male bullets	10
	00212704P	Kit: .180 male bullets, bezel	10
-	00212706P	Kit: Clear lens, .180 male bullets, bezel	10
	00212712P	Clear lens, metripack connector	10
		RED - 3 DIODES	
00212701B	00212709P	.180 male bullets	10
00212703B	00212711P	Clear lens, .180 male bullets	10
-	00212705P	Kit: .180 male bullets, bezel	10
-	00212707P	Kit: Clear lens, .180 male bullets, bezel	10
		ACCESSORIES	
00212717B	00212727P	Bezel	500/20





M5 LED WITH BEZEL



M5 CLEAR LENS LED WITH BEZEL




M5 LED WITH BEZEL



M5 CLEAR LENS LED WITH BEZEL



FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.033A
WT/DIMS	.066 lb. / 4.156" x 1.5" x .75"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1"







79

Recess mount lights with theft-deterrent mounting design

Easy to install: insert light into mounting hole and secure

PC rated: fulfills requirement for marker and clearance

PC Rated

3/4" Sealed LED Marker/Clearance

Lights with Theft-Deterrent Design

**MCL11S SERIES** 

PATENTED TECHNOLOGY

with locking ring

•

•

•

•

Sealed, waterproof design

light when properly mounted







**MCL11SAKB** 






**otronics** 

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 1 DIODE	
MCL11SAB	MCL11SABP	Light with gasket, .180 bullets	50
MCL11SAKB	MCL11SAKBP	Light with gasket and locking ring .180 bullets	50
MCL11SAK1B	MCL11AK1BP	Light with gasket and locking ring	50
RED - 1 DIODE			
MCL11SRB	MCL11SRBP	Light with gasket, .180 bullets	50
MCL11SRKB	MCL11SRKBP	Light with gasket and locking ring .180 bullets	50
MCL11SRK1B	MCL11SRKBP	Light with gasket and locking ring	50
ACCESSORIES			
A11SRB	A11SRBP	Stainless steel locking ring	100

FMVSS	PC
MATERIALS	Polycarbonate lens and housing, stainless steel locking ring, EPDM rubber gasket
VOLT/AMP	12.8VDC06A
WT/DIMS	.10 lbs. / 1" x 1" x .875"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: .75"



#### MCL110 SERIES GloLight® Uni-Lite™ 3/4" LED Non-Directional Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sealed, waterproof design
- PC rated when mounted in any direction 360 degrees!
- Hard wired, includes separate ground wire
- Choose from light only or kit with A11GB grommet

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW - F	PC RATED - 2 DIODES	
MCL110AB	MCL110ABP	Light only	50
MCL110AKB	MCL110AKBP	Light with A11GB grommet	50
MCL110AKBF	MCL110AKBFP	Light kit with grommet, .156 female barrels on 8" leads	50
MCL110AKPG	MCL110AKPGP	Light with grommet, .180 bullets	50
	RED - PC	RATED - 2 DIODES	
MCL110RB	MCL110RBP	Light only	50
MCL110RKB	MCL110RKBP	Light with A11GB grommet	50
MCL110RKBF	MCL110AKBFP	Light kit with grommet, .156 female barrels on 8" leads	50
MCL110RKPG	MCL110RKPGP	Light with grommet, .180 bullets	50
	AC	CESSORIES	
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070125"	100
A14GB	A14GBP	Sealing grommet, .125250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11SSB	A11SSBP	Stainless steel grommet cover	100
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100




**GloLight** 

MCL110AB

C Rated

MCL110RKB



**ONIC**S

81

FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.08A
WT/DIMS	.022 lbs. / .073" x .073" x 0.938"
WARRANTY	Lifetime LED Warranty



www.optronicsinc.com

#### MCL111 SERIES GloLight® Uni-Lite™ 3/4" Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY



QTY

- Sealed, waterproof design
- PC rated two diode models
- Hard wired, includes separate ground wire

POLYPACK P/N

- Available with optional plugs
- Choose from light only or kit with A11GB grommet
- Dual function models MCL121AK9PVG/RK9PVG provide a supplemental stop/turn function


DESCRIPTION

C	MCLIII	RKB

**GloLight** 

MCL111AKB

**BULK P/N** 



YELLOW - PC RATED - 2 DIODES			
MCL111AB	MCL111ABP	Light only	50
MCL111AKB	MCL111AKBP	Light with A11GB grommet	50
MCL111AKPG	MCL111AKPGP	Kit with .180 male bullets, A11GB	50
MCL121AK9PVG	MCL121AK9PVGP	Supplemental turn - kit with closed grommet, .180 male bullets	20
	RED - PC RA	TED - 2 DIODES	
MCL111RB	MCL111RBP	Light only	50
MCL111RKB	MCL111RKBP	Light with A11GB grommet	50
MCL111RKFPG	MCL111RKFPGP	Kit with .156 female bullets, A11GB	50
MCL111RKPG	MCL111RKPGP	Kit with .180 male bullets, A11GB	50
MCL121RK9PVG	MCL121RK9PVGP	Supplemental turn - kit with closed grommet, .180 male bullets	20
	ACCE	SSORIES	
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070125"	100
A14GB	A14GBP	Sealing grommet, .125250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11SSB	A11SSBP	Stainless steel grommet cover	100
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100



FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.04A
WT/DIMS	.022 lbs. / .75" x .75" x 0.875"
WARRANTY	Lifetime LED Warranty



0

#### **MCL112 SERIES** GloLight<sup>®</sup> Uni-Lite<sup>™</sup> 3/4" Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sealed, waterproof design
- P2 rated single diode models •
- Hard wired, includes separate ground wire •
- Choose from light only or kit with A11GB grommet •


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW - P	2 RATED - 1 DIODE	
MCL112AB	MCL112ABP	Light only	50
MCL112AKB	MCL112AKBP	Light with A11GB grommet	50
	RED - P2 F	RATED - 1 DIODE	
MCL112RB	MCL112RBP	Light only	50
MCL112RKB	MCL112RKBP	Light with A11GB grommet	50
	ACC	ESSORIES	
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070125"	100
A14GB	A14GBP	Sealing grommet, .125250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11SSB	A11SSBP	Stainless steel grommet cover	100
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100

A	Ø 3/4"
F	7/8"

**GloLight** 

MCL112AKB

MCL112RKB



**ptronics**.

G



**FMVSS** 

MATERIALS

VOLT/AMP

WARRANTY

WT/DIMS

P2

Polycarbonate lens and housing

.022 lbs. / .75" x .75" x 0.875"

Lifetime LED Warranty

12.8VDC - .047A



PC Rated



MCL10RKB



MCL10RB

MCL10AKB


.

•

#### **MCL10 SERIES** Uni-Lite<sup>™</sup> 3/4" LED Non-Directional Marker/Clearance Lights

- Sonically sealed, waterproof •
  - PC rated when mounted in any direction - 360 degrees!
  - Hard wired, includes separate ground wire
  - Choose from light only or kit with A11GB grommet

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLO	W - 1 DIODE	
MCL10AB	MCL10ABP	Light only	50
MCL10AKB	MCL10AKBP	Light with A11GB grommet	50
MCL10CAK14B	MCL10CAK14BP	Clear lens light with A11GB grommet	50
	RED	- 1 DIODE	
MCL10RB	MCL10RBP	Light only	50
MCL10RKB	MCL10RKBP	Light with A11GB grommet	50
MCL10CRK14B	MCL10CRK14BP	Clear lens light with A11GB grommet	50
	ACCI	ESSORIES	
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet for material thickness .070125"	100
A14GB	A14GBP	Sealing grommet for material thickness .125250"	100
A11PB	A11PBP	Snap-in mounting flange	100
A11SSB	A11SSBP	Stainless steel trim ring	100
A11AXB	A11AXBP	Yellow oval reflector, self adhesive	100
A11RXB	A11RXBP	Red oval reflector, self adhesive	100



HOLE CUT-OUT: .75"

FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC041A
WT/DIMS	.022 lbs. / .073" x .073" x .938"
WARRANTY	Lifetime LED Warranty

G

#### MCL11 SERIES Uni-Lite<sup>™</sup> 3/4" Sealed LED Marker/Clearance Lights **pcRated**

• Sealed, waterproof design

Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW -	PC RATED - 2 DIODES	
MCL11AB	MCL11ABP	Light only	50
MCL11APG	MCL11APGP	Light with .180 male bullets	50
MCL11CAB	MCL11CABP	Light only, clear lens	50
MCL11AKB	MCL11AKBP	Kit with A11GB grommet	50
MCL11CAKB	MCL11CAKBP	Kit with A11GB, clear lens	50
MCL11CAKPG	-	Kit with A11GB, clear lens, .180 male bullets	50
MCL11CAKBF	-	Kit with A11GB, clear lens, .156 female barrels	50
MCL11AHPG	-	Kit with .180 male bullets, A11GB	50
MCL11AKAB	MCL11AKABP	Kit with .156 female barrels, A11GB	50
MCL11AKBF	MCL11AKBFP	Kit with .156 female barrels, A11GB	50
MCL11AK12B	-	Kit with 12" leads, A11GB	50
MCL11AK12PG	-	Kit with 12" leads, A11GB, .156 male bullets	50
MCL11AKPVG	-	Kit with sealed grommet, .180 male bullets	50
-	MCL11AKBSSP	Kit with 12" leads, A11GB, A11SSB	50
MCL11A24KB	-	Kit with A11GB grommet, 24V	50
MCL11AKPV4G		Kit with sealed grommet, .180 male bullets, 24V	50
	RED - P	C RATED - 2 DIODES	
MCL11RB	MCL11RBP	Light only	50
MCL11RPG	MCL11RPGP	Light with .180 male bullets	50
MCL11CRB	MCL11CRBP	Light only, clear lens	50
MCL11RKB	MCL11RKBP	Kit with A11GB grommet	50
MCL11CRKB	MCL11CRKBP	Kit with A11GB, clear lens	50
MCL11CRKPG	-	Kit with A11GB, clear lens, .180 male bullets	50
MCL11CRKBF	-	Kit with A11GB, clear lens, .156 female barrels	50
MCL11RHPG	-	Kit with .180 male bullets, A11GB	50
MCL11RKAB	-	Kit with .156 female connectors, A11GB	50
MCL11RKBF	MCL11RKBFP	Kit with .156 female barrels, A11GB	50
MCL11RK12B	-	Kit with 12" leads, A11GB	50
MCL11RK12PG	-	Kit with 12" leads, A11GB, .156 male bullets	50
MCL11RKPVG	-	Kit with sealed grommet, .180 male bullets	50
-	MCL11RKBSSP	Kit with 12" leads, A11GB, A11SSB	50
MCL11R24KB	-	Kit with A11GB grommet, 24V	50
MCL11RKPV4G	-	Kit with sealed grommet, .180 male bullets, 24V	50

See Accessories section at back of catalog or listing on previous pages for additional mounting options

supplemental turn function


Kit with sealed grommet, male amp plug,







**MCL11RKB** 



HOLE CUT-OUT: 0.75"

FMVSS PC

MATERIALS Polycarbonate lens and housing


VOLT/AMP 12.8VDC - 0.03A

10

WT/DIMS .022 lbs. / .074" x .074" x 0.90"

**Ironic** 

WARRANTY Lifetime LED Warranty



MCL21RKPV4G -



#### MCL12 SERIES Uni-Lite<sup>™</sup> 3/4" Sealed LED Marker/Clearance Lights - P2

- Sealed, waterproof, P2 rated single diode models
- Hard wired, includes separate ground wire
- Three-piece identification light harnesses available; optional supplemental turn function
- MCL922RB is three-piece identification light bar

#### MCL12RKB



MCL12RK3B

MCL12AKB

MCL	922RB
	Ø 1.097 Ø 0.74
HOLE CUT-	OUT: 0.75''

FMVSS P2 MATERIALS Polycarbonate lens and housing VOLT/AMP 12.8VDC - 0.47A

WT/DIMS

.022 lbs. / .074" x .074" x 0.90"

WARRANTY Lifetime LED Warranty

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW -	P2 RATED - 1 DIODE	
MCL12AB	MCL12ABP	Light only	50
MCL12AKB	MCL12AKBP	Light kit with A11GB	50
MCL12AKPG	-	Light kit with .180 male bullets, A11GB	50
MCL12AK156PG	-	Light kit with .156 male bullets, A11GB	50
	RED - P2	RATED - 1 DIODE	
MCL12RB	MCL12RBP	Light only	50
MCL12RKB	MCL12RKBP	Light kit with A11GB	50
MCL12RKPG	-	Light kit with .180 male bullets, A11GB	50
MCL12RK156PG	-	Light kit with .156 male bullets, A11GB	50
RED IDEN1	TIFICATION LIC	GHT KIT WITH MOLDED HARNES	SS
MCL12RK3B	MCL12RK3BP	(3) red MCL12 lights	20
MCL12RK3RMB	-	(3) red MCL12 lights, weathertight plug	20
MCL22RK3B	-	(3) red MCL12 lights, supplemental turn function	20
MCL22RK4B	-	(3) red MCL12 lights, supplemental turn function, amp connector	20
	RED IDENTI	FICATION LIGHT BAR	
MCL922RB	MCL922RBP	(3) red MCL12 lights, molded bar, black	10
	AC	CESSORIES	
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070125"	100
A14GB	A14GBP	Sealing grommet, .125250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11SSB	A11SSBP	Stainless steel grommet cover	100
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100
		RETAIL	
MCL12AK	Retail Ready	Yellow light kit, card/slipover blister	12
MCL12RK		Red light kit, card/slipover blister	12

SEALED LED MARKER/ CLEARANCE LIGHTS

#### MCL12AR SERIES Uni-Lite<sup>™</sup> 3/4" Sealed LED Fender Lights

- Sealed, waterproof, P2 rated single diode lights pre-installed in durable ABS, surface mount bracket
- Hard wired, includes separate ground wire
- Available with clear or tinted lenses




MCL12ARRB MCL12ARLB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLOW /	RED FENDER LIGHTS	
MCL12ARLB	MCL12ARLBP	Driver side assembly, 2-wire	50/20
MCL12ARRB	MCL12ARRBP	Passenger side assembly, 2-wire	50/20
MCL12CA2RLB	-	Driver side assembly, clear lens, self grounding	50
MCL12CA2RRB	-	Passenger side assembly, clear lens, self grounding	50
	AC	CESSORIES	
A11GB	A11GBP	Grommet	100

2
olycarbonate lens and housing
2.8VDC - 0.047A
20 lbs. / 4.75" x 1.625" x 1.25"
ifetime LED Warranty





**ptronics** 

•

87





MCL21AB

MCL23AB


MCL21RB

#### MCL21/23 SERIES 2" & 2.5" Sealed LED Beehive Style Marker/Clearance Lights

- Sonically sealed, waterproof
- Clearance, side marker, or rear tracking light applications
- Accepts standard two-pin PL-10 plug


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YE	ELLOW - 8 DIODES	
MCL21AB	MCL21ABP	2" light	20
MCL23AB	MCL23ABP	2.5" light	20
		RED - 8 DIODES	
MCL21RB	MCL21RBP	2" light	20
MCL23RB	MCL23RBP	2.5" light	20
		ACCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
A55GB	A55GBP	2.5" Flush mount grommet (open back)	50
A56GB	A56GBP	2.5" Recess mount grommet (closed back)	100
A57GB	A57GBP	2.5" Recess mount grommet (open back)	50
A55GK	A55GKP	2.5" Kit: A55GB and A46PB	100
A57GK	A57GKP	2.5" Kit: A57GB and A46PB	100
A57CB	A57CBP	2.5" Chrome trim ring	20
BK5557GB	BK5557GBP	2"/2.5" Cam-on mounting bracket	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	MCL21: 12.8VDC - 0.061A
	MCL23: 12.8VDC - 0.051A
WT/DIMS	MCL21: .110 lbs. / 2" x 2" x 1.75"
	MCL23: .176 lbs. / 2.5" x 2.5" x 2.313"
WARRANTY	Lifetime LED Warranty



MCL23RB

MCL21 SERIES HOLE CUT-OUT: 2.313"



MCL23 SERIES HOLE CUT-OUT: 2.75"

88

#### MCL155 SERIES GloLight® 2" Round Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Recess grommet and flange mount models available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLO	W - 6 DIODES	
MCL155AB	MCL155ABP	Grommet mount	20
MCL155AFB	MCL155AFBP	Flange mount	20
	RED	- 6 DIODES	
MCL155RB	MCL155RBP	Grommet mount	20
MCL155RFB	MCL155RFBP	Flange mount	20
	ACC	ESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.06A
WT/DIMS	Grommet Mount: .066 lbs. / 2" x 2" x 1"
	Flange Mount: .078 lbs. / 2.938" x 2.938" x .938"
WARRANTY	Lifetime LED Warranty



**GloLight** 











MCL155RFB



MCL155AB/RB HOLE CUT-OUT: 2.313"




HOLE CUT-OUT: 2.313"



	MCL55 SERIES 2" Round Sealed LED Marker/Clearance Lights					
	• /		tanda	rd two-pi	proof in PL-10 plug 24V models	
	BULI	K P/N	POLYP	ACK P/N	DESCRIPTION	QTY
MCL55AB				YELLO	N - 3 DIODES	
	MCL	55AB	MCL55	ABP	Grommet mount, 12V	20
MCL55RB	MCL	55ACB	MCL55	ACBP	Clear lens grommet mount, 12V	20
	MCL	55A1224B	MCL55	A1224BP	Grommet mount, 12-24V	20
Total State	MCL	55AKB	MCL55	AKBP	Kit with grommet and plug, 12V	20
MCL55ACB				RED ·	- 3 DIODES	
MCL55RCB UCL55CB	MCL	55RB	MCL55	RBP	Grommet mount, 12V	20
UCESSED	MCL	55RCB	MCL55	RCBP	Clear lens grommet mount, 12V	20
	MCL	55R1224B	MCL55	R1224BP	Grommet mount, 12-24V	20
		55RKB	MCL55	RKBP	Kit with grommet and plug, 12V	20
		55FRB	MCL55	FRBP	Flange mount, 12V	50
		UTILITY LIGHT - 3 DIODES				
		55CB	UCL55	CBP	White LED, 12V	20
		ACCESSORIES				
		РВ	A46PB	Р	Straight PL-10 plug, 6" lead	100
HOLE CUT-OUT: 2.313"	A86F	РΒ	A86PB	Р	Straight PL-10 plug, 18" lead	100
	A540	ЭB	A54GE	P	2" Flush mount grommet	100
	A540	ЭK	A54Gk	P	2" Kit: A54GB and A46PB	100
	A550	СВ	A55CE	P	2" Chrome trim ring	20
	BK5	557GB	BK555	7GBP	Cam-on mounting bracket	50
				F	RETAIL	
		55AK	Yellow	kit with A54	GB & A46PB, clam	12
		55RK	Red kit	with A54G	B & A46PB, clam	12
		FMVSS		P2		
		MATERIAL	LS	Polycarbo	nate lens and housing	
MCL55FRB		VOLT/AMF	כ	12.8VDC -	0.06A	
		WT/DIMS		MCL55:	.066 lbs. / 2" x 2" x 1"	
				MCL55FR	B: .078 lbs. / 2.875" x 2.875" x 1"	

WARRANTY



HOLE CUT-OUT: 2.313"

**Optronics** 


Lifetime LED Warranty

90

#### **MCL505 SERIES** 2" Round Sealed LED ABS Lights


- Sonically sealed, waterproof ٠
- Accept standard two-pin PL-10 plugs •
- Available in grommet and flange mount models •
- MCL505GABSB includes A54GB grommet .

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		
	YELLOW	- 3 DIODES			
MCL505ABSB	MCL505ABSBP	Flange mount	50		
MCL505GABSB	MCL505GABSBP	Grommet mount kit, with A54GB grommet	20		
	ACCESSORIES				
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100		
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100		
A54GB	A54GBP	Standard flush mount grommet	100		
A54GK	A54GKP	Kit: A54GB and A46PB	100		
A55CB	A55CBP	Chrome trim ring	20		
BK5557GB	BK5557GBP	Cam-on mounting bracket	50		










HOLE CUT-OUT: 2.313"




MCL505GABSB



HOLE CUT-OUT: 2.313"

**tronics** 

91




FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC047A
WT/DIMS	MCL505ABSB: .078 lbs. / 2.875" x 2.875" x 1"
	MCL505GABSB: .066 lbs. / 2" x 2" x 1"
WARRANTY	Lifetime LED Warranty

www.optronicsinc.com

#### MCL56 SERIES FLEET Count<sup>™</sup> 2" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	YEL	LOW - 1 DIODE		
MCL56AB	MCL56ABP	Light only	20	
MCL5AFB	MCL56AFBP	Flange mount	20	
	R	ED - 1 DIODE		
MCL56RB	MCL56RBP	Light only	20	
MCL56RFB	MCL56RFBP	Flange mount	20	
	A	CCESSORIES		
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100	
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100	
A54GB	A54GBP	2" Flush mount grommet	100	
A54GK	A54GKP	2" Kit: A54GB and A46PB	100	
A55CB	A55CBP	2" Chrome trim ring	20	
BK5557GB	BK5557GBP	Cam-on mounting bracket	50	
RETAIL				
MCL56AK	Retail Ready	Yellow kit with A54GB & A46PB, clam	n 12	
MCL56AS	Reidin Reddy	Yellow light only, clam	12	
MCL56RK		Red kit with A54GB & A46PB, clam	12	
MCL56RS		Red light only, clam	12	
FMVSS	P2			
MATERIALS		te lens and housing		
VOLT/AMP	12.8VDC - 0	°		
WT/DIMS	Grommet mount: .066 lbs. / 2" x 2" x 1"			
	0.0.00	nt: .071 lbs. / 2.938" x 2.938" x .938"		
WARRANTY	Lifetime LED			
		wanany		




FLEET COUNT

MCL56AFB

MCL56AB

MCL56RB

HOLE CUT-OUT: 2.313"



HOLE CUT-OUT: 2.313"

92 **Optronics** 

#### MCL52 REFLEX SERIES 2" Round Sealed LED Marker/Clearance Lights with Reflex Lens and Flange

- Recess flange mount
- Sonically sealed, waterproof
- · Hard wired, includes separate ground wire
- Built-in reflex eliminates the need for a separate reflector





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLO	W - 7 DIODES	
MCL52AHXE	B MCL52AHXBP	Reflex flange	50
	RED	- 7 DIODES	
MCL52RHX	B MCL52RHXBP	Reflex flange	50


FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.063A
WT/DIMS	.088 lbs. / 3.063" x 3.063" x .813"
WARRANTY	Lifetime LED Warranty



MCL52AHXB







HOLE CUT-OUT: 2.313"






# MCL50AB

#### MCL50 SERIES Miro-Flex<sup>™</sup> 2" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available

MCL50RB	00

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		
	YEL	LOW - 9 DIODES			
MCL50AB	MCL50ABP	Light only	20		
	R	ED - 9 DIODES			
MCL50RB	MCL50RBP	Light only	20		
	ACCESSORIES				
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100		
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100		
A54GB	A54GBP	2" Flush mount grommet	100		
A54GK	A54GKP	2" Kit: A54GB and A46PB	100		
A55CB	A55CBP	2" Chrome trim ring	20		
BK5557GB	BK5557GBP	Cam-on mounting bracket	50		



HOLE CUT-OUT: 2.313"

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.088 lbs. / 2" x 2" x 1.188"
WARRANTY	Lifetime LED Warranty


94 **Optronics** 

#### MCL52/54 SERIES 2" Round Sealed LED Marker/Clearance Lights PCRated

- Sonically sealed, waterproof
- Available with standard PL-10 or optional weathertight connection
- PC rated: functions as both clearance and side marker light when properly mounted on a 45 degree angle
- Available in flange mount and grommet mount models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	YELI	LOW - 5 DIODES		
MCL52AB	MCL52ABP	Flange mount, PL-10 connection	20	
MCL52AMB	MCL52AMBP	Flange mount, weathertight connection; pigtail included	20	
MCL54AB	MCL54ABP	Grommet mount, PL-10 connection	20	
	RE	ED - 5 DIODES		
MCL52RB	MCL52RBP	Flange mount, PL-10 connection	20	
MCL52RMB	MCL52RMBP	Flange mount, weathertight connection; pigtail included	20	
MCL54RB	MCL54RBP	Grommet mount, PL-10 connection	20	
ACCESSORIES				
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100	
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100	
AL42PB	AL42PBP	Weathertight pigtail	100	
A54GB	A54GBP	2" Flush mount grommet	100	
A54GK	A54GKP	2" Kit: A54GB and A46PB	100	
A55CB	A55CBP	2" Chrome trim ring	20	
BK5557GB	BK5557GBP	Cam-on mounting bracket	50	
A52GB	-	Gasket for flange mount, black	100	

FMVSS	P2 PC	
MATERIALS	Polycarbonate len	s and housing
VOLT/AMP	12.8VDC - 0.063A	
WT/DIMS	Flange mount:	.088 lbs. / 2.938" x 2.938" x 0.938"
	Grommet mount:	.066 lbs. / 2.063" x 2.063" x 0.875"
WARRANTY	Lifetime LED Warr	ranty



MCL54 HOLE CUT-OUT: 2.313"




MCL54RB







detail of weathertight connection on MCL52AMB/RMB; pigtail included



HOLE CUT-OUT: 2.313"

 $\odot$ 



# GloLight MCL

#### MCL157 SERIES GloLight® 2.5" Round Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 9 DIODES	
MCL157AB	MCL157ABP	Light only	20
	RI	ED - 9 DIODES	
MCL157RB	MCL157RBP	Light only	20
	A	CCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50



 $\odot$ 

MCL157AB

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.099A
WT/DIMS	.132 lbs. / 2.5" x 2.5" x 1.125"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.75"

(optronics

#### MCL57 SERIES 2.5" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Available in 12V and 24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 3 DIODES	
MCL57AB	MCL57ABP	Light only, 12V	20
MCL57A24B	MCL57A24BP	Light only, 24V	20
MCL57ACB	MCL57ACBP	Clear lens light only, 12V	20
MCL57AKB	MCL57AKBP	Kit with grommet and plug	20
	REI	D - 3 DIODES	
MCL57RB	MCL57RBP	Light only, 12V	20
MCL57R1224B	MCL57R1224BP	Light only, 12-24V	20
MCL57R24B	MCL57R24BP	Light only, 24V	20
MCL57RCB	MCL57RCBP	Clear lens light only, 12V	20
MCL57RKB	MCL57RKBP	Kit with grommet and plug	20
	AC	CESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
		RETAIL	
MCL57AK	Retail Ready	Yellow kit with A55GB & A46PB, clam	12
MCL57RK		Red kit with A55GB & A46PB, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.096A
WT/DIMS	.132 lbs. / 2.5" x 2.5" x 1"
WARRANTY	Lifetime LED Warranty









MCL57RB



MCL57ACB/RCB





p**tro**nics.)

G

SEALED LED MARKER CLEARANCE LIGHT

www.optronicsinc.com

97

FLEET COUNT	FLEET C		I <mark>ES</mark> 5" Round Sealed LE nce Lights	D
MCL527AB	Accepts		erproof o-pin PL-10 plug tions available	
	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LOP .			LOW - 2 DIODES	1
	MCL527AB	MCL527ABP	Light only	20
	MCL527AFB	MCL527AFBP	Flange mount	20
		RI	ED - 2 DIODES	ŝ
	MCL527RB	MCL527RBP	Light only	20
	MCL527RFB	MCL527RFBP	Flange mount	20
MCL527AFB		Α	CCESSORIES	
	A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
	A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
	A55GB	A55GBP	Flush mount grommet (open back)	50
	A56GB	A56GBP	Recess mount grommet (closed back)	100
HILL BE THE BEACH	A57GB	A57GBP	Recess mount grommet (open back)	50
MCL527RB	A55GK	A55GKP	Kit: A55GB and A46PB	100
	A57GK	A57GKP	Kit: A57GB and A46PB	100
100	A57CB	A57CBP	Chrome trim ring	20
	BK5557GB	BK5557GBP	Cam-on mounting bracket	50
			RETAIL	
	MCL527AK		Yellow kit with A57GB & A46PB, clam	12
	MCL527AS	Retail Ready	Yellow light only, clam	12
	MCL527RK		Red kit with A57GB & A46PB, clam	12
	MCL527RS		Red light only, clam	12
MCL527RFB				
	FMVSS	P2		
	MATERIALS	Polycarbona	ate lens and housing	
	VOLT/AMP	12.8VDC - (	0	
	WT/DIMS	Grommet M	ount: .088 lbs. / 2.5" x 2.5" x 1.063"	
		Flange Mou	nt: .088lbs. / 3.438" x 3.438" x .938"	
	WARRANTY	Lifetime LE	D Warranty	
3 7/16" 15/16" 15/16" 15/8" 15/8" 10 10 10 10 10 10 10 10 10 10	diame et a diame			

SEALED LED MARKER/ CLEARANCE LIGHTS

98 **Optronics** 

#### **MCL51 SERIES** Miro-Flex<sup>™</sup> 2.5" Round Sealed LED Marker/Clearance Lights


MCL51AB

- Sonically sealed, waterproof •
- Accepts standard two-pin PL-10 plug •
- Multiple mounting options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 3 DIODES	
MCL51AB	MCL51ABP	Light only	20
	RI	ED - 3 DIODES	
MCL51RB	MCL51RBP	Light only	20
	A	CCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.033A
WT/DIMS	.088 lbs. / 2.5" x 2.5" x 1.188"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.75"

**Optronics** 

99

www.optronicsinc.com

**MCL58 SERIES** 2.5" Round Sealed LED Marker/Clearance Lights



- Sonically sealed, waterproof .
- Available with standard PL-10 or optional • weathertight connection
- Multiple mounting options available •
  - PC rated: functions as both clearance and side marker light when properly mounted on a 45 degree angle

( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MCL58ACB		YELI	OW - 7 DIODES	
	MCL58AB	MCL58ABP	Light only	20
	MCL58ACB	MCL58ACBP	Clear lens, yellow diodes, light only	20
	MCL58AMFB	MCL58AMFBP	Flange mount, weathertight connection	50
		RE	D - 7 DIODES	
MCL58RB	MCL58RB	MCL58RBP	Light only	20
MCLOOKD	MCL58RMFB	MCL58RMFBP	Flange mount, weathertight connection	50
		A	CCESSORIES	
	A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
	A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
	AL42PB	AL42PBP	Weathertight pigtail	100
	A55GB	A55GBP	Flush mount grommet (open back)	50
	A56GB	A56GBP	Recess mount grommet (closed back)	100
	A57GB	A57GBP	Recess mount grommet (open back)	50
	A55GK	A55GKP	Kit: A55GB and A46PB	100
	A57GK	A57GKP	Kit: A57GB and A46PB	100
MCL58AMFB	A57CB	A57CBP	Chrome trim ring	20
	BK5557GB	BK5557GBP	Cam-on mounting bracket	50
	FMVSS	P2 PC		
	MATERIALS		te lens and housing	
	VOLT/AMP	12.8VDC - 0	· ·	
	WT/DIMS		ount: .132 lbs. / 2.5" x 2.5" x 0.938"	
			nt: .112lbs. / 3.42" x 3.42" x 1.30"	
	WARRANTY	Lifetime LED		
MCL58RMFB	$\sim$		00000	
li li		-	3.42" 2.63" .44" .8	8"
60012				0
				1
		~		
		6		2.69"
		F ()		
detail of weathertight connection;	, Dual,	-		•
	2 1/2"		.19"	
HC	DLE CUT-OUT: 2.7	75''	HOLE CUT-OUT: 2.75"	

Gotr

MCL58AB

NIC

100 Cotronics

# **MCL59 SERIES**

#### 2.5" Round Sealed LED Marker/ Clearance Lights with Reflex

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available
- Built-in reflex eliminates the need for a separate reflector


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 8 DIODES	
MCL59AB	MCL59ABP	Light only	20
	RI	ED - 8 DIODES	
MCL59RB	MCL59RBP	Light only	20
	Α	CCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.088 lbs. / 2.5" x 2.5" x 1.063"
WARRANTY	Lifetime LED Warranty









HOLE CUT-OUT: 2.75"







MCL190AB




MCL190RB

#### MCL190 SERIES GloLight® Mini Thinline Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Hard wired with female PL-10 plug on 5" leads
- Includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YI	ELLOW - 8 DIODES	
MCL190AB	MCL190ABP	Kit with chrome base, female PL-10 plug	50
		RED - 8 DIODES	
MCL190RB	MCL190RBP	Kit with chrome base, female PL-10 plug	50



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.16A
WT/DIMS	.044 lbs. / 2.625" x 1.25" x .875"
WARRANTY	Lifetime LED Warranty



#### AL91 SERIES Mini Thinline Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Standard models accept standard 1- or 2-wire plugs
- Hard wired design available in 1- and 2-wire models
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces
- PC rated light functions as both clearance and side marker light when properly mounted on a 45 degree angle

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YI	ELLOW - 3 DIODES	
AL91AB	AL91ABP	PC rated	50
AL91CAB	AL91CABP	PC rated, clear lens	50
MCL91AB	MCL91ABP	Kit: AL91AB, A91CB & A91LW	50
AL82AB	AL82ABP	PC rated, hard wired, 2-wire	50
MCL96AB	MCL96ABP	P2 rated kit, hard wired, 1-wire, A91BB base	50
		RED - 3 DIODES	
AL91RB	AL91RBP	PC rated	50
MCL91RB	MCL91RBP	Kit: AL91RB, A91CB & A91LW	50
AL82RB	AL82RBP	PC rated, hard wired, 2-wire	50
MCL96RB	MCL96RBP	P2 rated kit, hard wired, 1-wire, A91BB base	50
		ACCESSORIES	
A46PB	A46PBP	2-wire PL-10 plug, 6" lead	100
A86PB	A86PBP	2-wire PL-10 plug, 18" lead	100
A91LW	A91LWP	1-wire plug, 12" lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A910BP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
		RETAIL	
MCL91AK		Yellow P2 kit with A91CB & A91LW, clam	12
MCL90AS	Retail Ready	Yellow P2 light only, clam	12
MCL91RK		Red P2 kit with A91CB & A91LW, clam	12
MCL90RS		Red P2 light only, clam	12




.....

AL91AB



FMVSS MATERIALS	PC (unless noted) Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.088 lbs. 2.5" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty



**otronics** 

103








#### FLEET Count<sup>™</sup> Mini Thinline Sealed LED Marker/Clearance Light

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- · Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	Y	ELLOW - 1 DIODE	
AL90AB	AL90ABP	Light only	50
		RED - 1 DIODE	
AL90RB	AL90RBP	Light only	50
AL90RCB	AL90RCBP	Clear lens, red diode, light only	50
		ACCESSORIES	
A46PB	A46PBP	2-wire PL-10 plug, 6" lead	100
A86PB	A86PBP	2-wire PL-10 plug, 18" lead	100
A91LW	A91LWP	1-wire plug, 12" lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
		RETAIL	
AL90AK		Yellow kit with A91BB & A91LW, clam	12
AL90AS	Retail Ready	Yellow light only, clam	12
AL90RK	<b>V</b>	Red kit with A91BB & A91LW, clam	12
AL90RS		Red light only, clam	12



104 Gotronics

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.023A
WT/DIMS	.044 lbs. / 2.5" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty



AL90RB

#### MCL165 SERIES GloLight® Thinline Sealed LED Marker/Clearance Lights

#### PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 10 DIODES	
MCL165AB	MCL165ABP	Light only	20
	RE	D - 10 DIODES	
MCL165RB	MCL165RBP	Light only	20
	A	CCESSORIES	
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
		n mounting and wiring accessories, es section at back of catalog.	



MCL165AB


**Glo**Light

-

MCL165RB

optronics)

P2
Polycarbonate lens and housing
12.8VDC - 0.07A
.066 lbs. / 3.875" x 1.25" x 1"
Lifetime LED Warranty





105





MCL65AB

#### **MCL65 SERIES Thinline Sealed** LED Marker/Clearance Lights

Sonically sealed, waterproof •

**BULK P/N** 

- Accept standard 1- or 2-wire plugs •
- Single wire design grounds through mounting hardware .
- Two-wire design includes both lead and ground wire for • mounting to all surfaces

POLYPACK P/N DESCRIPTION

QTY




MCL65CRB



		YELLOW	
MCL65AB	MCL65ABP	12V, 3 diodes	20
MCL65A24B	MCL65A24BP	24V, 3 diodes	20
MCL65CAB	MCL65CABP	12V, 3 diodes, clear lens	20
MCL67AB	MCL67ABP	12V, 3 diodes, kit with A65PB	20
MCL75AB	MCL75ABP	12V, 4 diodes	20
MCL77AB	MCL77ABP	12V, 4 diodes, kit with A65PB	20
		RED	
MCL65RB	MCL65RBP	12V, 3 diodes	20
MCL65R24B	MCL65R24BP	24V, 3 diodes	20
MCL65CRB	MCL65CRBP	12V, 3 diodes, clear lens	20
MCL67RB	MCL67RBP	12V, 3 diodes, kit with A65PB	20
MCL75RB	MCL75RBP	12V, 4 diodes	20
MCL77RB	MCL77RBP	12V, 4 diodes, kit with A65PB	20
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
		mounting and wiring accessories,	

see Accessories section at back of catalog




FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.048A
WT/DIMS	.066 lbs. / 3.938" x 1.25" x 1.25"
WARRANTY	Lifetime LED Warranty




#### MCL61 SERIES FLEET Count<sup>™</sup> Thinline Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELI	LOW - 2 DIODES	
MCL61AB	MCL61ABP	Light only	20
	RE	ED - 2 DIODES	
MCL61RB	MCL61RBP	Light only	20
	A	CCESSORIES	
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
		n mounting and wiring accessories, es section at back of catalog.	
		RETAIL	
MCL61AK		Yellow kit with A65PB, clam	12
MCL61AS	Retail Ready	Yellow light only, clam	12
MCL61RK		Red kit with A65PB, clam	12
MCL61RS		Red light only, clam	12







optronics)

107

# FLEET COUNT





MCL61RB

www.optronicsinc.com





#### MCL63 SERIES Miro-Flex<sup>™</sup> Thinline Sealed LED Marker/Clearance Lights


- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- · Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

MCL63AB




MCL63CRB









108 Cotronic

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
YELLOW - 4 DIODES				
MCL63AB	MCL63ABP	Light only	20	
MCL63CAB	MCL63CABP	Light only, clear lens	20	
	RE	ED - 4 DIODES		
MCL63RB	MCL63RBP	Light only	20	
MCL63CRB	MCL63CRBP	Light only, clear lens	20	
	Α	CCESSORIES		
A65B	A65BP	Black bracket	50	
A65P	A65PP	Single wire plug, .156 male bullet	50	
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50	
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50	
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50	
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50	
For more details on mounting and wiring accessories, see Accessories section at back of catalog.				

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.066 lbs. / 4" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty

#### MCL61/65 SERIES Thinline Sealed LED Fender Lights

- · Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
D	UAL RED/YEL	LOW - 10 DIODES	
MCL65ARB	MCL65ARBP	Light only	20
MCL65CARB	MCL65CARBP	Light only, clear lens	20
MCL67ARB	MCL67ARBP	Kit with A65PB bracket & plug	20
D	UAL RED/YEL	LOW - 2 DIODES	
MCL61ARB	MCL61ARBP	Light only	20
MCL61AR26BK	MCL61AR26BKP	Kit with A67BB black base & 26" power wire with .150 male bullet	20
	ACC	ESSORIES	
A67BB	A67BBP	Black fender bracket	50
A67GB	A67GBP	Gray fender bracket	50
A67CVB	A67CVBP	Curved fender bracket, gray	50
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
Fo		ounting and wiring accessories, section at back of catalog.	

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.048A
WT/DIMS	.066 lbs. / 3.875" x 1.25" x 0.875"
WARRANTY	Lifetime LED Warranty






MCL65ARB






MCL61ARB



light only



light with base

**tronics** 





#### MCL180 SERIES LED Fender Light Assembly


- Reversible one product can be used for either driver or passenger side of trailer
- Sonically sealed, waterproof
- P2 rated

WARRANTY

Hard wired, includes separate ground wire

Lifetime LED Warranty

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	FENDER L	IGHT - 2 DIODES	
MCL180ARB	MCL180ARBP	Amber/red, reversible	50
FMVSS	P2		
MATERIALS	Polycarbonate le	ens and housing	
VOLT/AMP	12.8VDC033A		
WT/DIMS	.05 lbs. / 8.50" x	1.688" x .813"	






#### MCL99 SERIES Mini Sealed LED Horizontal-Vertical Marker/Clearance Lights

- · Sealed, waterproof design
- Surface mount installation at either horizontal or vertical
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELLC	W - 1 DIODE	
MCL99AB	MCL99ABP	2-wire	20
MCL99A1B	MCL99A1BP	Single wire, self-grounding	20
MCL99AC1B	MCL99AC1BP	Clear lens, single wire, self-grounding	50
	RED	- 1 DIODE	
MCL99RB	MCL99RBP	2-wire	20
MCL99R1B	MCL99R1BP	Single wire, self grounding	20
MCL99RC1B	MCL99RC1BP	Clear lens, single wire, self-grounding	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC06A
WT/DIMS	.088 lbs. / 2.5" x 1.125" x 0.625"
WARRANTY	Lifetime LED Warranty











MCL99RB/R1B



MCL99AC1B



MCL99RC1B

**ptronics**)







MCL13A2B





MCL13CA2B

MCL13CR2B





MCL13R2B



MCL13CA3B









#### MCL13 SERIES Mini Sealed LED Marker/Clearance Lights


- Sonically sealed, waterproof
- Surface mount installation
- · Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces
- Available in red, yellow, and clear utility light

Y	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
)	
0	
0	
0	
2	
2	
2	
2	
-	
12.8VDC - 0.046A .088 lbs. / 2.5" x 1.063" x 0.688" (models with no base .625" H)	

#### **MCL14 SERIES** Mini Sealed LED Horizontal-Vertical Marker/Clearance Lights Rated

- Sonically sealed, waterproof •
- Surface mount installation at either horizontal or vertical •
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for • mounting to all surfaces
- Available in red, yellow, and clear lens

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 3 DIODES	
MCL14AB	MCL14ABP	2-wire	20
MCL14ABF	MCL14ABFP	2-wire, female plug	20
MCL14AGB	MCL14AGBP	1-wire, self grounding	20
MCL14AGPB	MCL14AGPBP	1-wire, .180 male bullet	20
MCL14CABF	MCL14CABFP	Clear lens, 2-wire, .156 female barrels	20
MCL14A12GB	MCL14A12GBP	1-wire, 12" lead	20
	RE	D - 3 DIODES	
MCL14RB	MCL14RBP	2-wire	20
MCL14RBF	MCL14RBFP	2-wire, female plug	20
MCL14RGB	MCL14RGBP	1-wire, self grounding	20
MCL14CRBF	MCL14CRBFP	Clear lens, 2-wire, .156 female barrels	20
MCL14RPG	MCL14RPGP	2-wire, 12" leads, .156 male bullets	20
ACCESSORIES			
A13C2B	A13C2BP	Chrome base/bezel	100
A13B2B	A13B2BP	Black base/bezel	100
A13G2B	A13G2BP	Gasket	200



	011
-13/4"	-
-	5/8"

A	3	A13C2B

P2 PC

12.8VDC - 0.06A

Lifetime LED Warranty

Polycarbonate lens and housing

.088 lbs. / 2.5" x 1.125" x 0.625"

**FMVSS** 

MATERIALS

**VOLT/AMP** 

WT/DIMS

WARRANTY



MCL14AB



MCL14 clear lens, unlit





QTY


20 20

20 20

100 100 50

	Surface	<b>5 SERIES</b> Mount LE /Clearanc		
MCL15APG	<ul><li>Surface</li><li>Hard with</li></ul>	y sealed, water mount installati red, includes bo .180 male bullet	on th lead and ground wire with	
	Chrome     BULK P/N	finish ABS trim	ring included with kits DESCRIPTION	
	YELLOW - 2 DIODES			
MCL15AKPG	MCL15APG	MCL15APGP	Light only, .180 male bullets	
	MCL15AKPG	MCL15AKPGP	Kit: MCL15APG, chrome trim ring	
		RED	- 2 DIODES	
	MCL15RPG	MCL15RPGP	Light only, .180 male bullets	
	MCL15RKPG	MCL15RKPGP	Kit: MCL15RPG, chrome trim ring	
		ACC	ESSORIES	
MCL15RPG	A15CB	A15CBP	Chrome base/bezel	
	A15BB	A15BBP	Black base/bezel	
	A15GB	A15GBP	Gasket	
MCL15RKPG	FMVSS	P2		
	MATERIALO	<b>D</b>	ADOL'S IS	

FMVSS	P2	
MATERIALS	Polycarbo	nate lens and housing, ABS trim ring
VOLT/AMP	12.8VDC -	0.047A
WT/DIMS	Light:	.088 lbs. / 2.625" x 1.375" x .563"
	Kit:	.092 lbs. / 3.938" x 1.344" x .688"
WARRANTY	Lifetime L	ED Warranty



MCL15AKPG/RKPG



114 Cotronics

800-364-5483 / 918-683-9514

Hard wired, includes separate ground wire

Sonically sealed, waterproof

Adhesive mount

•

•

•

#### MCL299 SERIES Sealed LED Marker/Clearance Light


C Rated



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 1 DIODE	
MCL299AB	MCL299ABP	Light only	50
	RE	D - 1 DIODE	
MCL299RB	MCL299RBP	Light only	50



FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Yellow: 12.8VDC - 0.12A
	Red: 12.8V - 0.065A
WT/DIMS	.03 lbs. / 1.50" x .625" x .75"
WARRANTY	Lifetime LED Warranty















MCL19AB



MCL19CAB/CRB



MCL19RB





#### MCL17/19 SERIES Miro-Flex<sup>™</sup> Surface Mount Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof •
- Two-wire design includes both lead and ground wire for • mounting to all surfaces
- Snap-on chrome trim ring included •
- Available in 3-LED 4" model and 4-LED 6" model

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL17AB	MCL17ABP	3-LED	20
MCL17APG	MCL17APGP	3-LED, female PL-10 plug	20
MCL17CAB	MCL17CABP	3-LED, clear lens	20
MCL19AB	MCL19ABP	4-LED	20
MCL19CAB	MCL19CABP	4-LED, clear lens	20
		RED	
MCL17RB	MCL17RBP	3-LED	20
MCL17RPG	MCL17RPGP	3-LED, female PL-10 plug	20
MCL17CRB	MCL17CRBP	3-LED, clear lens	20
MCL19RB	MCL19RBP	4-LED	20
MCL19CRB	MCL19CRBP	4-LED, clear lens	20
	A	CCESSORIES	
A17GB	A17GBP	Black gasket for 3-LED models	100

FMVSS	P2	
MATERIALS	Polycarbor	nate lens and housing
VOLT/AMP	MCL17:	12.8VDC - 0.047A
	MCL19:	12.8VDC - 0.051A
WT/DIMS	MCL17:	.088 lbs. / 4.188" x 1.375" x .75"
	MCL19:	.132 lbs. / 5.75" x 1.563" x .75"
WARRANTY	Lifetime LE	ED Warranty





MCL17





800-364-5483 / 918-683-9514

#### MCL31 SERIES Surface Mount LED Marker/ Clearance Lights with Reflex

- Snap-on, replaceable lens
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	MCL31RB
	YEL	LOW - 6 DIODES		
MCL31AB	MCL31ABP	Light only, white base	20	
	RE	ED - 6 DIODES		
MCL31RB	MCL31RBP	Light only, white base	20	
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	A P2 Acrylic lens, ABS 12.8VDC - 0.040 .132 lbs. / 4" x 2 Lifetime LED Wa	)A .063" x 1"		(


## MCL32 SERIES Surface Mount LED Marker/ Clearance Lights with Reflex

- Snap-on, replaceable lens
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 3 DIODES	
MCL32AB	MCL32ABP	Light only, white base	100
MCL32ABB	MCL32ABBP	Light only, black base	100
	RE	ED - 3 DIODES	
MCL32RB	MCL32RBP	Light only, white base	100
MCL32RBB	MCL32RBBP	Light only, black base	100
		RETAIL	
MCL32AS		Yellow light with white base	12
MCL32ABS	<b>Retail Ready</b>	Yellow light with black base	12
MCL32RS		Red light with white base	12
MCL32RBS		Red light with black base	12

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.132 lbs. / 4" x 2" x 1"
WARRANTY	Lifetime LED Warranty

MCL31AB











www.optronicsinc.com






#### MCL35A32G Surface Mount LED Marker/ Clearance Light with Reflex

- Surface mount black base, mounts on 3-5/16" centers
- · Lens with reflex eliminates need for separate reflector
- Self grounding; 32" power wire with .180 male bullet

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YEL	LOW - 6 DIODES	
MCL35A32G	MCL35A32GP	Light, 32" lead with .180 male bullet	50



FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.165A
WT/DIMS	.110 lbs. / 3.875" x 2.375" x 0.938"
WARRANTY	Lifetime LED Warranty



118 **Gpt** 

MCL36AB

#### MCL36 SERIES Stud Mount LED Marker/ Clearance Light with Reflex

- Stud mount black base; two-wire design
- · Lens with reflex eliminates need for separate reflector

	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
1999		YEL	LOW - 6 DIODES	
	MCL36AB	MCL36ABP	Hard wired	20
	MCL36APG	MCL36APGP	Hard wired, .180 male bullets	20
		RI	ED - 6 DIODES	
MCL36RB	MCL36RB	MCL36RBP	Hard wired	20
			RETAIL	
<b>→</b> 2 7/8* <b>→</b>	MCL36AS	Retail Ready	Yellow light with hardware, clam	12
	FMVSS	A P2		
2 1/8"	MATERIALS	Acrylic lens, ABS	6 housing	
15/16"	VOLT/AMP	12.8VDC - 0.054	A	
(	WT/DIMS	.110 lbs. / 2.875"	x 2.125" x .938"	
· 5/8"	WARRANTY	Lifetime LED Wa	irranty	

#### MCL40/44 SERIES Surface Mount LED Marker/ Clearance Lights with Reflex

- Select from 2-LED and 6-LED models in amber and red
- Snap-on, replaceable lens
- Surface mount white base, mounts on 3" centers
- Lens with reflex eliminates need for separate reflector
- Single wire and two-wire designs available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL40AB	MCL40ABP	2-LED, 2-wire, power and ground	20
MCL40AB1	MCL40AB1P	2-LED, 1-wire, self grounding	20
MCL40APB	MCL40APBP	2-LED, 2-wire .180 male bullets	20
MCL44AB	MCL44ABP	6-LED, 2-wire, power and ground	20
MCL44AB1	MCL44AB1P	6-LED, 1-wire, self grounding	20
		RED	
MCL40RB	MCL40RBP	2-LED, 2-wire, power and ground	20
MCL40RB1	MCL40RB1P	2-LED, 1-wire, self grounding	20
MCL44RB	MCL44RBP	6-LED, 2-wire, power and ground	20
MCL44RB1	MCL44RB1P	6-LED, 1-wire, self grounding	20
	A	CCESSORIES	
A44GTB	-	Mounting gasket, white	1000
		RETAIL	
MCL40AS		2-LED, 2-wire, yellow, clam	12
MCL40RS	RetailReady	2-LED, 2-wire, red, clam	12






MCL40/44AB



MCL40/44RB

FMVSS	P2 A
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 2-LED 0.040A; 6-LED .054A
WT/DIMS	.088 lbs. / 4" x 1.5" x 0.938"
WARRANTY	Lifetime LED Warranty











MCL45/46AB



MCL45/46RB





#### MCL45/46 SERIES LED Double Bullseye Style Marker/Clearance Lights



- Snap-on, replaceable lens
- Surface mount white base, mounts on 3" centers
  - Single wire and two-wire designs available


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELL	OW - 10 DIODES	
MCL45AB	MCL45ABP	1-wire, self grounding	20
MCL46AB	MCL46ABP	2-wire, power and ground	20
	RE	D - 10 DIODES	
MCL45RB	MCL45RBP	1-wire, self grounding	20
MCL46RB	MCL46RBP	2-wire, power and ground	20
ACCESSORIES			
AL46AB	AL46ABP	Yellow replacement lens	50
AL46RB	AL46RBP	Red replacement lens	50
FM (00			

FMVSS	P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.087A
WT/DIMS	.088 lbs. / 4.063" x 2.125" x 1.125"
WARRANTY	Lifetime LED Warranty





MCL49AB



120 0

#### MCL49AB Surface Mount Sealed LED Marker/Clearance Light



- Sonically sealed, waterproof
- Surface mount, mounts on 3" centers
- Includes both lead and gound wire

BULK P/N	POLYPACK P/N DESCRIPTION	QTY
	YELLOW - 14 DIODES	
MCL49AB	MCL49ABP Light only	20
FMVSS	P2 PC	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	12.8VDC - 0.87A	
WT/DIMS	.132 lbs. / 3.875" x 2" x 1"	
WARRANTY	Lifetime LED Warranty	

800-364-5483 / 918-683-9514

## MCL48 SERIES

LED Intermediate Side Marker Light with Supplemental Mid-Ship Turn

- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELI	OW - 16 DIODES	
MCL48AB	MCL48ABP	Light	20
MCL48CAB	MCL48CABP	Light, clear lens	20
MCL48AKB	MCL48AKBP	Kit: MCL48AB with A48CB bezel	20
	A	CCESSORIES	
A48CB	A48CBP	Chrome bezel	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - Side marker .074A; Turn signal .248A
WT/DIMS	.221 lbs. / 6" x 2.25" x 1.375"
WARRANTY	Lifetime LED Warranty





- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Includes both lead and ground wires


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELI	OW - 16 DIODES	
MCL73AB	MCL73ABP	Light	20
	RE	D - 16 DIODES	
MCL73RB	MCL73RBP	Light	20
	Α	CCESSORIES	
A48CB	A48CBP	Chrome bezel	50
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	P2 PC Polycarbonate I 12.8VDC248 .221 lbs. / 6" x 2 Lifetime LED W	2.25" x 1.375"	






MCL48AB









MCL73AB



**tro**nics

121

www.optronicsinc.com









MCL66CRB



			Dette The se
BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL66AB	MCL66ABP	6-LED, 12V	20
MCL66APG	MCL66APGP	6-LED, 12V, .180 male bullets	20
MCL66A24B	MCL66A24BP	6-LED, 12-24V	20
MCL66CAB	MCL66CABP	6-LED, 12V, clear lens	20
MCL166AB	MCL166ABP	2-LED, 12V with gasket	20
		RED	
MCL66RB	MCL66RBP	6-LED, 12V	20
MCL66RPG	MCL66RPGP	6-LED, 12V, .180 male bullets	20
MCL66R24B	MCL66R24BP	6-LED, 12-24V	20
MCL66CRB	MCL66CRBP	6-LED, 12V, clear lens	20
MCL166RB	MCL166RBP	66RBP 2-LED, 12V with gasket	
	Α	CCESSORIES	
A66GB	A66GBP	Gasket, black	100
BK66DB	BK66DBP	Heavy duty armored base, die cast metal	50
		RETAIL	
MCL66AS		Yellow 6-LED, 12V, clam	12
MCL66RS	Retail Ready	Red 6-LED, 12V, clam	12
	-		
FMVSS	P2		





FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.057A
WT/DIMS	.088 lbs. / 4" x .875" x 1.188"
WARRANTY	Lifetime LED Warranty



- Select from 6-LED and 2-LED models in amber and red
- Sonically sealed, waterproof

•

- Surface mount, mounts on 3" centers
- Includes both lead and gound wire
- MCL166 series lights include a gasket and wire outlet grommet

800-364-5483 / 918-683-9514

#### MCL71 SERIES Low Profile LED Marker/ Clearance Light

- Chrome plated housing, replaceable lens
- Includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RE	ED - 2 DIODES	
MCL71RB	MCL71RBP	Flush mount marker light	20
FMVSS	P2		
MATERIALS	Acrylic lens, chr	ome plated ABS bezel	
VOLT/AMP	12.8VDC - 0.054	4A	
WT/DIMS	.088 lbs. / 3.75"	x 2.25" x 1/2"	
WARRANTY	Lifetime LED Wa	arranty	

# 






#### MCL76 SERIES Sealed LED Surface Mount Marker/ Clearance Lights with Reflex

- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Lens with reflex eliminates need for a separate reflector
- Includes weathertight pigtail with both lead and ground wire


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	YELI	LOW - 4 DIODES	
MCL76AB	MCL76ABP	Light with reflex	20
	RE	ED - 4 DIODES	
MCL76RB	MCL76RBP	Light with reflex	20
	. 50		
FMVSS	A P2		
MATERIALS	Polycarbonate le	ens and housing	
VOLT/AMP	12.8VDC - 0.063	BA	
WT/DIMS	.132 lbs. / 5.813	" x 2" x 1.188"	
WARRANTY	Lifetime LED Wa	arranty	
WARRANTY	Lifetime LED Wa	arranty	







MCL76RB



tronics.


123

www.optronicsinc.com





MCL85AB



#### MCL85 SERIES Sealed LED Surface Mount Amber Marker/Clearance Light

- Sonically sealed, waterproof
- Surface mount, mounts on 2-3/4" centers
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	YELI	LOW - 3 DIODES		
MCL85AB	MCL85ABP	Surface mount light	50	
		000		
			177	
FMVSS	P2 P3			
MATERIALS	Polycarbonate le	ens and housing		
VOLT/AMP	12.8VDC - 0.066	6A		
WT/DIMS	.044 lbs. / 3.188	" x 1.063" x 1.188"		






MCL81AB



MCL81RB



124 GPtronic

#### MCL81 SERIES Chrome Plated LED Marker/Clearance Lights

Lifetime LED Warranty



Chrome plated ABS housing

WARRANTY

• Includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY			
YELLOW - 6 DIODES						
MCL81AB	MCL81ABP	Light with ABS housing	20			
	F	ED - 6 DIODES				
MCL81RB	MCL81RBP	Light with ABS housing	20			
FMVSS	P2 PC					

FMVSS	P2 PC
MATERIALS	Acrylic lens, chrome plated ABS bezel
VOLT/AMP	12.8VDC - 0.153A
WT/DIMS	.265 lbs. / 4.781" x 2.125" x 1.375"
WARRANTY	Lifetime LED Warranty

#### MCL86 SERIES Armored Die Cast LED Marker/Clearance Lights

- Die cast steel housing, mounting gasket
- Surface mount, mounts on 3-7/8" centers
- Two-wire design with power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	• • •
	YEL	LOW - 6 DIODES		MCL86RB
MCL86AB	MCL86ABP	Light with steel housing	20	
	RI	ED - 6 DIODES		
MCL86RB	MCL86RBP	Light with steel housing	20	3 7/8"
				↑ OII 1 3/16"
FMVSS	P2 PC			2"
MATERIALS	Acrylic lens, ste	el housing		
VOLT/AMP	12.8VDC - 0.20	A		1 1/2"
WT/DIMS	.463 lbs. / 4.5" x	x 2.25" x 1.5"		
WARRANTY	Lifetime LED W	arranty		4 1/2"

C Rated

## MCL95 SERIES Sealed Stud Mount LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY				
YELLOW - 3 DIODES							
MCL95AB	MCL95ABP	1-wire, 20" lead	50				
MCL95ABF	MCL95ABFP	2-wire, 5mm female barrels	50				
	RE	ED - 3 DIODES					
MCL95RB	MCL95RBP	1-wire, 20" lead	50				
MCL95RBF	MCL95RBFP	2-wire, 5mm female barrels	50				
		RETAIL					
MCL95AS	Retail Ready	Yellow, clam	12				
MCL95RS		Red, clam	12				
FMVSS	FMVSS P2 P3						
MATERIALS	•						
VOLT/AMP	12.8VDC - 0.051A						
WT/DIMS	.088 lbs. / 2.125" x 1.125" x 1.063"						
WARRANTY	Lifetime LED Warranty						




Gotr


ONIC

MCL86AB

















CBL22 SERIES
Sealed LED Triangular
Cab/Clearance Light



- Sonically sealed, waterproof
  - Design includes lead and ground wire
- Mounting gasket included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		
	YELL	OW - 15 DIODES			
CBL22AB	CBL22ABP	Cab light	50		
CBL22CAB	CBL22CABP	Cab light, clear lens	50		
	RE	D - 15 DIODES			
CBL22RB	CBL22RBP	Cab light	50		
		RETAIL			
CBL22AS	RetailReady	Yellow cab light, clam	12		
FMVSS	P2 PC				
MATERIALS Polycarbonate lens and housing					
VOLT/AMP 12.8VDC - 0.107A					
WT/DIMS	DIMS .176 lbs. / 3.5" x 2.75" x 1.688"				
WARRANTY Lifetime LED Warranty					

SURFACE MOUNT LED MARKER/CLEARANCE LIGHTS



#### MCL70 SERIES Sealed LED Identification Light Bars for Over 80" Applications



MCL70RB

## Sonically sealed, waterproof Ultra thin – only 5/8" thick

Design includes both lead
 and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		MCL70RCE
	RED ID LI	GHT BAR - 3 DIODES			
MCL70RB	MCL70RBP	ID light bar	10		
MCL70RBF2	MCL70RBF2P	ID light bar, .180 female barrels	10		
MCL70RCB	MCL70RCBP	ID light bar, clear lens	10		
	Α	CCESSORIES			
A69CB	A69CBP	Chrome base/bezel	10		
A69GB	A69GBP	Mounting gasket, black	10		
		RETAIL			
MCL70RS	Retail Ready	Red, clam	20		1.61
510/00	<b>D</b> 0				3/8
FMVSS	P2			14 1/8"	
MATERIALS Polycarbonate lens and housing		6		6	
VOLT/AMP 12.8VDC - 0.038A				10	
WT/DIMS .441 lb. / 15" x 1.375" x .625"		-		5/8	
WARRANTY Lifetime LED Warranty			15"		
		-			

#### MCL78/88 SERIES Sealed LED Identification Light Bars for Over 80" Applications



8 8 8 8 8 8 8 8 8 8 8


MCL78RB

MCL88RCB

- Sonically sealed, waterproof
- Ultra thin only 1" thick
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY				
RED ID LIGHT BAR - 3 DIODES							
MCL78RB	MCL78RBP	ID light bar	10				
MCL88RCB	MCL88RCBP	ID light bar, clear lens	10				
	Α	CCESSORIES					
A79CB	A79CBP	Chrome base/bezel	10				
FMVSS		6					
MATERIALS Polycarbonate lens and housing				4			
VOLT/AMP							
WT/DIMS .441 lb. / 17" x 1.375" x 1"							
WARRANTY Lifetime LED Warranty							





**ONIC**S



FLEET COUNT	MCL83 SERIES FLEET Count <sup>™</sup> Sealed LED Identification Light Bar for Over 80" Applications				
	I • I •		<ul> <li>Sonically sealed, wa lights snap onto corr proof polycarbonate</li> <li>Design includes both and ground wire</li> </ul>	osion base	
MCL83RCB	BULK P/N	POLYPACK P	/N DESCRIPTION	QTY	
		RED ID	LIGHT BAR - 3 DIODES		
	MCL83RB	MCL83RBP	3-LED ID light bar	10	
	MCL83RCB	MCL83RCBF	P Clear lens, red diodes	10	
	AL90RB	AL90RBP	1-LED replacement light	50	
		Retail Ready	RETAIL		
	MCL83RK		3-LED ID light bar, slipover blister	6	
15 15/16*		FMVSS	P2		
	15/32"	MATERIALS VOLT/AMP	Polycarbonate lens and housing 12.8VDC069A		
	5/8*	WT/DIMS WARRANTY	.397 lb. / 15.938" x 1.469" x 1.625" Lifetime LED Warranty		



## MCL93 SERIES Sealed LED Identification Light Bar for Over 80" Applications



- Sonically sealed, waterproof lights snap onto corrosion proof polycarbonate base
- Design includes both lead and ground wire

	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RED ID LIGHT BAR - 9 DIODES		
	MCL93RB	MCL93RBP	9-LED ID light bar	10
	MCL93RPG	MCL93RPGP	9-LED ID light bar, .180 male bullet on power, eyelet on ground	10
	AL91RB	AL91RBP	3-LED replacement light	50
			RETAIL	
	MCL93RK	Retail Ready	9-LED ID light bar, slipover blister	6
15 15/16*			2	
	15/32"		Polycarbonate lens and housing	
			2.8VDC - 0.153A	
	5/8*		397 lb. / 15.938" x 1.469" x 1.625"	
· · · · · · · · · · · · · · · · · · ·		WARRANTY L	ifetime LED Warranty	



128 Optronics

#### MCL84 SERIES Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof lights snap onto stainless steel base
- Design includes both lead and ground wire

**BULK P/N** 


AL91RB

**FMVSS** 

VOLT/AMP

WT/DIMS

A TOTAL



## **MCL97 SERIES** Sealed LED Identification Light Bar for Over 80" Applications




- Sealed, waterproof lights on stainless steel base
- Single wire, grounds through mounting hardware



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 9 DIODES			
MCL97RB	MCL97RBP	9-LED ID light bar	10
MCL97RPG	MCL97RPGP	9-LED ID light bar, .180 male bullet	10
		RETAIL	
MCL97RK	Retail Ready	ID light bar, slipover blister	6
	•		
	20.02		

1 10 00	1210
MATERIALS	Polycarbonate light, stainless steel base
VOLT/AMP	12.8VDC153A
WT/DIMS	.287 lb. / 14.25" x 1.188" x 1.313"
WARRANTY	Lifetime LED Warranty



129



MCL84RB




#### MCL98 SERIES Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof
- Compact 14.25" x 1.125"
- Design includes both lead and ground wire

MCL98RB
---------

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED ID LI	GHT BAR - 3 DIODES	
MCL98RB	MCL98RBP	ID light bar	10
		RETAIL	
MCL98RK	Retail Ready	Light bar, slipover blister	6
FMVSS	P2		
MATERIALS	Polycarbonate le	ens and housing	
VOLT/AMP	12.8VDC - 0.020	A	
WT/DIMS	.243 lb. / 14.25"	x 1.125" x .875"	

Lifetime LED Warranty



WARRANTY





#### MCL1922 SERIES GloLight® Sealed 3/4" LED Identification Lights for Over 80" Applications

GloLight

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
  Design includes both lead
- Design includes both lead and ground wire

and gro				MCL1922RB
BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	RED ID LIC	GHTS - 3 DIODES	in the second	
MCL1922RB	MCL1922RBP	ID light bar, molded black base	10	
MCL112RB	MCL112RBP	GloLight <sup>®</sup> replacement light	50	
FMVSS	P2			14 15/16"
MATERIALS	Polycarbonate lens a	nd housing		
VOLT/AMP	12.8VDC - 0.022A		0 0	(O)
WT/DIMS	MCL922RB: .441 lb	o. / 14.875" x 1.25" x 1"	-	an. an. 1.
WARRANTY	Lifetime LED Warran	ty	A.L.	MCL1922RB

#### MCL922 & MCL12/22 SERIES Sealed 3/4" LED Identification Lights for Over 80" Applications




MCL922RB

- Sonically sealed, waterproof
- Design includes both lead
   and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RED ID LIGHTS - 3 DIODES		
MCL922RB	MCL922RBP	ID light bar, molded black base	10
MCL12RK3B	MCL12RK3BP	(3) red MCL12 lights, molded harness	20
MCL12RK3RMB	-	(3) red MCL12 lights, molded harness, weathertight plug	50
MCL22RK3B	-	(3) red MCL12 lights, molded harness, supplemental turn function	50
MCL22RK4B	-	(3) red MCL12 lights, supplemental turn function, amp connector	20
MCL12RB	MCL12RBP	Single diode replacement light	50



FMVSS	P2			
MATERIALS	Polycarbonate lens and housing			
VOLT/AMP	12.8VDC - 0.022A			
WT/DIMS	MCL922RB: .441 lb. / 14.875" x 1.25" x 1"			
WARRANTY	Lifetime LED Warranty			





**LPL11 SERIES** 

Mini License Plate Light

Sonically sealed, waterproof

Easy snap-in mounting

Chrome-plated brass construction

Two-wire design includes both lead and

**Snap-In LED** 

ground wire

•









BULK P/N	POLYPACK P/	DESCRIPTION	QTY
	LICENSE	E LIGHT - 2 DIODES	
LPL11CB	LPL11CBP	Snap-in, license light	50
FMVSS MATERIALS	(2) L Polycarbona	te lens and brass housing	

MATERIALS	Polycarbonate lens and brass housing
VOLT/AMP	12.8VDC - 0.14A
WT/DIMS	.068lbs. / 1.5" x 1.5" x 1.125"
WARRANTY	Lifetime LED Warranty







LED LICENSE PLATE LIGHTS



800-364-5483 / 918-683-9514

#### **LPL12 SERIES** 3/4" Sealed LED License Light

- Sealed, waterproof ٠
- Meets SAE J587 when properly mounted using • brackets listed below
- Design includes both lead and ground wire

	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LICE	NSE LIGHT - 2 DIODES	
	LPL12CB	LPL12CBP	Light with .180 female barrels	20
	LPL12CPGB	LPL12CPGBP	Light with .180 male bullets	20
	LPL12CKM2B	LPL12CKM2BP	Kit: LPL12CPGB, A12B2LPB surface mount bracket, A12GLPB grommet	50
	LPL12CKMB	LPL12CKMBP	Kit: LPL12CPGB with A11BLPB bracket	20
	LPL12CKF2B	LPL12CKF2BP	Kit: LPL12CB, A12B2LPB surface mount bracket, A12GLPB grommet	50
	LPL12CKM5B	LPL12CKM5BP	Kit: LPL12CPGB, A12B2LPB surface mount bracket with gasket, A12GLPB grommet	50
			ACCESSORIES	
	A11BLPB	A11BLPBP	Black flush mount bracket	50
	A11GLPB	A11GLPBP	Gray flush mount bracket	50
	A12B2LPB	A12B2LPBP	Black vertical mount bracket	50
	A12GLPB	A12GLPBP	Grommet for A12B2LPB	50





LPL12CB

Kit with A12B2LPB bracket




13/8

ptronics)

133

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.11A
WT/DIMS	.022 lb. / 0.74" x 0.74" x .938"
WARRANTY	Lifetime LED Warranty




LPL12CB





LPL21CB



#### LPL21 SERIES LED Heavy Duty License Plate Light

- Armored light made of durable, chrome plated steel
- Surface mount on 2" centers
- Design includes both lead and ground wire

	BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LICENSE	LIGHT - 1 DIODE	
	LPL21CB	LPL21CBP	Armored license light	20
1211	FMVSS	L		
16"	MATERIALS	Steel, polycarbona	ate lens	
	VOLT/AMP	12.8VDC - 0.054A	L Contraction of the second	
	WT/DIMS	.132 lb. / 2.5" x 1.8	313" x 2"	
	WARRANTY	Lifetime LED Warr	anty	






LPL31CB



LPL31CSB



134 Optronics

#### LPL31 SERIES Mini LED License Light

- Polished, chrome plated housing
- Surface mount on 2" centers
- Design includes both lead and ground wire
- Two LPL31CB/CEZB required to meet DOT requirements, mounted on each side
- Single LPL31CSB required to meet DOT requirements, mounted at center


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LICENSE	LIGHT - 2 DIODES	
LPL31CB	LPL31CBP	License light	20
LPL31CEZB	LPL31CEZBP	License light, .180 female barrels	20
LPL31CPG	LP31CPGP	License light, .156 female barrels	20
LPL31CSB	LPL31CSBP	Light with spacer	50
	-	RETAIL	
LPL31CS	Retail Ready	Light with mounting hardware, clam	12
FMVSS MATERIALS VOLT/AMP WT/DIMS WARRANTY	(2) L Polycarbonate len 12.8VDC - 0.027A .066 lb. / 2.563" x Lifetime LED War	1.188" x .938"	

#### LPL41/43 SERIES Surface Mount LED License Light

- Armored housing
- Surface mount using ears or studs
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LICE	ENSE LIGHT	
LPL41CB	LPL41CBP	5-LED ear mount license light, chrome finish housing	20
LPL42CBF	LPL42CBFP	5-LED stud mount license light, chrome finish housing	20
LPL43CB	LPL43CBP	3-LED ear mount license light, stainless steel housing	20
FMVSS MATERIALS		s, chrome plated housing, stainless st L43 has stainless steel housing)	eel
VOLT/AMP WT/DIMS WARRANTY	12.8VDC - 0.054A .176 lb. / 4" x 1.75' Lifetime LED Warr		





## LPL55 SERIES LED License Light with Bracket

- Light attached to corrosion proof black bracket
- Surface mount on 3-1/4"
   centers

BULK P/N

LPL55CB

Design includes both lead
 and ground wire




 POLYPACK P/N
 DESCRIPTION
 QTY

 LICENSE LIGHT - 5 DIODES
 Light with ABS bracket
 10

 LPL55CBP
 Light with ABS bracket, female PL-10 plug
 10

		•	
LPL55CPG	LPL55CPGP	Light with ABS bracket, female PL-10 plug	10
LPL55CKB	LPL55CKBP	Light/bracket, gasket and hardware	10
LPL56CB	LPL56CBP	Light with steel bracket and gasket	10


FMVSS	L
MATERIALS	Polycarbonate lens and housing, plastic bracket
VOLT/AMP	12.8VDC - 0.045A
WT/DIMS	.198 lb. / 8.625" x 3.25" x 2.375"
WARRANTY	Lifetime LED Warranty







LPL61C24B



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LICENS	E LIGHT - 6 DIODES	
LPL61C24B	LPL61C24BP	LED license light, black housing, 12-24V	50
FMVSS	L		
MATERIALS	Polycarbonate		
VOLT/AMP	12.8VDC - 0.02	A	
WT/DIMS	.132 lb. / 3.55" x	x 1.2" x 1.82"	
WARRANTY	Lifetime LED Wa	arranty	





LPL65CB

#### LPL65 SERIES LED License Light

**LPL61 SERIES** 

•


**LED License Light** 

Sonically sealed, waterproof

Design includes both lead and ground wire

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LICENSE	E LIGHT - 3 DIODES	
LPL65CB	LPL65CBP	LED license light, gray housing	20



FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.052A
WT/DIMS	.089 lb. / 3.9" x 1.3" x 1.2"
WARRANTY	Lifetime LED Warranty



## LPL91 SERIES Sealed LED License Light

- · Sonically sealed, waterproof
- Use with LP25SB bracket and designated license plate brackets
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	LICENSE	LIGHT - 2 DIODES	
LPL91CB	LPL91CBP	License light	50
LPL91CAB	LPL91CABP	License light, .156 female plugs	50
LPL91CPG	LPL91CPGP	License light, female PL-10 connector	50
LPL91CKB	LPL91CKBP	License light, A91OB chrome base	50
LPL91CBKB	LPL91CBKBP	License light, A91BOB black base	50
LPL91CKALPB	LPL91CKALPBP	License light, .150 female barrels, black light bracket, gasket	50
LPL26SKB	LPL26SKBP	License light, .180 male bullets, gray light bracket	50
	LICENSE I	PLATE BRACKETS	
LP25SB	LP25SBP	Bracket, black coated	100
LP25SGGB	LP25SGGBP	Bracket, gray coated	
LP5SB	LP5SBP	Straight license plate bracket	100
LP15SB	LP15SBP	Zinc license plate bracket	12
LP35BB	LP35BBP	License plate holder	25
	AC	CESSORIES	
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A910BP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100






LPL91



LPL26SKB









LPL91

**Gotronics** 137





www.optronicsinc.com





BUL13CB



#### **BUL13 SERIES** 4" Round Sealed LED Utility Light


- Miro-Flex<sup>™</sup> design with Crystal Clear<sup>™</sup> lens
- Sonically sealed, waterproof
- Accepts standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
UTILITY LIGHT - 12 DIODES				
BUL13CB	BUL13CBP	Utility light	10	
	AC	CESSORIES		
A45GB	A45GBP	Grommet	50	
A45CB	A45CBP	Pigtail, 2-wire	100	
A49PB	A49PBP	Right angle pigtail, 2-wire	100	
MATERIALS	Polycarbonate len	s and housing		
VOLT/AMP	12.8VDC - 0.074A			
WT/DIMS	.331 lb. / 4.313" x	4.313" x 2.375"		
WARRANTY	Lifetime LED Warr	anty		
		•		





BUL43CB



138 **GPLIC** 

#### BUL43 SERIES 4" Round Sealed LED Utility Light

• Crystal Clear<sup>™</sup> lens

WARRANTY

- Sonically sealed, waterproof
- Accepts standard two-pin plugs

Lifetime LED Warranty

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	UTILITY L	IGHT - 10 DIODES		
BUL43CB	BUL43CBP	Utility light	10	
BUL43CBK	BUL43CBKP	Kit with A45GB grommet and A45CB pigtail	10	
	AC	CESSORIES		
A45GB	A45GBP	Grommet	50	
A45CB	A45CBP	Pigtail, 2-wire	100	
A49PB	A49PBP	Right angle pigtail, 2-wire	100	
MATERIALS	Polycarbonate len	s and housing		
VOLT/AMP	12.8VDC - 0.275A			
WT/DIMS	.529 lb. / 4.313" x 4.313" x 1.938"			

800-364-5483 / 918-683-9514

Sealed LED Thinline Utility Light	
<ul> <li>Sonically sealed, waterproof</li> <li>Ultra thin – only 5/8" thick</li> <li>Design includes both lead and ground wire</li> </ul>	
BULK P/N POLYPACK P/N DESCRIPTION QTY	
UTILITY LIGHT - 11 DIODES	
BUL69CB BUL69CBP Utility light 10	
BUL69CPG BUL69CPGP Light with .180 male bullets 10	
BUL69CBMCV2B BUL69CBMCV2BP Kit: 2-wire female PL-3, A69CB base 10	
ACCESSORIES	
A69CB A69CBP Chrome base/bezel 10	
14 1/8"	
MATERIALS Polycarbonate lens and housing	÷
VOLT/AMP 12.8VDC - 0.025A 1 3	/8"
WT/DIMS .265 lb. / 15" x 1.375" x .625"	5/8"
WARRANTY Lifetime LED Warranty	- 100 A 1221

## **BUL72 SERIES** 6" Oval Sealed LED Utility Lights


- Crystal Clear<sup>™</sup> lens
- Sonically sealed, waterproof
- Accepts standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY	LIGHT - 10 DIODES	
BUL72CB	BUL72CBP	Utility light	10
BUL72CBGK	BUL72CBGKP	Utility light with A70GB grommet	50
BUL74CBK	BUL74CBKP	Utility light with A70GB & A49PB	50
	AC	CESSORIES	
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.080A
WT/DIMS	.529 lb. / 6.438" x 2.313" x 1.75"
WARRANTY	Lifetime LED Warranty



BUL72CB



**Optronics** 





## BUL73 SERIES

#### FLEET Count<sup>™</sup> 6" Oval Sealed LED Utility Light for Surface Mount

- Sonically sealed, waterproof
- Surface flange mount no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY	LIGHT - 6 DIODES	
BUL73CB	BUL73CBP	Utility light	10
	A	CCESSORIES	
A78CB	A78CBP	Chrome trim ring	25
MATERIALS	Polycarbonate le	ens and housing	
VOLT/AMP	12.8VDC - 0.054	4A	
WT/DIMS	.265 lb. / 7.563"	x 3.313" x .75"	
WARRANTY	Lifetime LED Wa	arranty	


## **BUL78 SERIES** 6" Oval Sealed LED Utility Light for Surface Mount

- Sonically sealed, waterproof
- Surface flange mount no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY	LIGHT - 10 DIODES	
BUL78CB	BUL78CBP	Utility light	10
BUL78CEZB	BUL78CEZBP	Utility light with 2-way female PL-3	10
BUL78C3MB	BUL78C3MBP	Utility light with 2-way female PL-3 plug, adhesive back	10
BUL28CLPB	BUL28CLPBP	Low profile utility light with 2-way female PL-3 connector and gasket	10
ACCESSORIES			
A78CB	A78CBP	Chrome trim ring	25
MATERIALS	Polycarbonate le	ns and housing	

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	BUL78: .265 lb. / 7.563" x 3.313" x .75"
	BUL28: .255 lb. / 7.50" x 3.313" x .5625"
WARRANTY	Lifetime LED Warranty


BUL73CB








BUL78CB





140 GDUONIC


#### UCL178 SERIES GloLight® 6" Oval Sealed LED Utility Light for Surface Mount PATENTED

**TECHNOLOGY** 

- Sonically sealed, waterproof
- Surface flange mount no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY LIG	HT - 22 DIODES	
UCL178RFP2E	3 UCL178RFP2BP	Utility light	10
	ACCE	SSORIES	
A7TRSSB	A7TRSSBP	Stainless steel trim ring	100
A78CB1	A78CB1P	Chrome trim ring	25
MATERIALS Volt/AMP Wt/Dims Warranty	Polycarbonate lens a 12.8VDC - 0.050A .265 lb. / 7.50" x 3.25 Lifetime LED Warran	5" x 1.25"	





## UCLO9 SERIES 3" Sealed LED Utility/Hitch Light for Surface Mount


- Designed to illuminate hitch area of trailer
- Sonically sealed, waterproof
- Flange surface mount no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	UTILIT	Y LIGHT - 9 DIODES		
UCL09CB	UCL09CBP	Utility light, 9 white LEDs	50	
UCL09CBB	UCL09CBBP	Utility light, 6 white, 3 blue LEDs, 3-wire	50	
ACCESSORIES				
A09BB	A09BBP	Black snap-on trim ring	50	
A09CB	A09CBP	Chrome snap-on trim ring	50	
A09WB	A09WBP	White snap-on trim ring	50	

MATERIALS	Polycarbonate lens and housing		
VOLT/AMP	UCL09CB:	12.8VDC - 0.074A	
	UCL09CBB:	12.8VDC - 0114A	
WT/DIMS	.265 lb. / 3.25'	' x 3.25" x .813"	
WARRANTY	Lifetime LED Warranty		








NICS





UCL11CKB



#### UCL11 SERIES 3/4" Sealed LED Utility Light

- Sealed, waterproof
- Compact fits 3/4" hole
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY		
	UTILITY LIGHT - 2 DIODES				
UCL11CB	UCL11CBP	Utility light	50		
UCL11CKB	UCL11CKBP	Kit: UCL11CB & A11GB grommet	50		
UCL11CKPG	UCL11CKPGP	Kit: UCL11CB with .180 male bullets & A14GB grommet	50		
ACCESSORIES					
A11GB	A11GBP	Grommet	100		
A14GB	A14GBP	Sealing grommet, .125250" material	100		
A11PB	A11PBP	Snap-in mounting flange	100		
MATERIALS	Polycarbonate le	ens and housing			
VOLT/AMP	12.8VDC - 0.054	A			






UCL13C2PG



UCL13CB2B







142 **GPLIC** 

UCL13 SERIES Sealed LED Utility Light

• Sealed, waterproof

WT/DIMS

WARRANTY

- Compact, surface mount design
- Design includes both lead and ground wire


.265 lb. / 0.74" x 0.74" x 0.938"

Lifetime LED Warranty

POLYPACK P/N	DESCRIPTION	QTY
WHITE UTILIT	Y LIGHT - 2 DIODES	
UCL13C2PGP	Utility light, .180 female barrels	20
UCL13CPGP	Utility light, .156 male bullets	20
BLUE	- 2 DIODES	
UCL13CB2BP	Blue LED utility light	20
ACC	ESSORIES	
A13C2BP	Chrome base/bezel	100
A13B2BP	Black base/bezel	100
A13G2BP	Gasket	200
Polycarbonate lens	and housing	
12.8VDC - 0.020A		
.088 lb. / 2.5" x 1.00	63" x .688"	
Lifetime LED Warra	anty	
	WHITE UTILIT UCL13C2PGP UCL13CPGP BLUE UCL13CB2BP ACC A13C2BP A13B2BP A13B2BP A13G2BP Polycarbonate lens 12.8VDC - 0.020A .088 lb. / 2.5" x 1.0	WHITE UTILITY LIGHT - 2 DIODESUCL13C2PGPUtility light, .180 female barrelsUCL13CPGPUtility light, .156 male bulletsBLUE - 2 DIODESUCL13CB2BPBlue LED utility lightACCESSORIESA13C2BPChrome base/bezelA13B2BPBlack base/bezelA13G2BPGasketPolycarbonate lens and housing

#### UCL19 SERIES Miro-Flex<sup>™</sup> Sealed LED Utility Light

- Sealed, waterproof
- Surface mount, mounts on 4-5/8" centers
- · Design includes both lead and ground wire









## UCL50 SERIES Miro-Flex<sup>™</sup> 2" Sealed LED Utility Light




- Miro-Flex<sup>™</sup> design with Crystal Clear<sup>™</sup> lens
- Operating voltage 12-24VDC
- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY	' LIGHT - 9 DIODES	
UCL50CB	UCL50CBP	12-24VDC Utility light	20
	A	CCESSORIES	
A46PB	A46PBP	Straight plug, 6" lead	100
A86PB	A86PBP	Straight plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

Polycarbonate lens and housing
12.8VDC - 0.013A
.088 lb. / 2" x 2" x 1.188"
Lifetime LED Warranty







otronics.





UCL55CB

2'

#### **UCL55 SERIES** 2" Sealed LED Utility Light


- Sonically sealed, waterproof .
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILITY	LIGHT - 3 DIODES	
UCL55CB	UCL55CBP	Utility light	20
	A	CCESSORIES	
A46PB	A46PBP	Straight plug, 6" lead	100
A86PB	A86PBP	Straight plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
MATERIALS	Polycarbonate l	ens and housing	
VOLT/AMP	12.8VDC - 0.04	7A	
WT/DIMS	.088 lb. / 2" x 2"	x 1"	
WARRANTY	Lifetime LED W	arranty	





UCL65CB



144 0





WARRANTY

**UCL65 SERIES** Sealed LED Thinline Utility Light •

- Sealed, waterproof
- Multiple mounting and wiring options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	UTILI	TY LIGHT - 6 DIODES	
UCL65CB	UCL65CBP	Utility light	20
		ACCESSORIES	
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
		on mounting and wiring accessories,	
	see Access	ories section at back of catalog.	
MATERIALS	Polycarbonat	a long and housing	
VOLT/AMP	Polycarbonate lens and housing		
WT/DIMS	12.8VDC - 0.048A		
WI/DIWS	.066 lb. / 3.875" x 1.25" x 1.125"		

Lifetime LED Warranty

800-364-5483 / 918-683-9514

#### UCL60/160 SERIES Sealed LED Utility Light


- Sealed, waterproof
- Compact, surface mount design
- Design includes both lead and ground wire
- CSA certified for use in sleeping quarters
- Snap-on trim ring included, multiple finishes available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
то	UCH SWITCH (	JTILITY LIGHT - 6 DIODES	
UCL60CSBB	UCL60CSBBP	Utility light, black trim ring	20
UCL60CSNB	UCL60CSNBP	Utility light, brushed nickel trim ring	20
UCL60CSWNB	UCL60CSWNBP	Utility light, warm white LED, brushed nickel trim ring	20
ι	JTILITY LIGHT,	NO SWITCH - 6 DIODES	
UCL60CB	UCL60CBP	Utility light, chrome trim ring	20
UCL60CSCB	-	Utility light, chrome trim ring, Delphi connector	20
UCL60CBB	UCL60CBBP	Utility light, black trim ring	20

Raw lumen output:	224 lm
Effective lumen output:	168 lm

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	GLOLIGHT <sup>™</sup> U	TILITY LIGHT - 6 DIODES	
UCL160CB	UCL160CBP	Utility light, chrome trim ring	20
	imen output: ve lumen outp	224 lm out: 168 lm	

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.020A
WT/DIMS	.088 lb. / 3" x 3" x .375"
WARRANTY	Lifetime LED Warranty















otronics.

#### **ILLO1 SERIES** 3/4" LED Emergency Egress Light 3/4" recess mount light for use in transit vehicles Hard wired, includes lead and ground with female Staykon connectors Sealed, waterproof construction - maintenance free Snap-in design for quick and easy installation LLO1RB **BULK P/N BOX/UPC P/N** DESCRIPTION QTY **EGRESS LIGHT - 1 DIODE** ILL01RB ILL01RBP 3/4" egress light 50 MATERIALS Polycarbonate lens and housing VOLT/AMP 12.8VDC - .1A 9/16 13/16 WT/DIMS 0.018 lb. / .695" x .695" x .81"

Ø-11/16

1/2" 19/32"





ILL06COB



A06TR


## ILLO6/07 SERIES Opti-Brite<sup>™</sup> LED Mini Dome Light

WARRANTY

Lifetime LED Warranty

- Compact 11-inch dome light fits many applications
- Design includes 6-inch, 16-gauge power and ground wires with tinned ends
- Available with neutral white or cool white LEDs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	COOL WHIT	TE - 16 DIODES		
ILL06COB	ILL06COBP	Dome light, white trim ring	12	
ILL06COPG	ILL06COPGP	Dome light, .180 bullets, white trim ring	12	
	NEUTRAL WH	HITE - 16 DIODES		
ILL07COB	ILL07COBP	Neutral white LEDs	12	
ACCESSORIES				
A06TR	A06TRP	White trim ring	50	



Raw lumen output:		643 lm
Effective lumen output:		354 lm
MATERIALS VOLT/AMP WT/DIMS WARRANTY	Polycarbonate lens an 12.8VDC48A .05 lbs. / 11" x 4" x .94 Lifetime LED Warranty	n



146 Cotronics

#### ILLO8 SERIES Opti-Brite<sup>™</sup> LED Dome Lights

- Designed for use in extreme temperatures; ideal for refrigerated trucks and trailers (-40 to 140 degrees F)
- Operating voltage 7-30VDC; voltage cut-off at 7VDC prevents battery drain
- Use with both 12VDC and 24VDC systems; light output remains consistent at all operating voltages (no dimming), cutting off when voltage is outside range
- Design includes 16-inch, 16-gauge power and ground wires with tinned ends

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY		
DOME LIGHT - 8 DIODES					
ILL08COB	ILL08COBP	Light	6		
ILL08COPG	ILL08COPGP	Light, .180 male bullets,	6		
N	IOTION SEN	SOR DOME LIGHT - 8 DIODE	S		
ILL28CMB	ILL28CMBP	Light with motion sensor	6		
ILL28CMPG	ILL28CMPGP	Light with motion sensor, .180 male	bullets 6		
	men output ve lumen ou		2 3/16°		
MATERIALS	Polycarbonat	e lens and housing	- Le		

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.61A; 24VDC - 0.80A
WT/DIMS	1 lb. / 18.25" x 5.75" x 1.078"
WARRANTY	Lifetime LED Warranty

## 2 3/15 17 1/8 3/4<sup>-</sup> ILL08/28/10 SERIES DIMENSIONS

## ILL10 SERIES Opti-Brite<sup>™</sup> LED Dome Light

For 12VDC systems, general applications

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY
	DOME LIGH	T - 10 DIODES	
ILL10CCB	ILL10CCBP	11-16VDC Dome light	6
	men output: ve lumen out	1100 lm t <b>put:</b> 880 lm	
MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC - 1.8/ 1 lb. / 18.25" x	5.75" x 1.078"	
WARRANT	Lifetime LED W	Varianty	



optronics)

147





ILL28CMB

3/4

www.optronicsinc.com






ILL21CB

#### ILL21 SERIES Opti-Brite<sup>™</sup> LED 6" Dome Light

- Low profile dome light less than 5/8" thick
- Operating voltage 12-24VDC; use with both 12VDC and 24VDC systems
- Low voltage cut-off at 11VDC, prevents battery drain
- Sealed, waterproof

•

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME	LIGHT - 21 DIODES	
ILL21CB	ILL21CBP	Dome light, two-wire, .180 male bullets	10
ILL21CTPB	-	ILL21CB with adhesive mounting pad	10
A21CHB	-	Chrome trim ring	25




	nen output: e lumen output:	250 lm 214 lm	
MATERIALS VOLT/AMP WT/DIMS WARRANTY	Polycarbonate lens and l 12.8VDC408A; 24VD0 .250 lb. / 6.0938" x 6.093 Lifetime LED Warranty	C385A	





ILL39CB



148 **G** 

## ILL39 SERIES Opti-Brite<sup>™</sup> LED 7" Dome Light

- Low profile dome light less than 5/8" thick
- Operating voltage 12-24VDC; use with both 12VDC and 24VDC systems
- · Low voltage cut-off at 11VDC, prevents battery drain
- Hard wired design includes 16-gauge power and ground wires with .180 male bullets
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME	LIGHT - 39 DIODES	
ILL39CB	ILL39CBP	Dome light	5/10
	nen output: e lumen out	460 lm put: 390 lm	
MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC669/	ens and housing A; 24VDC217A x 6.969" x .625" arranty	

800-364-5483 / 918-683-9514

#### **ILL25/26 SERIES LED Low Profile Interior Lights**

#### PATENTED TECHNOLOGY

- Low profile dome lights •
- Surface mount .

WT/DIMS

WARRANTY

Hard wired design includes both lead and ground wire •

BULK P/N	POLYPACK P/N DOME	DESCRIPTION	QTY	
ILL25CB ILL25CBP Interior light, 3.5"			20	
Raw lumen output:400 lmEffective lumen output:260 lm				


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME I	LIGHT - 18 DIODES	
ILL26CB	ILL26CBP	Interior light, 4.5"	10
Raw Iu			
Effective lumen output: 390 lm			
MATERIALS	MATERIALS Polycarbonate lens and housing		
VOLT/AMP ILL25CB: 12.8VDC32A			

ILL26CB: 12.8VDC - .42A

Lifetime LED Warranty

ILL25CB: .097 lb. / 3.50" x 3.50" x .75" ILL26CB: .156 lb. / 4.50" x 4.50" x .875" 3.50\* 75" 562" ILL25CB

**GloLight** 



optronics)



Opti-Brit

ILL22CB

#### ILL22 SERIES Sealed LED Dome Lights

- Low profile dome lights only 1" thick
- Sealed, waterproof design
- Hard wired with 6" power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
	DOME	LIGHT - 18 DIODES	7	
ILL22CB	ILL22CBP	Dome light, on/off switch	10	
ILL22CHB	ILL22CHBP	Dome light, no switch	10	
Raw lu	imen output:	1044 lm		274
Effecti	ve lumen out	put: 810 lm		
				1
MATERIALC	Delveerbenetel	ana and hausing		

MATERIALSPolycarbonate lens and housingVOLT/AMP12.8VDC - .7AWT/DIMS.182 lb. / 4.5" x 2.875" x 1"WARRANTYLifetime LED Warranty

## ILL24 SERIES Sealed LED 6" Dome Light


- Low profile dome light only 7/8" thick
- · Sealed, waterproof
- Hard wired design includes power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME	LIGHT - 24 DIODES	\$
ILL24CB	ILL24CBP	Dome light	10
	men output: ve lumen out	585 lm <b>put:</b> 453 lm	
MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC127	x 6.125" x 0.875"	4 11/16 7/8"





ILL24CB



## ILL30CBB SERIES Constellation<sup>™</sup> LED Bullet Light

- Surface mount fixture; trim ring covers mounting hardware
- Ratchet motion design with on/off switch
- Lightly frosted lens
- Hard wired design includes power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	BULL	ET LIGHT - 1 DIODE	
ILL30CBB	ILL30CBBP	Bullet light	25
MATERIALS	Plastic housing	]	
VOLT/AMP	12.8VDC28	8A	
WT/DIMS	.250 lb. / 3.75"	x 1.938" x 3.5"	
WARRANTY	Lifetime LED V	Varranty	

## ILL31/32/35 SERIES LED Low Profile Dome Lights

- Low profile dome lights for semi-recess or surface mount
- Durable steel housing and replaceable polycarbonate lens
- Hard wired design includes power and ground wires
- Select from standard diode or SMD LED models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RE	ECESS MOUN	T DOME LIGHT - 10 DIODES	
ILL31CB	ILL31CBP	Standard LED	10
ILL35CB	-	SMD LED	10
SU	RFACE MOUN	T DOME LIGHT - 10 DIODES	
ILL32CB	ILL32CBP	SMD LED	10
ILL32CPG	-	SMD LED, .180 male bullets	10
Raw lur	men output:	70 lm	
Effectiv	ve lumen out	<b>put:</b> 53 lm	
MATERIALS VOLT/AMP WT/DIMS	12.8VDC024 ILL31/35: .243	ens, plated steel housing A Ib. / 5.75" x 2.75" x .938" Ib. / 5.75" x 2.75" x .75"	
WARRANTY	Lifetime LED W	arranty	






ILL30CBB





ILL31CB





ILL31/35 - recess mount



ILL32 - surface mount

**tro**nics

151



www.optronicsinc.com






ILL33CB

4.3/4

#### ILL33 SERIES Opti-Brite<sup>™</sup> LED Sealed Dome Light

- Low profile surface mount design less than 3/4" thick
- Hard wired design includes 18-gauge lead wires
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME	LIGHT - 10 DIODES	
ILL33CB	ILL33CBP	Dome light	10
Raw lu	men output:	210 lm	
Effecti	ve lumen out	<b>put:</b> 160 lm	
MATERIALS	Polycarbonate I	ens and housing	
VOLT/AMP	12.8VDC147	° °	
WT/DIMS	.154 lb. / 5.125"		
		ALLO ANO	



13/16\*






ILL36CB

## ILL36 SERIES Opti-Brite<sup>™</sup> LED Sealed Dome Light

- Low profile surface mount design less than 3/4" thick
- Sealed, waterproof
- Durable polycarbonate construction

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY	
DOME LIGHT - 9 DIODES				
ILL36CB	ILL36CBP	Dome light	10	
ILL36CPG	ILL36CPGP	Dome light, .180 male bullets	10	



Raw lu	men output:	400 lm
Effectiv	/e lumen output:	227 lm
MATERIALS	Polycarbonate lens and	housing
VOLT/AMP	12.8VDC33A	-
WT/DIMS	.154 lb. / 5.75" x 2.75" x	.688"
WARRANTY	Lifetime LED Warranty	

152 **Gptronic** 

#### ILL45 SERIES Opti-Brite<sup>™</sup> LED Interior Light

- Low profile surface mount design less than 1" thick
- Durable polycarbonate construction

BULK P/N ILL45CB	POLYPACK P/N INTERIOR ILL45CBP	DESCRIPTION LIGHT - 42 DIODES Interior light	<b>QTY</b> 50	
	men output: ve lumen outp	300 lm ut: 260 lm		ILL45CB
MATERIALS VOLT/AMP WT/DIMS WARRANTY	12.8VDC37A	25" x 4.625" x .79"		

## ILL46 SERIES Opti-Brite<sup>™</sup> Sealed LED Dome Light

- Low profile surface mount design less than 3/4" thick
- Sealed, waterproof
- Durable polycarbonate construction


BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DOME L	IGHT - 9 DIODES	
ILL46CB	ILL46CBP	Dome light	10
	nen output: e lumen outp	540 lm ut: 380 lm	
MATERIALS	Polycarbonate	lens and housing	
VOLT/AMP	12.8VDC33A		
WT/DIMS	.154 lbs. / 5.75	5" x 2.75" x .688"	
WARRANTY	Lifetime LED V	Varranty	



**Opti-Brite** 







**otronics**