

SpilKleen

DIVISION OF AGRA MAX INC.



Protect Our Environment

CYLINDER PRODUCTS & CABINETS

SPILKLEEN, A Div. Of AgraMax Inc.

2395 Drew Road, Unit 1

Mississauga, Ontario L5S 1A1

Toll Free: 1-877-455-5336 / Phone: (905) 293-9995

Fax: (905) 293-9996

4216 54th Avenue SE, Bays 3 & 4

Calgary, Alberta T2C 2E3

Toll Free: 1-877-455-5336 / Phone: (403) 236-0015

Fax: (403) 236-0016

www.spilkleen.com
sales@spilkleen.com

DECEMBER 2012

6-PACK CYLINDER RACK

Maximize floor space while eliminating clutter and safety hazards by properly storing your industrial cylinders. Efficiently sized to easily move through standard doorways. Forkliftable. Handles cylinders 3" to 10" diameter. Add optional lower strap to bottom for extra security - Part #: 7205-BK.

**Part #: 7202-YE,
6-Pack Cylinder Rack**

Dimensions: 48"L x 31"W x 41"H
Weight: 62 lbs
Load Bearing Capacity UDL: 1200 lbs.

**Part #: 7203-BK
6-Pack Ramp**

Dimensions: 46"L x 20"W x 6"H
Weight: 20 lbs.
Load Bearing Capacity UDL: 600 lbs.



Part #: 7204-BK - Caster Frame

Dimensions: 33.5"L x 31.5"W x 4.5"H, Weight: 49.5 lbs, Load Bearing Capacity UDL: 1200 lbs.

2 AND 4 CYLINDER POLY-STAND

Ideal for inexpensive wall-mounted storage. The 2 Cylinder Poly-Stand accommodates two cylinders with diameters of 3" to 12 3/8".

The 4 Cylinder Poly-Stand is forkliftable and floor mountable. Specially designed so even unbalanced loads can be moved with ease. Holds four cylinders up to 12 3/8" in diameter. Add optional lower strap (Part #: 7205-BK) for extra security.

**Part #: 7212-YE
2-Cylinder Poly Stand**

Dimensions: 28"L x 14"W x 30"H
Weight: 14 lbs
Load Bearing Capacity UDL: 400 lbs.

**Part #: 7213-YE
4-Cylinder Poly Stand**

Dimensions: 41"L x 29"W x 46"H
Weight: 55 lbs
Load Bearing Capacity UDL: 800 lbs.



SINGLE CYLINDER DOLLY

Half the size of the Dual-Cylinder Dolly. Designed for demanding industrial facilities or tough outdoor applications in which transport of a single cylinder is required.

Accommodates one cylinder, up to 12" in diameter.

Pneumatic wheels standard on 7301-BK-A to maximize maneuverability over rough terrain.

**Part #: 7301-BK
Single Cylinder Dolly HD**

Dimensions: 23.75"L x 23"W x 46"H
Weight: 31 lbs.

**Part #: 7301-BK-A
Single Cylinder Dolly HD ATD,**

Dimensions: 23.75"L x 23"W x 46"H
Weight: 35 lbs.



DUAL-CYLINDER DOLLY

The Dual Cylinder Dolly is designed to be a more functional, maneuverable and better balanced transporter for gas cylinder than conventional dollies or forklifts.

Ideal for industrial or construction operations, it accommodates any two cylinders each up to 12" in diameter. Lightweight and durable polyethylene construction and effective counter balancing makes it easy to handle with a minimum of physical effort.

Part #: 7302-BK

Weight: 61 lbs.

Dimensions: 37"L x 23.5"W x 45"H

Load Bearing Capacity UDL: 500 lbs.



UNIVERSAL CYLINDER BRACKET

Ideal for inexpensive wall mounted storage. For modular extendable flexibility, design your own configuration to hold one, two, three, or X amount of cylinders. Units link together to extend and customize the amount of cylinders needed. Attaches to any wall securely and easily and accommodates cylinders from 3" to 10" in diameter and saves space on any wall.

Part #: 7216-YE

Single, 15.13"L x 6.3"W x 3.3"H



FLAMMABLE LIQUID SAFETY CABINETS FOR FLAMMABLES IN SAFETY CANS

PRODUCT FEATURES:

- all welded double wall 18 gauge construction with 1-1/2" insulating air space
- 2" leakproof sill to contain leaks
- lockable flush mounted handle (gripper pad) with 2 keys
- doors have 3 point locking system and radius edges
- doors are double walled, 14 gauge outside & 18 gauge inside
- 4" heavy duty welded hinges with brass pins
- twin 2" flame arrester vents
- adjustable leveling feet
- powder coated yellow finish (see options)
- safety signage in large red letters
- galvanized steel shelves adjust on 2-1/2" centers
- grounding connector



Meets OSHA and NFPA code 30 & UFC 79 standards

Chemical storage maximum: Class I & II - 60 gallons, Class III - 120 gallons

Manual Close	Self-Close	Bi-Fold	Capacity	Dimensions	Doors	Shelves	FM	Manual Weight	Self-Close Weight	Bi-Fold Weight
FCF6M	FCF6S		6	22x23x18	1	1	N	110	130	
FCF12M	FCF12S		12	35x23x18	1	1	Y	140	160	
FCF18M	FCF18S		18	44x23x18	1	1	Y	170	190	
FCF24M	FCF24S		24	65x23x18	1	2	Y	234	254	
FCF40M	FCF40S		40	44x23x34	1	1	Y	270	290	
FCF22M	FCF22S		22	35x34x18	2	1	Y	170	190	
FCF28M	FCF28S		28	44x34x18	2	1	Y	220	240	
FCF30M	FCF30S	FCF30B	30	44x43x18	2	1	Y	240	260	270
FCF44M	FCF44S		44	65x34x18	2	2	Y	290	310	
FCF45M	FCF45S	FCF45B	45	65x43x18	2	2	Y	358	378	388
FCF60M	FCF60S	FCF60B	60	65x34x34	2	2	Y	430	450	460
FCF90M	FCF90S	FCF90B	90	65x43x34	2	2	Y	470	490	500
FCF120M			120	65x59x34	2	2	Y	540		
FCVC120M			120	COMBO UNIT		2	Y	540		

VERTICAL DRUM FLAMMABLE LIQUID SAFETY CABINETS

PRODUCT FEATURES:

Has all the same features as the Flammable Liquid Safety Cabinet but also comes complete with conveyor rollers for ease of drum entry and removal

Meets OSHA and NFPA code 30 & UFC 79 standards - FM approved



Manual Close	Self-Close	Capacity	Dimensions		Shelves	FM	Manual Weight	Self-Close Weight
FCV55M	FCV55S	1 x (55)	65x34x34	/w rollers	1	Y	366	564
FCV120M		2 x (55)	65x59x34	/w rollers	1	Y	544	



PAINT & INK SAFETY STORAGE CABINETS

PRODUCT FEATURES:

- all welded double wall 18 gauge construction with 1-1/2" insulating air space
- 2" leakproof sill to contain leaks
- lockable flush mounted handle (gripper pad) with 2 keys
- doors have 3 point locking system and radius edges
- doors are double walled, 14 gauge outside & 18 gauge inside
- 4" heavy duty welded hinges with brass pins
- twin 2" flame arrester vents - adjustable leveling feet
- standard powder coated red finish with safety signage in large red letters
- galvanized steel shelves adjust on 2-1/2" centers
- grounding connector



Meets OSHA and NFPA code 30 & UFC 79 standards

Chemical storage maximum: Class I & II - 60 gallons, Class III - 120 gallons

Manual Close	Self-Close	Bi-Fold	Capacity	Dimensions	Shelves	FM	Manual Weight	Self-Close Weight	Bi-Fold Weight
FCP12M	FCP12S		12	22x23x18	1	Y	120	140	
FCP18M	FCP18S		18	35x23x18	2	Y	150	170	
FCP24M	FCP24S		24	44x23x18	3	Y	180	200	
FCP36M	FCP36S		36	65x23x18	5	Y	240	260	
FCP48M	FCP48S	FCP48B	48	44x43x18	3	Y	268	286	296
FCP72M	FCP72S	FCP72B	72	65x43x18	5	Y	400	420	430
FCP96M	FCP96S	FCP96B	96	65x34x34	5	Y	472	492	502
FCP120M	FCP120S	FCP120B	120	65x43x34	5	Y	500	520	512

OXYGEN GAS VERTICAL SECURITY STORAGE CABINETS

PRODUCT FEATURES:

- lockable mesh doors with side bolt hasp (no lock)
- all welded - ready to use
- 13 gauge flattened mesh sides, 14 gauge top - 1 1/2" x 3/16" thick corner angles
- foot pads with pre-drilled holes - powder coated safety yellow
- safety signage in large red letters
- adjustable safety retention chains
- meets OSHA 1910



Manual Close	Capacity	Dimensions	Shelves	FM	Manual Weight
FCOG10S	10	70x33x38	0	Y	204
FCOG20S	10 to 20	70x60x38	0	Y	360

LIQUID PROPANE VERTICAL SECURITY STORAGE CABINETS

PRODUCT FEATURES:

- lockable mesh doors with side bolt hasp (no lock)
- all welded - ready to use
- 13 gauge flattened mesh sides, 14 gauge top - 1 1/2" x 3/16" thick corner angles
- foot pads with pre-drilled holes - powder coated safety yellow
- safety signage in large red letters - adjustable safety retention chains
- meets OSHA 1910



Manual Close	Capacity	Dimensions	Shelves	Manual Weight
FCLP2VS	2	35x18x30	1	170
FCLP4VS	4	35x30x30	1	
FCLP12VS	12	70x33x38	2	340
FCLPOG	COMBO	70x62x38	2	490



TOLL FREE
1-877-455-5336

PROTECT OUR ENVIRONMENT

Head Office

2395 Drew Road, Unit #1
Mississauga, Ontario L5S 1A1
Toll Free 1-877-455-5336
Phone (905) 293-9995
Fax (905) 293-9996

Calgary Warehouse

4216-54th Avenue SE, Bays 3 & 4
Calgary, Alberta T2C 2E3
Toll Free 1-877-455-5336
Phone (403) 236-0015
Fax (403) 236-0016

www.spilkleen.com
sales@spilkleen.com

COMPLIANCE: When it comes to handling, storing and disposing, you must comply with all local, provincial and federal regulations. Various fluids absorbed or contained may be hazardous or toxic. Dispose according to the relevant government regulations.

CAUTION: Flammable and other hazardous liquids, under certain conditions can spontaneously ignite. Ensure that all personnel handling these materials do so with caution and always wear protective clothing and respiratory devices.

It is the Purchaser's sole responsibility to conduct testing to establish the suitability of any product for Purchaser's intended use.

SpilKleen reserves the right to change, add to, and delete from its product line at any time without notice.